GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/NDZ/2018/ 1706

Dated :-- 7-1-18---

FIRE SAFETY CERTIFICATE

Certified that the M/s Gola Restaurant located at K-24, Connaught Place, New Delhi comprises of Ground + Mezzanine floor owned/occupied by M/s Gola Restaurant was granted FSC by this department vide letter No.F6/DFS/MS/EH/2015/NDZ/1024 dated 18/06/15. The premises was re-inspected by the officer concerned of this department on 09/07/18 in the presence of Mr. Mukesh and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building Group D with effect from 2017/18-for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -- 2017 1-8---- at New Delhi by.

Chief Fire Officer Delhi Fire Service

Copy to:-

1. The Medical Officer of Health, Health Department, Palika Kendra, New Delhi.

2. The Manager,

M/s Gola Restaurant at K-24, Connaught Place, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

I	1	V	S	P	E	C	T	I	O	1	1	R	E	P	0	R	

1. Name & address of the M/s Gola Restaurant at K-24, Connaught

Place, New Delhi

Assembly Building Group-D 2. Type of occupancy:-

Gr. + Mezzanine

3. Type of case:-Renewal

4. Details of previous FSC:-F6/DFS/MS/EH/2015/NDZ/1024 dated

18/06/15.

5. Fire safety directives No.-N/A

6. Date of inspection:-

09/07/18 7. Name of the inspecting officer:-Sh. Manoj Kumar Sharma (ADO/CC)

8. Name & designation of officer

from the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Mr. Mukesh

Old Heritage Bldg.

Nil dated 21/06/2018

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR					
1.	Access to Building								
	1) Road width	N/A	30 mtr.	N/A					
	2) Gate width	N/A	On Road	N/A					
	3)Width of internal road	N/A	N/A	N/A					
2.	Number, Width Type & Arr								
	A. Number of staircases								
	1. Upper floors	02 Nos.	02 Nos.	MR					
	2. Basements	N/A	N/A	N/A					
	B. Width of staircase								
	1. Upper floors	0.75 mtr.	02 Nos. 0.75	MR					
			mtr.						
	2. Basements	N/A	N/A	N/A					
	C. Protection of exits	N/A	N/A	N/A					
	1. Fire check door	N/A	N/A	N/A					
	2. Pressurization	N/A	N/A	N/A					
	D. No. of continuous	01	01	MR					
	staircase to terrace		(3, A,						
	E. Width of corridor	N/A	N/A	N/A					
	F. Door size	1.0 mtr.	1.0 mtr.	MR					
3.	Compartmentation								
	1) Fire check door	N/A	N/A	N/A					
	2) Sealing of electrical shafts	N/A	N/A	N/A					
	3) Fire rating of shaft door	N/A	N/A	N/A					
	4) Water curtain	N/A	N/A	N/A					
	5) Fire Dampers	N/A	N/A	N/A					
4.	Smoke Management System								
	1) Basements	30 ACPH	N/A	N/A					
	2) Upper floors	12 ACPH	Natural	MR					
5.	Fire Extinguishers								
	1) Total numbers	07 Nos.	07 Nos.	MR					
	2) Types	ABC & CO2	ABC & CO2	MR					
	3) ISI marking	Required	Provided	MR					

6.	First-Aid Hose Reel	N					
	1) Total number of eachfloor	01	01	MR			
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR			
	3) Nozzle diameter	05 mm	05 mm	MR			
7.	Automatic Fire Detection &	Alarming Syst	tem	1			
	1) Type of detectors	N/A	N/A	N/A			
	2) Location of main panel	N/A	N/A	N/A			
	3) Location of repeater panel	N/A	N/A	N/A			
	4) Alternate source of power	N/A	N/A	N/A			
	5) Hooter's Location	N/A	N/A	N/A			
8.	MOEFA	Required	Provided	MR			
9.	Public Address System	N/A	N/A	N/A			
10.	Automatic Sprinkler System						
	1) Basement	N/A	N/A	N/A			
	2) Upper floors Gr. + Mezz. floor	Required	Provided	MR			
	3) Sprinkler above false	N/A	N/A	N/A			
	ceiling						
11.	Internal Hydrants						
	1) Size of riser/down-comer	N/A	N/A	N/A			
	2) Number of hydrants per	N/A	N/A	N/A			
	floor						
	3) Hose box	N/A	N/A	N/A			
12.	Yard Hydrants						
	1) Total number of hydrants	N/A	N/A	N/A			
	2) Hose box	N/A	N/A	N/A			
13.	Pumping Arrangement						
	1) Ground level		2 2				
	a) Discharge of main	N/A	N/A	N/A			
	pump						
	b) Head of main pump	N/A	N/A	N/A			
	c) Number of main pun		N/A	N/A			
	d) Jockey pump out put		N/A	. N/A			
	e) Jockey pump head	N/A	N/A	N/A			
	f) Stand by pump outpu		N/A	N/A			
	g) Stand by pump head		N/A	N/A			
	h) Auto starting/Manua	I N/A	N/A	N/A			
	stopping						
	2) Terrace level						
	a) Discharge of pump	450 LPM	450 & 225 LPM				
	b) Head of pump	40 mtr.	40 mtr.	MR			
	c) Power supply	Required	Provided	MR			
4.4	d) Auto starting of pum		Provided	MR			
14.	Captive Water Storage for Fire Fighting						
	Under ground tank capacity	N/A	N/A	N/A			
	a) Draw-off connection	N/A	N/A	N/A			
				1.00			
	b) Fire service inlet	Required	Provided	MR			
	b) Fire service inlet c) Access to tank d) Over head tank capacity	Required N/A	Provided N/A	N/A			

15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	1		
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
5	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any: ABC & Co2	em for Protec	tion of special	MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/EH/2015/NDZ/1024 dated 18/06/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation:- ADO (CC)

Gual croping C FO miscell FTM.

1017/18/72 - C FO Miscell FTM.

f.T. Letter is put up for sig