GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/NDZ/2018/ [7]

Dated: 20/7/18

FIRE SAFETY CERTIFICATE

Certified that the M/s MGM Club Society located at 4643/1, Building No. 19, Ansari Road, Darya Ganj, New Delhi comprises of Basement + Ground + 05 Upper floor, owned/occupied by M/s MGM Club Society was granted FSC by this department vide letter No.F6/DFS/MS/2015/NDZ/670 dated 01/05/15. The premises was re-inspected by the officer concerned of this department on 02/07/18 in the presence of Mr. Anil Rathore (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules. 2010 and that the period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 2017 118----at New Delhi by.

(Vipin Kentar) Chief Fire officer Delhi Fire Service

Copy to:-

1. The Manager,
M/s MGM Club Society at 4643/1, Building No. 19, Ansari Road, Darya Ganj,
New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

4		PECTION REP					
1.	1. Name & address of the building M/s MGM Club Society at 4643/1,						
	Building No. 19, Ansari Road, Darya Ganj,						
2	New Delhi						
2.	Type of occupancy:- Mixed Business/Assembly Basement + Ground + 05 upper floors Renewal						
2							
4	 4. Details of previous FSC:- F6/DFS/MS/2015/NDZ/670 dated 01/05/15 5. Fire safety directives No Date of inspection:- Name of the inspecting officer:- Name & designation of officer 8. Name & designation of officer 						
5							
0.	from the building side:-		Rathore (Manager)				
9.	Year of construction:-	1989	(Manager)				
	Applicant's letter No:-		dated 25/06/2018				
	Tapphoenic S lotter 110	TVII diary (aleu 23/00/2018				
S.No.	Minimum Standards on fire	Existing	Provided at site	Remarks			
	Prevention and fire safety	Requirement	110 vided at Site	MR/NMR			
	U/R 33	BBL-1983	* .	TVIIC/TVIVIIC			
1.	Access to Building	-	-	_			
	1) Road width	06 mtr.	09 mtr.	MR			
	2) Gate width	N/A	N/A	N/A			
	3)Width of internal road	N/A	N/A	N/A			
2.	Number, Width Type & Ari			IN/A			
	A. Number of staircases	angement of E	AAIIS				
	1. Upper floors	02 No.	03 No.	MR			
	2. Basements	02 No.	02 No.	MR			
	B. Width of staircase	02 110.	02 110.	IVIK			
	1. Upper floors	1.25 mtr.	1.5 mtr. , 1.25	MR			
		1.23 11101.	mtr. & 1.20 mtr.	IVIIX			
	2. Basements	1.25 mtr.	1.25 mtr.	MR			
	C. Protection of exits	N/A	N/A	N/A			
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous	01	02	MR			
	staircase to terrace			TVIIC			
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size/ exit	1.0 mtr.	1.0 mtr.	MR			
3.	Compartmentation			1			
	1) Fire check door	Required	Provided at staircase of	MR			
	2) Sealing of electrical shafts	N/A	basement				
	3) Fire rating of shaft door	N/A	N/A N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
4.	Smoke Management System	1 1/ / 1	IN/A	N/A			
	1) Basements	30 ACPH	Exhaust fan	MD			
	2) Upper floors	12 ACPH	Natural Natural	MR			
5.	Fire Extinguishers	12 ACIII	ivaturar	MR			
constant	1) Total numbers	30 Nos.	30 Nos.	MD			
-	2) Types	ABC & CO2		MR			
	3) ISI marking	Required	ABC & CO2	MR			
	- / - / - / - / - / - / - / - / - / - /	required	Provided	MR			

	-						
6.	First-Aid Hose Reel		~				
	1) Total number of eachfloor	01	01	MR			
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR			
7	3) Nozzle diameter	05 mm	05 100 100	MR			
7.	Automatic Fire Detection & Alarming System						
	1) Type of detectors	Required	Provided	MR			
	2) Location of main panel	Gr. floor	Gr. floor	MR			
	3) Location of repeater panel	Gr. floor	Gr. floor	MR			
	4) Alternate source of power	Required	Provided	MR			
	5) Hooter's Location	N/A	N/A	N/A			
8.	MOEFA	Required	Provided				
9.	Public Address System	Required	Provided	MR			
10.	Automatic Sprinkler System Required Provided MR						
	1) Basement	Required	Provided	MD			
	2) Upper floors	Required	Provided	MR			
	3) Sprinkler above false	N/A	N/A	MR			
	ceiling		1 1/1	N/A			
11.	Internal Hydrants						
	1) Size of riser/down-comer	Required	Provided	MD			
	2) Number of hydrants per	01	01	MR			
	floor		V1	MR			
	3) Hose box	01	01	MD			
12.	Yard Hydrants		V1	MR			
	1) Total number of hydrants	N/A	N/A	NI/A			
	2) Hose box	N/A	N/A	N/A			
13.	Pumping Arrangement		1 1/7	N/A			
	1) Ground level		, B	-			
	a) Discharge of main	1620 LPM	1620 I DM	1/2			
	pump	1020 LFW	1620 LPM	MR			
	b) Head of main pump	70 mtr.	70 mtr.	MD			
	c) Number of main pum	p 01	01	MR			
	d) Jockey pump out put	180 LPM	180 LPM	MR			
	e) Jockey pump head	N/A	N/A	MR			
	f) Stand by pump output		70 mtr.	MR			
	g) Stand by pump head	1620 LPM	1620 LPM	MR			
	h) Auto starting/Manual	Required	Provided	MR			
	stopping	Required	Trovided	MR			
	2) Terrace level						
	a) Discharge of pump	900 LPM	900 LPM	MD			
	b) Head of pump	40 mtr.	40 mtr.	MR			
	c) Power supply	Required		MR			
	d) Auto starting of pump	Required	Provided	MR			
14.	Captive Water Storage for F	Gire Fighting	Provided	MR			
	1) Under ground tank	50,000 ltr.	50,000 1				
	capacity	50,000 Itr.	50,000 ltr.	MR			
	a) Draw-off connection	Required	Duari 1 1				
	b) Fire service inlet	Required	Provided	MR			
		required	Provided	MR			
	c) Access to tank	Dagwing 1	D • 1 1				
	c) Access to tank d) Over head tank capacity	Required 10,000 ltr.	Provided 25,000 ltr.	MR MR			

15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.		Trovided	IVIIC
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any: ABC & Co2			

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/2015/NDZ/670 dated 01/05/13 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

FI little is put up for sign