## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ /フュフ

Dated:

24/7/18

## FIRE SAFETY CERTIFICATE

Certified that M/s. Silver Stone guest house located at 13A/22, B.C. Marg, Karol Bagh, New Delhi- 110005, comprised of basement, ground plus three upper floors, using basement as hall/storage, ground floor as reception, lobby, office & shops, first, second & third floor each having 05 guest rooms respectively (total 15 guest rooms) and a pantry for staff in temporary shed on terrace, was granted FSC by this department vide letter No. F6/DFS/MS/GH/2015/NDZ/956 dated 09.06.2015. The premises was re-inspected by the officer concerned of this department on 19/07/2018 in presence of Sh. Bhupesh Pathak, manager and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 2010 and that the premises is fit for occupancy class residential (and subject from 2010 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on  $\frac{24/7/18}{}$  at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

## Copy to:-

- 1. Sh. Sanjeev Sapra (Owner), M/s. Silver Stone guest house, 13A/22, B.C. Marg, Karol Bagh, New Delhi-110005.
- 2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

## Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [ sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

1. Name & address of the building : M/s. Silver Stone guest house, 13A/22, B.C. Marg, Karol Bagh, New Delhi- 110005. 2. Type of Occupancy : Lodging House 3. Type of Case : Renewal 4. Details of previous NOC : F6/DFS/MS/GH/2015/NDZ/956 dated 09.06.2015 5. Fire Safety directives letter No : Nil 6. Date of inspection : 19.07.2018 7. Name of the Inspecting Officers : M.K. Chattopadhyay, DO(South West) 8. Name and designation of officers from the building side : Sh. Bhupesh Pathak, manager 9. Year of Construction : 2010-11 10. Applicant's letter No. : 3624/Addl. C.P./Lic (H) dated New Delhi the 25.05.2018 The said guest house is comprised of basement, ground plus three upper floors. S. Minimum Standards on fire Fire safety requirements as per Provided at site Remarks No. prevention and fire safety U/R 33 letter dt. 10.06.2015 MR/NMR 1 Access to building Road width Provided 06 mts MR Gate width 4.5mts Directly accessible from the road MR Width of internal road N/A N/A N/A 2 Number, Width, Type & Arrangement of Exits a. Number of staircases Upper Floors 01 01 MR being old case Basements 01 01 MR being old case b. Width of staircases Upper Floors 1.25 mts 1.30 mts MR being old case Basements Old case 1.10 mts. MR being old case c. Protection of exits Fire check door N/A N/A N/A Pressurization N/A N/A N/A e. No. of continuous staircases to terrace 01 01 MR g. Width of Corridor 1.0 mt. 1.30 mts MR h. Door Size 1.0 mt. 0.84 mts MR being old case Compartmentation. Fire check door N/A N/A N/A Sealing of electrical shafts N/A Sealed Fire Rating of shaft door N/A N/A N/A Water Curtain N/A N/A N/A Fire Dampers N/A N/A N/A Smoke Management System. Basements Exhaust fan provided 30 a/c per hour MR Upper floors 12 a/c per hour

3

4

5	Fire Extinguishers		2 111	MR			
	• Total numbers	14	Provided				
	• Types	CO <sub>2</sub> , ABC, WCO <sub>2</sub>	Provided	MR			
	IS marking	ISI marked	Provided	MR			
6	First-Aid Hose Reels.						
	Total numbers on each floor	01	Provided	MR			
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	Provided	MR			
	Nozzle diameter	5 mm	Provided	MR			
7	Automatic fire detection and alarming system.						
	Type of detectors	N/A	N/A	N/A			
	<ul> <li>Location of Main Panel</li> </ul>	N/A	N/A	N/A			
	Location of Repeater Panel	N/A	N/A	N/A			
	Alternate source of power	Required	Provided	MR			
	Hooters' Location	N/A	N/A	N/A			
0	MOFFA	Required	Provided	MR			
8	MOEFA  Diship Address System	Required	Provided	MR			
9	Tublic Address System.						
10	Automatic Sprinkler System.     Basement	N/A	Provided	Area less than 200 sq. mts.			
	A003, 14400 1 3 3 1 1		N/A	N/A			
	Upper Floor  Sprinkler shows folce seiling	N/A		N/A			
	Sprinkler above false ceiling     N/A     N/A     N/A						
11	Internal Hydrants	N/A	DT/A	N/A			
	Size of riser/down-comer	N/A	N/A	N/A			
	<ul> <li>Number of hydrants per floor</li> </ul>	N/A	N/A	N/A			
	Hose Box	14/71	N/A	IN/A			
12	Yard Hydrants.		N/A	N/A			
	<ul> <li>Total number of hydrants</li> </ul>	N/A	N/A	N/A			
	Hose Box	N/A	14/11				
13	Pumping Arrangements.						
	Ground Level						
	Discharge of main Pump	N/A	N/A	N/A			
	Head of Main pump	N/A	N/A	N/A			
	> Number of main pumps	N/A	. N/A	N/A			
	Jockey Pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	> Standby Pump out put	N/A	N/A	N/A			
	> Standby Pump Head	N/A	N/A	N/A			
	Auto Starting/ Manual stopp	oing N/A	N/A	N/A			
	> Pump House Access	N/A	N/A	N/A			
	Terrace level						
	Discharge of pump	450 LP	PM Provided	MR			
	> Head of the pump	30 mt	Duaridad	MR			
	> Power Supply	Requir	ed Provided	MR			

		MIO				
14	Captive Water Storage for fire fighting.					
	<ul> <li>Underground tank capacity</li> </ul>	N/A	N/A	N/A		
	Draw-off connection	N/A	N/A	N/A		
	Fire service inlet	N/A	N/A	N/A		
	Access to tank	N/A	N/A	N/A		
	Overhead Tank capacity	Old Case	Provided (4000 lts)	MR being old case		
15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.					
	Pressurization of Lift Shaft	N/A	N/A	N/A		
,	Pressurization of Lift lobby	N/A	N/A	N/A		
	Communication In lift Car	Required	Provided	MR		
	Fireman's Grounding Switch	Required	Provided	MR		
	Lift Signage	Required	Provided	MR		
17	Standby power supply	Required	Provided MR			
18 Refuge Area.						
	> Total Area	N/A	N/A	N/A		
	> Location	N/A	N/A	N/A		
19	19 Fire Control Room					
	Detector System Panel	N/A	N/A	N/A		
	Flow Switch Panel	N/A	N/A	N/A		
	PA System Panel	N/A	N/A	N/A		
	Battery backup	N/A	N/A	N/A		
	Building Floor Plans	N/A	N/A	N/A		
20	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	N/A		

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2015/NDZ/956 dated 09.06.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Ts put up for approval & signature please.

Signature of the Inspecting Officer M.K. **CHATTOPADHYAY** 

Div. Officer (South West)