GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 17 26

Dated:

24/07/18

FIRE SAFETY CERTIFICATE

Certified that M/s. Taksh Inn guest house located at 13A/26, WEA, Karol Bagh, New Delhi- 110005, comprised of basement, ground plus three upper floors, using basement- vacant, ground floor as reception, lobby, shops & 02 guest room, first, second & third floor each having 06 guest rooms respectively (total 20 guest rooms) and a pantry for staff on terrace, was granted FSC by this department vide letter No. F6/DFS/MS/GH/2015/SZ/983 dated 10.06.2015. The premises was reinspected by the officer concerned of this department on 19/07/2018 in presence of Sh. Umesh Singh, manager and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 21/18 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on _______at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

- 1. Sh. Heera Singh (Owner), M/s. Taksh Inn guest house, 14A/4, WEA, Karol Bagh, New Delhi-110005.
- 2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building : M/s. Taksh Inn guest house, 13A/26, WEA, Karol Bagh, New Delhi- 110005.

2. Type of Occupancy : Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/GH/2015/SZ/983 dated 10.06.2015

5. Fire Safety directives letter No : Nil

6. Date of inspection : 19.07.2018

7. Name of the Inspecting Officers : M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers from the building side : Sh. Umesh Singh, manager

9. Year of Construction : 2010-11

10. Applicant's letter No. : 3666/Addl. C.P./Lic (H) dated New Delhi the 25.05.2018

The said guest house is comprised of basement, ground plus three upper floors.

S. No.	1	Ainimum Standards on fire vention and fire safety U/R 33	Fire safety requirements as letter dt. 10.06.20	per 015	Provided at site	Remarks MR/NMR		
1	Acces	s to building						
	•	Road width	06 mts		Provided	MR		
	•	Gate width	4.5mts	Dire	ectly accessible from the road	MR		
	•	Width of internal road	N/A		N/A	N/A		
2	Numb							
	(nber of staircases	-		-	_		
	•	Upper Floors	01		01	MR being old case		
	•	Basements	02		02	MR		
	b. Wid	th of staircases	_			_		
	•	Upper Floors	Old case		1.32 mts	MR being old case		
	•	Basements	Old case		1.41, 1.22 mts.	MR being old case		
	c. Prot	ection of exits	-			-		
	•	Fire check door	N/A		N/A	N/A		
	•	Pressurization	N/A		N/A	N/A		
	e. No. c	of continuous staircases to terrace	01		01	MR		
	g. Wid	th of Corridor	Old case		2.42, 1.10 mts	MR		
	h. Door	Size	Old case		0.90 mts	MR being old case		
	Compa	artmentation.						
	•	Fire check door	N/A		N/A	N/A		
		Sealing of electrical shafts	N/A		Sealed	∞ ∞ ∞		
		Fire Rating of shaft door	N/A		N/A	N/A		
	•	Water Curtain	N/A		N/A	N/A		
	•	Fire Dampers	N/A		N/A	N/A		
	Smoke	moke Management System.						
	•	Basements	30 a/c per hour		Exhaust fan provided	MR		
	•	Upper floors	12 a/c per hour		Natural Ventilation	MR		

3	Fire Extinguishers		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					
	Total numbers	13	Provided	MR				
	• Types	CO ₂ , ABC, WCO ₂	Provided	MR				
	IS marking	ISI marked	Provided	MR				
6	First-Aid Hose Reels.							
	Total numbers on each floor	01	Provided	MR				
	 Length of hose reel hose 	30 m	Provided	MR				
	Nozzle diameter	5 mm	Provided	MR				
7	Automatic fire detection and alarming system.							
	Type of detectors	N/A	N/A	N/A				
	 Location of Main Panel 	N/A	N/A	N/A				
	Location of Repeater Panel	N/A	N/A	N/A				
	Alternate source of power	Required	Provided (D.G set 125 K)	VA) MR				
	Hooters' Location	N/A	N/A	N/A				
8	MOEFA	Required	Provided	MR				
9	Public Address System.	Required	Provided	MR				
10	Automatic Sprinkler System.							
-	Basement	N/A	Provided	Area less than 200 sq. mts.				
	Upper Floor	N/A	N/A	N/A				
	Sprinkler above false ceiling	N/A	N/A	N/A				
11	Internal Hydrants							
11	Size of riser/down-comer	N/A	N/A	N/A				
	 Number of hydrants per floor 	N/A	N/A	N/A				
	Hose Box	N/A	N/A	N/A				
12	Yard Hydrants.							
12	Total number of hydrants	N/A	N/A	N/A				
	Hose Box	N/A	N/A	N/A				
13	Pumping Arrangements.							
	Ground Level							
	Discharge of main Pump	N/A	N/A	N/A				
	> Head of Main pump	N/A	N/A	N/A				
	Number of main pumps	N/A	N/A	N/A				
	> Jockey Pump out put	N/A	N/A	N/A				
	> Jockey pump head	N/A	N/A	N/A				
	Standby Pump out put	N/A	N/A	N/A				
	> Standby Pump Head	N/A	N/A	N/A				
	Auto Starting/ Manual stoppi	ng N/A	N/A	N/A				
	> Pump House Access	N/A	N/A	N/A				
	Terrace level							
	Discharge of pump	450 LP	M Provided	MR				
	> Head of the pump	30 mt	D '1 1	MR				
	> Power Supply	Requir	20 1 1	MR				

- <u>-</u>		All .						
14	Capt	ive Water Storage for fire fighting	ng.					
		Underground tank capacity	N/A	N/A	N/A			
	>	Draw-off connection	N/A	N/A	N/A			
	>	Fire service inlet	N/A	Provided				
	-	Access to tank	N/A	N/A	N/A			
	0	Overhead Tank capacity	Old Case	Provided (5000 lts)	MR being old case			
15	Exit	Signage.	Required Provided		MR			
16	Provision of Lifts.							
	•	Pressurization of Lift Shaft	N/A	N/A	N/A			
	•	Pressurization of Lift lobby	N/A	N/A	N/A			
	•	Communication In lift Car	Required	Provided	MR			
1		Fireman's Grounding Switch	Required	Provided	MR			
	•	Lift Signage	Required	Provided	MR			
17	Stand	by power supply	Required	Provided	MR			
18								
	>	Total Area	N/A	N/A	N/A			
	>	Location	N/A	N/A	N/A			
19								
SERV		Detector System Panel	N/A	N/A	N/A			
X	[m]	Flow Switch Panel	N/A	N/A	N/A			
3) भार	18 ·	PA System Panel	N/A	N/A	N/A			
124	37.	Battery backup	Required	Provided	MR			
Fire C		Building Floor Plans	N/A	N/A	N/A			
20	Specia Protec	l Fire Protection Systems for tion of special Risks, if any:	N/A	N/A	N/A			

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2015/SZ/983 dated 10.06.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

720/20/500

Signature of the Inspecting Officer Name M.K. CHATTOPADHYAY Div. Officer (South West)

DCFO (SZ)

1652/2/fo/52 24/07/20/8 52/2

F1 by