GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE NEW DELHI- 110001

NO. F6/DFS/MS/GH/2018/SZ/ 1737

Dated: 25/7/18

FIRE SAFETY CERTIFICATE

Certified that the Mira International Guest House 103 Block-B, pocket- 10 Sector-13, Dwarka, New Delhi-110078, comprised of basement, ground Plus three upper floors, Ground floor (Reception, Office, Dining hall & Kitchen) at 1st floor (8 guest rooms) 2nd floor (8 guest rooms), 3rd floor (6 guest rooms) total 22 guest rooms owned / occupied by Mira International have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officers concerned of Fire Service on 20.7.2018 in the presence of Sh. Rakesh Tiwari (Manager) of the guest house and that the building is fit for occupancy class A-1 "Lodging or rooming building" (Total- Guest Rooms) with effect from... 2.5. 1.7... 1.2... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf.

Issued on ... 2.5. ... 1.9. ... at New Delhi by

(Vipin Kental)
Chief Fire Officer

Copy to:-

- 1. The Addl. Commissioner of Police (Lic.), st Floor Police Station Defence Colony, New Delhi
- 2. Mira International Guest House 103 Block-B, pocket- 10 Sector-13, Dwarka, New Delhi-110078,

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- ·3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

		Mire Intern	TION REF	et House) Plot No 103 F	3 Block Po	ocket-10, Sector
1	Name & address of the building	Mira International (Gust House) Plot No.103,B Block Pocket-10, Sector-13,Dwarka New Delhi -110078				
2	Type of Occupancy	Lodging or rooming "A-1"				
3	Type of case	New (bsaement+Ground plus three upper floors				
4	Details of previous NOC	Nil				
5	Fire safety directives letter No	BBL/NBC of India				
6	Date of inspection	20.7.2018				
7	Name of the inspecting Officers :	D.O M.K Chattopadhyay S.P. Bhardwaj (ADO Dwarka)				
8	Name and designation of officers from the building side	Sh.Rakesh Tiwari (Director)				
9	Year of construction	2015 Basement , Ground Plus Three Upper Floors (Ground floor & 2000) Reception + office+Dining hall+Kitchen, 1st floor & 2000 floor 8 Guest room each & 3rd Floor 6 Guest Rooms Too 22 Guest Rooms			1st floor & 2nd	
10	Applicant's letter No.	7.6.2018		• •		
S. NO.	Minimum Standards on fire prevention	UBBL/NBC Requirements		Provided at site		Remarks MR / NMR
5. NO.	and fire safety U/R 33					
1	Access to building					7
	1) Road width	18 Mtrs.		Provided		MR ·
	2) Gate width	4.5 Mtrs.		Direct Accessible From Road		MR
	3) Width of internal road	N/A		N/A		N/A
2	Number, width Type & arrangement of	exits				
	a. Number of staircases					
	1. Upper floors	One		Two	-	MR
	2. basements	Two		Provided		MR
	b. Width of staircase					
	1. Upper floors	1.25 Mtrs.		1.62, 1.25Mtrs.		MR
	2. basements	1.25 Mtrs. each		1.67 & 1.30 Mtrs.		MR
	c. Protection of exits					
	1. Fire check door	N/A		N/A		N/A
	2. Pressurization	N/A		N/A		N/A
	d. No. of continuous staircase t	Two		Two		MR
	e. Width of corridor	1.35 Mtr.		1.35 Mtr.		MR
	f. Door size	1.35 Mtrs	S.	1.35 Mtr.		MR
3	Compartmentation.				1	
	1. Fire check door	N/A		N/A		N/A
	2. Sealing of electrical shafts	Required		Sealed		MR
	3. Fire Rating of shaft door	N/A		N/A		N/A
	4. water curtain	N/A		N/A		N/A
	5. Fire dampers	N/A		N/A		N/A
4	Smoke Management system.					
	basement	30 a/c per hour 12 a/c per hour		Exhaust Fans Provid	ed	MR
				National Vantilation		- MB
	upper floors			Natural Ventilation		MR
5	Fire Extinguishers	1				IMP
	total numbers	2 Nos. Each Floor		12 Nos.		MR
	Types		CO2, ABC			MR
	ISI marking	Require	d	Provided		MR

6	First-Aid Hose Reels.		4	
	total numbers on each floor	One each floor	provided	MR
	Length of Hose reel hose	30 Mtr	provided	MR
	Nozzle Diameter	5 MM	provided	MR
7	Automatic fire detection and alarming	system		
	Type of detectors	N/A	Somke	N/A
	location of Main Panel	N/A	Ground Floor	N/A
	location of Repeater panel	N/A	N/A	N/A
	Alternate source of power	N/A	Battery back up	N/A
	hooter's location	N/A	N/A	N/A
8	MOEFA	Required	Provided	MR
9	Public Address System.	N/A	Provided	N/A
10	Automatic Sprinkler System.			Contraction
	basement	Required	Provided in Basement	MR
	upper floors	N/A	N/A	N/A
	sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants			
	Size of riser/down-corner	100 mm	Provided	MR
	Number of Hydrants per floor	One each floor	Provided	MR
	hose Box	Required	Provided	MR
12	Yard Hydrants.	T. Coquillou	Ţ. TOVIGOG	Tivii V
1.60	total number of hydrants	N/A	N/A	N/A
	hose box	N/A	N/A	N/A
13	Pumping arrangements	13//	114/7	IIIV
13	1. Ground level			
		NI/A	N1/0	NI/A
	a. Discharge of main Pump	N/A	N/A	N/A
	b.Head of main pump	N/A	N/A	N/A
	c.Number of main pumps	N/A	N/A	N/A
	d.jockey pump out put	N/A	N/A	N/A
	e.jockey pump head	N/A	N/A	N/A
	f. Standby Pump output	N/A	N/A	N/A
	g.Stanby Pump head	N/A	N/A	N/A
	h.Auto Starting/Manual stopping	N/A	N/A	N/A
	pump house access	N/A	N/A	N/A
	2.Terrace level			
	a. Discharge of pump	900 & 180 LPM	provided	MR
	b. head of the pump	40 Mtrs.	provided	MR
	c. Power supply	Required	Provided	MR
	d. Auto starting of pump	Required	Provided	MR
4.4				
14	Captive water storage for fire fighting	11/4	1	1
	Underground tank capacity Draw off connection	N/A	N/A	N/A
	a. Draw-off connection	N/A	N/A	N/A
	b. fire service inlet	N/A	N/A	N/A
	c.Access to tank	N/A	N/A	N/A
	Over head tank Capacity	15000 Ltrs.	15000 Ltrs.	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of lifts.			
	a. Pressurization of lift shaft	N/A	N/A	N/A
	b. pressurization of lift lobby	N/A	N/A	N/A
	c. communication in lift car	Required	Provided	MR
	d. Fireman's grounding switch	Required	Provided	MR
	e. Lift signage	Required	Provided	MR
17	Standby power supply	Required	DG Set 125 KVA	MR
18	Refuge Area.			
	total area		Not Required	
	location			1

ontrol room ector system Panel v switch Panel system Panel ter backup	N/A N/A	N/A	N/A
ector system Panel v switch Panel system Panel			N/A
v switch Panel system Panel			
system Panel		N/A	N/A
	N/A	N/A	N/A
ci baokap	N/A	N/A	N/A
ding floor plans	N/A	N/A	N/A
ial Fire Protection system			
ded near electric Panel ection systems provided in the	ne building were chec	ked and found functional a	MR at the time of inspection
	rules 35 of the Delhi	Fire Service Act 2007 & R	If fire safety requirements under ules 2010, is recommended. S.P. Bhardwaj ADO Dwarka
Fo (Sp) 18	Larp		
eto Sy	1=7107	14.	
		put-up of	Par your Cind
CFO (32/			Month Run ADOJAN
	l		CFO (32) m.scell 25/7.