## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI- 110001

NO. F6/DFS/MS/School/2018/SZ/ 1738

Dated: 25/7/18

## FIRE SAFETY CERTIFICATE

Certified that the N K Bagrodia Public School, located at Sector-IV, Dwarka, New Delhi-110078 comprised of basement, ground plus three upper floors was issued Fire Safety Certificate by this department vide letter no. F6/DFS/MS/School/2018/SZ/942 dated 7.5.2018. Management has constructed one more upper floor, now building is Comprised of basement, ground plus four upper floors & have complied with fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire service Rules, 2010 as verified by the officers concerned of fire service on 29.6.2018 in presence of Sh. M L Saran (Admin.) and that the premises/building is fit for occupancy class B "Educational building" with effect from...

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service

Copy to:-

1. The Joint Director (L&I) Bldg., DDA. Vikas Sadan INA, New Delhi.

2. The Deputy Director (Education), Govt. of NCT of Delhi, Old Secretariat, New Delhi-54.

3. Principal, N K Bagrodia Public School, Sector-IV, Dwarka, New Delhi-110078.

## **CONDITIONS**

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

1000 Dweller

<u> </u>		N.K. Bagdodia Public Scho 110078.	ol, Sector-4,	Dwarka, New D	elhi -	
	Type of Occupancy	Educational Building "B"	e ,			
3	Type of case	Addition of Floor / 4th floupper floors.	or (Now bas	ement ground p	lus four	
4	Details of previous NOC	F6/DFS/MS/School/2018/SZ/942 dated 7.5.2018 (Basement, G+3)				
5	Fire safety directives letter No	F6/DFS/MS/BP/2014/237	dated 1.9.2014			
	Date of inspection	29.06.2018		B	8	
6	Name of the inspecting Officers	DO M K Chattopadhyay A	DO S.P. Bha	ardwaj		
7	Name and designation of officers	Sh. M L Saran (Admn. Officer)				
8	from the building side	2003, 2017				
9	Year of construction		Cart /17	basement gro	ound plus	
10	Applicant's letter No.	NKBPS/DWK/Fire Safety Dated. 23.04.2018		four upper flo	ors.	
S. NO	. Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement/ letter dated 1.9.2014	Provide	04 4. 0	Remarks MR / NMR	
1	Access to building		D 11-4		MR	
	1) Road width	12 Milio.	Provided		MR	
	2) Gate width	4.0 1010	Provided			
	3) Width of internal road	6 Mtrs.	Provided		M/R	
2	Number, width Type & arrangement of	exits				
	a. Number of staircases	3 Nos.	6 Nos.		MR	
	<ol> <li>Upper floors</li> <li>basements</li> </ol>	2 Nos.	2 Nos.	:+	MR	
	b. Width of staircase					
a.	1. Upper floors	1.5 Mtrs.	1.50 x1,1.73 travel dista 100 Cms. up	<b>X 2 meets</b> <b>nce</b> (119 X 2 & o to 4 th floor) $\frac{7}{4}$	MR	
,	2. basements	1.5 Mtrs., 1.18 Mtr.	173, 118 Cn	ns. Mtrs.	MR being old case	
	c. Protection of exits					
	1. Fire check door	Required	Provided in	basement	MR	
	2. Pressurization	N/A	N/A		N/A	
	d. No. of continuous staircase t	4 Nos.	4 Nos.		MR	
	e. Width of corridor	1.50 Mtrs.	213, 297, &	192 Cms.	MR	
	f. Door size	1 Mtr.	108 Cms.		MR	
3	Compartmentation.				145	
	1. Fire check door	Required	Provided in	basement	MR	
	2. Sealing of electrical shafts	N/A	N/A		N/A N/A	
	3. Fire Rating of shaft door	N/A	N/A	e e	N/A	
	4. water curtain	N/A	N/A		N/A	
	5. Fire dampers	N/A	N/A		8	
4	Smoke Management system.  basement	20 ala chargo	Exhaust fa	n provided	MR	
	pasement	30 a/c charge 12/ac charge	Natural Ve	ntilation	_ MR	
	upper floors		Inatural ve	Hullauon	IVIEV	
5	Fire Extinguishers		Description		MR	
	total numbers	16 Nos. CO2 & ABC IS	Provided	2	MR	
	Types	Marked	TTOVICCO			
	JSI marking		ISI Marked		MR	

	i iist-Aid iiose ikeeis.	Service of the servic			
	total numbers on each floor	Two	Three	MR _	
	Length of Hose reel hose	30 m	Provided	MR	
	Nozzle Diameter	5 mm	Provided	MR	
7	Automatic fire detection and alarming	system	9		
	Type of detectors	N/A	N/A	N/A	
	location of Main Panel	N/A	N/A	N/A	
	location of Repeater panel	N/A	N/A	N/A	
	Alternate source of power	N/A	N/A	N/A	
	hooter's location	N/A	N/A	N/A	
8	MOEFA	Required	Provided	MR	
9	Public Address System.	Required	Provided	MR	
10	Automatic Sprinkler System.				
	basement	Required	Provided	MR	
	upper floors	N/A	N/A	N/A	
	sprinkler above false ceiling	N/A	N/A	N/A	
11	Internal Hydrants		, , , , , , , , , , , , , , , , , , ,		
	Size of riser/down-corner	100 mm	Provided	MR	
	Number of Hydrants per floor	Two	Three	MR	
	hose Box	Required	Provided	MR	
12	Yard Hydrants.		B G	*	
	total number of hydrants	N/A	One	N/A	
	hose box	N/A	Provided	N/A	
13	Pumping arrangements		8 1 8 1 8 1		
- 10	1. Ground level				
	a. Discharge of main Pump	N/A	N/A	N/A	
	b.Head of main pump	N/A	N/A	N/A	
	c.Number of main pumps	N/A	N/A	N/A	
	d.jockey pump out put	N/A	N/A	N/A	
	e.jockey pump head	N/A	N/A	N/A	
	f. Standby Pump output	N/A	N/A	N/A	
	g.Stanby Pump head	N/A	N/A	N/A	
	h.Auto Starting/Manual stopping	N/A	N/A	N/A	
	pump house access	N/A	N/A	N/A	
	2.Terrace level			2 -	
	a. Discharge of pump	1620 Lpm.	1620 Lpm.	MR	
	b. head of the pump	40 Mtrs.	40 Mtrs.	MR	
	c. Power supply	Required	Provided	MR	
	d. Auto starting of pump	Required	Provided	MR	
14	Captive water storage for fire fighting				
	Underground tank capacity	N/A	N/A	N/A	
	a. Draw-off connection	N/A	N/A	N/A	
	b. fire service inlet	N/A	N/A	MR	
	c.Access to tank	N/A	N/A	N/A	
	Over head tank Capacity	25000 Ltrs.	25000 Ltrs.	MR	
15	Exit Signage.	Required	Provided	MR	
16	Provision of lifts.		* * * .		
	a. Pressurization of lift shaft	N/A	N/A	N/A	
	b. pressurization of lift lobby	N/A	N/A	N/A	
	c. communication in lift car	N/A	N/A	N/A	
	d. Fireman's grounding switch	N/A	N/A	N/A	
	e. Lift signage	N/A	N/A	N/A	

47	04	Described	125 1010	MR
17	Standby power supply	Required	125 KVA	IVIR
6	Refuge Area.		Not Required	
	total area	3		
	location			
19	Fire control room		*	
	a. detector system Panel	N/A	N/A	N/A
	b. Flow switch Panel	N/A	N/A	N/A
	c. PA system Panel	Required	Provided	MR
	d. Batter backup	Required	Provided	MR
	e. Building floor plans	Required	Provided	MR
20	Special Fire Protection systems electric panel	for protection of specia	I risks, if any: CO2 fire ex	tinguisher provided ne
ortcom	protection systems provided in the buning vide letter no. F6/DFS/MS/Scho	ol/2017/SZ/3170 dated 29	.11.2017 found rectified.	
ortcom te:- Th rridoor eping		ol/2017/SZ/3170 dated 29 1.73 & 1.73 Mtrs. meet the e minimum standards on f	.11.2017 found rectified. travel distance & All stairca	ases are opening in op
ortcom te:- Th rridoor eping	ning vide letter no. F6/DFS/MS/Schonree Stairecases having width 1.50, 2 & not enclosure type. in view substantial compliance of the issuanc of FSC for Basement, Ground	ol/2017/SZ/3170 dated 29 1.73 & 1.73 Mtrs. meet the e minimum standards on f	.11.2017 found rectified. travel distance & All stairca ire prevention and fire safets recommended.	ases are opening in op
ortcom te:- Th rridoor eping	ning vide letter no. F6/DFS/MS/Schonree Stairecases having width 1.50, 2 & not enclosure type. in view substantial compliance of the issuanc of FSC for Basement, Ground	ol/2017/SZ/3170 dated 29 1.73 & 1.73 Mtrs. meet the e minimum standards on f nd plus four upper floors is	.11.2017 found rectified. travel distance & All stairca ire prevention and fire safets recommended.	ases are opening in op
ortcom te:- Th rridoor eping	ning vide letter no. F6/DFS/MS/Schonree Stairecases having width 1.50, as not enclosure type. In view substantial compliance of the issuanc of FSC for Basement, Ground Accordingly DMK Chattopadhyay	ol/2017/SZ/3170 dated 29 1.73 & 1.73 Mtrs. meet the e minimum standards on f nd plus four upper floors is	travel distance & All stairce ire prevention and fire safets recommended.  and signature please.  S.P. Bhardwaj	ases are opening in op

Go sof

PA speak We 2017

Defoste.

Sponen

1. F1 10. Ve