GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6 / DFS / MS / 2018 / W2 / 1754

Dated: 27 / 7 /2018

FIRE SAFETY CERTIFICATE

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 8. The basement is not allowed to use as undertaking given by the Management.

Issued on at New Delhi

Chief Fire Officer Ph:-011-23414250

Copy to:

 M/s Ganesh Diagnostic & Imaging Centre Pvt. Ltd, Pocket CS/OCF-7, Sec-08, Rohini, Delhi-110085.

INSPECTION REPORT

Name & address of the building: Ganesh Diagnostic & Imaging Centre Pvt. Ltd, Pocket-CS/

OCF-7, Sec-08, Rohini, Delhi-110085.

Type of Occupancy : Institutional (Basement+G+02 upper floors) Type of Case

: Renewal

4. Details of previous NOC : F.6/DFS/MS/09/168 dated 20.01.2009

5. Fire Safety directives letter No : F6/DFS/MS/2006/BP/2001 dated 10.08.2006

: 12.07.2018

7. Name of the Inspecting Officers: Rajesh Kumar /ADO (RN)

8. Name and designation of officers

from the building side : Dr. Ravin Sharma

9. Year of Construction

10. Applicant's letter No. : Nil Dairy No 7753 dated 23.05.2018

No	1	imum Standards on ention and fire safety U/R	fire 33	NBC Requirement	Provided at site	Remark MR/NM
1	Acces	ss to building				
	•	Road width				
				9m	13.5m	MR
	•	Gate width		4.5m	4.5m	
		W: 1/1 0:			1.5111	MR(old case
		Width of internal road		NA	NA	NA
	Numl	ber, Width, Type & Arrang				IVA
	a.	Number of staircases	eme	nt of Exits		
	•	Upper Floors				
	•	Basements		02	02	
	b.	Width of staircases		02	02	MR
	•	Upper Floors			02	MR
		Basements	2.0	m &1.50m	2.0 0 1.70	- 13
C.	. Prote	ection of exits		m &1.50m	2.0m &1.50m	MR
		Fire check door		201.30111	2.0m & 1.50m	MR
		Pressurization		Required		
d.	No.	of continuous staircases to		NA	Provided	MR
	terra	ce staircases to		01	NA	NA
e.	2	h of Corridor			01	MR
	Door			NA	NA	NA
				2m	2m	
Co	mpar	tmentation.				MR

- 1	• Fire check door			
	THE CHECK GOOT	Required in	Provided	MR
	 Sealing of electrical shafts 	basement		IVIIN
	 Fire Rating of shaft door 	Required	Provided	MR
	Water Curtain	NA	NA	NA
		NA	NA	
	Fire Dampers	NA	NA	NA NA
4	Smoke Management System.			INA
	 Basements 	30ACPH	2	
	• Upper floors		Exhaust Fan	MR
5		12ACPH	Natural	MR
	Fire Extinguishers			
	 Total numbers 	10nos	12	
	• Types		12nos	MR
		ABC/ Co2	ABC-12	MR
6	IS marking	Required	Provided	MR
6	First-Aid Hose Reels.			14110
	 Total numbers on each 	01nos	01nos) (D
	floor		OTHOS	MR
	 Length of hose reel hose 	30m	30m	MR
	Nozzle diameter	5mm	5mm	MR
7	Automatic fire detection and alarmi	na system		
	Type of detectors			
	Location of Main Panel	Required	Provided	MR
	Location of Repeater Panel	G.F	Provided	MR
	Alternate source of power	Required	Provided	MR
	Hooters' Location	Required	Provided	MR
	MOEFA	Required	Provided	MR
		Required	Provided	MR
)	Public Address System.	Required	Provided	MR.
	Automatic Sprinkler System.			
	• Basement	Required	Provided	
	• Upper Floor	NA		MR
	Sprinkler above false	-	NA	NA
	ceiling	NA	NA	NA
	Internal Hydrants			11

2.	• Size of riser/down-comer	100mm	Provided	MR
	 Number of hydrants per floor 	01 nos each	Provided	MR
	• Hose Box	01nos each	Provided	MR
12	Yard Hydrants.			
la)	Total number of hydrants	NA	NA	NA
	• Hose Box	NA	NA	NA
13	Pumping Arrangements.			
	➤ Ground Level			
	Discharge of main Pump	1620 lpm	1620 lpm	MR
	Head of Main pump	70m	70m	MR
	Number of main pumps	01	01	MR
	Jockey Pump out put	180 lpm	180 lpm	MR
	Jockey pump head	70m	70m	MR
	Standby Pump out put	1620 lpm	1620 lpm	MR
	> Standby Pump Head	NA	NA	NA
	➤ Auto Starting/ Manual	Required	Provided	MR
	stoppingPump House Access	Required	Provided	MR
	Terrace level		3	
	Terrace lever	NA	NA	NA
	Discharge of pump	NA	NA	NA
	Head of the pumpPower Supply	NA	NA	NA
	Auto Starting of pump	NA	NA	NA
4	Captive Water Storage for fire fighting.			
	Underground tank capacity	50,000ltrs	50,000ltrs	MR
	> Draw-off connection	Required	Provided	MR
	Fire service inlet	Required	Provided	MR
	Access to tank	Required	Provided	MR
	Overhead Tank capacity	10,000 ltrs	10,000 ltrs	MR
5	Exit Signage.	Required	Provided	MR
6	Provision of Lifts.			

+

	Pressurization of Lift Shaft	NA	NA	NA		
	Pressurization of Lift	NA	NA	NA		
	lobby	Required	Provided	MR		
	Communication In lift Car	Required	Provided	MR		
	Fireman's Grounding		¥			
	Switch	Required	Provided	MR		
	Lift Signage					
17	Standby power supply	Required	Provided	MR		
18	Refuge Area.					
	> Total Area	NA	NA	NA		
	> Location	NA	NA	NA		
19	Fire Control Room					
	Detector System Panel	NA	NA	NA		
	Flow Switch Panel	NA	NA	NA		
	PA System Panel	NA	NA	NA		
	Batter backup	NA	NA	NA		
	Building Floor Plans	NA	NA	NA		
20	Special Fire Protection Systems for Protection of special Risks, if any:	NA	NA	NA		

The fire protection systems provided in the building were tested/ checked randomly and found in working conditions at the time of inspection

Keeping in view of the satisfactory compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to issue FSC under Rule 35 of Delhi Fire Service Rules, 2010.

Signature of the Inspecting Officer

Name: - Rajesh Kumar Designation:- ADO/RN

As approved, f.f. tetter is putyle for your signature PI My