GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI . HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.F.6/DFS/MS/NDZ/DMRC/2018

Dated: 31/7/18

FIRE SAFETY CERTIFICATE

Certified that the M/s Staff Quarters, of DMRC, at Vinod Nagar, Delhi, building comprised of A - 1, block stilts plus ten upper floor, B - 1 block, stilt plus ten upper floors & A-2N & B-2N, stilt plus eleven upper floors & C - block stilts plus four upper floor, owned / occupied by DMRC. The building was inspected by the team of officers concerned of this department on 20/07/2018 in the presence of Sh. J. K. Jain (Assist. Manager) and others and found that the residential building have complied with the Fire prevention and Fire safety requirements in accordance with the rules. The Fire Safety Certificate under rule 35 unless renewed under rule 36 or sooner cancelled under Rule 40 and that the building is fit for occupancy Group "A" "Residential Building" with effect from .. 31/17/18....for a period of three years, subject to conditions printed overleaf.

Issued on at New Delhi by

(Vipin Kenta Chief Fire Officer Delh Fire Service

To:-

Sh. J. K. Jain (AM/Elect) Chief Project manager - 7, Opp. Frank Anthony Public School, Lala Lajpat Rai Marg, Lajpat Nagar-IV, New Delhi-110024

Copy lo:-

The Manager Metro Bhawan, Fire Brigade Lane, Barakhanmba Raod. New Delhi-110001

1. Name & address of the building: Staff Quarters, DMRC, Vinod Nagar, Delhi

2. Building is comprised of : A-1&B-1, block stilts + 10,A-1N, B-2N block stilt + 11 & C

block stilts + 4 upper floor. 3. Type of Occupancy : Residential Building,

4. Type of Case : New 5. Details of Previous FSC letter

6. Fire Safety direction letter no. : Directive no. F6/DFS/MS/BP/2016/184 dt.-04/08/16.*

7. Date of Inspection : 20/03/18.
8. Name of the Inspecting officers : DO Francis Brown & ADO R. K. Yadav

9. Name and designation of Officer

from the building side : Sh. J. K. Jain (Assist. Manager)

10. Year of Construction : 2015

11. Applicant's letter No DMRC/Elect/PH-III/SQ-VN/DFS/2018/67Dt 06/07/2018

NO.	Minimum Standards on fire prevention and fire safety U/R33	Requirement	Provided at Site	Remark MR/NMR			
1	Access to building						
	 Road width 	06 mtr	06 mtr	MR			
	 Gate width 	06 mtr	06 mtr	MR			
	 Width of internal road 	06 mtr	06 mtr	MR			
2	Number, Width, Type and Arrangement of Exits						
	a. Number of Staircases						
	 Upper Floor (each block) 	04 no.	04 no.	MR			
	 Basement 	N/A	N/A	N/A			
	b. Width of Staircases						
	 Upper Floor (each block) 	1.50 mtr	1.50 mtr each	MR			
	 Basement 	N/A	N/A	N/A			
	c. Protection of exits			1 1// 1			
8	 Fire check door 	Required	Provided	MR			
	 Pressurization 	Required	Provided	MR			
	d. No. of continuous staircases to terrace	All	. All	MR			
	e. Width of Corridor	1.80 mtr	1.00	110			
	f. Door Size	1.50 mtr	1.80 mtr	MR ·			
3	Compartmentation.	1.50 mtr	1.50 mtr	MR			
	Fire check door	Doguirod	D : I I				
	 Sealing of electrical shafts 	Required Required	Provided	MR			
	 Fire rating of shaft door 	N/A	Provided N/A	MR			
	Water curtain	ENTALA	PA/A-A	N/A			
	• Fire Dampers	N/A	N/A	N/A N/A			
1	Smoke Management System.	- 1477	TW/A	IVA			
	Basement	N/A	N/A	N/A			
	 Upper floor 	N/A	N/A	N/A			
). ·	Fire Extinguishers	1477	IVA	IV/A			
	 Total numbers of each floor 	06 nos.	06 nos.	MR			
	• types	ABC & Co2	ABC & Co2	MR			
	ISI marking	ISI marked	ISI marked	MR			

6	First-aid-Hose Reels.					
	Total numbers of each floor	03 nos	03 nos	MR		
	 Length of hose reel hose 	30 mtr	30 mtr	MR		
_	Nozzle diameter	05 mm	05 mm	MR		
7	Automatic fire detection and alarming system.					
	Type of detectors	N/A	N/A	N/A		
	 Location of main panel 	G. Floor	Provided	MR		
	 Location of repeater panel 	N/A	N/A	N/A		
	Alternate source of power	N/A	N/A	N/A		
	Hooter's location	N/A	N/A	N/A		
8	MOEFA	Required	Provided	MR		
9	Public address System.	Required	Provided	MR		
10	Automatic Sprinkler System.					
	Stilt floor	Required	Provided	MR		
	upper floor	N/A	N/A	N/A		
	sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants					
	 size of riser/down-comer 	100 mm	100 mm	MR-		
33	 Number of hydrants per floor 	03 nos	03 nos	MR		
	Hose Box each floor	03 nos.	03 nos.	MR		
12	Yard Hydrants.					
	 Total number of hydrants 	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
13	Pumping Arrangements.					
	Ground Level					
	Discharge of main Pump	2280 lpm	2280 lpm	MR		
	Head of Main Pump	80 mtr	80 mtr	MR		
	Number of main pumps	02 nos	02 nos	MR		
	Jockey pump out put	180 lpm	180 lpm	MR		
	> Jockey pump head	80 mtr	80 mtr	MR		
	> Standby pump out put	2280 lpm	2280 lpm	MR		
	> Standby pump Head	80 mtr	80 mtr	MR		
	> Auto Starting /Manual	Auto	Provided	MR		
	stopping	Auto	Flovided	IVIE		
	> Pump House Access	Required	Provided	MR		
	Terrace Level		1.1011404			
	Discharge of pump	900 lpm	900 lpm	MR		
-	➢ Head of the Pump	25 mtr	25 mtr	MR		
	Power supply	Required	Provided	MR		
V	Auto Starting of pump	Required	Provided	MR		
14	Captive Water Storage for Fire Fighting					
	 Underground tank capacity 	1,00,000 Ltrs	1,00,000 Ltrs	MR		
	Draw-off connection	Required	Provided	MR		
	Fire service inlet	Required	Provided	MR		
	Access to tank	Required	Provided	MR		
	 Overhead Tank capacity 	25,000 Ltrs. &	25,000 Ltrs.	MR		
	4.	10,000 Ltrs	& 10,000 Ltrs			
15	Exit Signage.	Required	Provided	MR		

16	Provision of Lifts.			
	Pressurization of Lift Shaft	Ventilated	Provided	MR
	 Pressurization of Lift lobby 	Required	Provided	MR
	Communication in lift car	Required	Provided	MR
	Firemen's grounding switch **	Required	Provided	MR
	 Lift Signage 	Required	Provided	MR
17	Standby power supply	Required	Provided	MR ·
18	Refuge Area.			
	Total area	N/A	N/A	N/A
	Location	N/A	N/A	N/A
19	Fire Control Room			
	 Detector system panel 	Required	Provided	MR
	Flow switch panel	Required	Provided	MR
-	 PA system panel 	Required	Provided	MR
	Battery backup	Required	Provided	MR
	Building Floor Plans	Required	Provided	MR
20'	Special Fire Protection systems for	Required	Provided	MR
	protection of special Risks, if any:			

The Fire protection systems provided in the building were Tested / Checked and found functional, at the time of inspection.

Keeping In view, compliance of the minimum standards of Fire prevention Safety measured as required under the Directive No. F.6/DFS/MS/BP/2016/184 dated 04/08/16 issued by this department.

The Fire safety certificate issued under rule 35 of the Delhi Fire Service

Rules 2010 is recommended.

Signature of the Inspedting Officer Name :- Francis Brown

Designation :- DO (ED)

Signature of the Inspecting Officer

Name

:- R. K. Yadav:

Designation

:- ADO (LN)

DCFO/NDZ

Prepar and put leb for Bisnal Mr

CFO MDa

miscell 1/30/7