GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ | 78 4

FIRE SAFETY CERTIFICATE

Certified that the Hindustan International Guest House located at 8220, Multani Dhanda, Pahar Ganj, New Delhi comprised of Ground + 05 Upper floors, Ground floor (Reception + 01 office), 1st floor to 4th floor (05 guest rooms at each floor) and 5th floor found sealed, total 20 guest rooms owned/occupied by Hindustan International Guest House was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/NDZ/966 dated 09/06/15. The premise was re-inspected by the officer concerned of this department on 18/07/18 in the presence of Sh. Deepak (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 20 guest rooms only at 1st floor to 4th floor with effect from -1-1 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -----at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- The Manager, Hindustan International Guest House at 8220, Multani Dhanda, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	17	VSPECTION R	EPOPT				
	INSPECTION REPORT 1. Name & address of the building Hindustan International Guest House						
2	2. Type of occupancy:- Multani Dhanda, Pahar Ganj, New Residential Sub Division A. 1						
	and the state of t						
	Gr. + 05 Upper floors (total 20 Guest rooms) Ground floor (Reception + 01 office), 1st floor to 4						
	11001 (03 guest rooms at each floor) and 5 th floor						
	3. Type of case:-	round sea	ied	11001			
	4. Details of previous FSC:-	Renewal					
	Details of previous FSC:-	No. F6/I	DFS/MS/GH/2015	/NDZ/966 dated			
4	5. Fire safety directives No	09/06/1.	5.				
-	5. Date of inspection:-	N/A					
1	7. Name of the inspecting office	18/07/18					
8	3. Name & designation of office	er:- Sh. Mar	noj Kumar Sharma	(ADO/CC)			
_	From the building side:-	er					
g	Year of construction	Sh. Deep	oak (Manager)				
9. Year of construction:- 10. Applicant's letter No:-		Before 2001					
10		3925/Add	ll. C.P/Lic.(H) dat	ed 12/06/2018.			
S.No.	Minimum Standards on fire			Old Case			
	Prevention and fire safety U/R 33	Requirement/ Existing fire saf	Provided at s	ite Remarks			
1.		arrangements	Cty	MR/NMR			
1.	Access to Building						
	1) Road width	N/A	06 mtr.	N/A			
	2) Gate width	N/A	N/A	N/A			
	3) Width of internal road	N/A	N/A	N/A			
2.	Number, Width Type & Ar	rangement of	Exits	IN/A			
	A. Number of staircases	8					
	1. Upper floors	01 Nos.	01 Nos.	MD			
	2. Basements	N/A	N/A	MR			
	B. Width of staircase		IVA	N/A			
	1. Upper floors	1.0 mtr.	1.24 mtr.	MAD			
	2. Basements	N/A	N/A	MR			
	C. Protection of exits	1.071		N/A			
	1. Fire check door	N/A	N/A				
	2. Pressurization	N/A	-	N/A			
	D. No. of continuous staircase to terrace	01	N/A	N/A			
	E. Width of corridor		01	MR			
	F. Door size	N/A	N/A	N/A			
	Compartmentation	01 mtr.	01 mtr.	MR			
	1) Fire check door						
-	2) Sealing of clastic 1 1 C	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
	3) Fire rating of shaft door 4) Water ourtain	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
,	5) Fire Dampers	N/A	N/A	N/A			
•	Smoke Management System 1) Basements	1					
		30 ACPH	N/A	N/A			
	2) Upper floors	12 ACPH	Natural	MR			
	Fire Extinguishers						
	1) Total numbers	20 Nos.	20 Nos.	MR			
	2) Types	ABC & CO2	ABC & CO2	MR			
	3) ISI marking	Required	ADC a COZ	IVIC			

	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel	1 1		IVIIX		
	1) Total number of eachfloor	01	01	MR		
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR		
	3) Nozzle diameter	05 mm	05 mm	MR		
7.	Automatic Fire Detection &	Alarming Syst	em	IVIIX		
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	Required	Provided			
9.	Public Address System	Required		MR		
10.	Automatic Sprinkler System		Provided	MR		
10.	1) Basement	N/A	NI/A	71/1		
	2) Upper floors	N/A N/A	N/A	N/A		
	3) Sprinkler above false	N/A N/A	N/A	N/A		
	ceiling	IN/A	N/A	N/A		
11.	Internal Hydrants	1				
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor		. 17.1	1 1//1		
	3) Hose box	N/A	N/A	N/A		
12.	Yard Hydrants					
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement			1 1 1 / / 1		
	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main	N/A	N/A	N/A		
	pump		AMIL	19/74		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump	N/A	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual	N/A	N/A	N/A		
	stopping		- N 4 A	1 8/ /4		
	2) Terrace level			-		
	a) Discharge of pump	225 LPM	225 LPM	MR		
	b) Head of pump	30 mtr.	30 mtr.	MR		
	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided	-		
4.	Captive Water Storage for Fi	re Fighting	TIOVICCI	MR		
	Under ground tank	N/A	N/A	N/A		
	capacity	4. 31 E \$	1 V / / 1	IN//A		
		1				
	a) Draw-off connection	N/A	N/A	N/A		

m

	c) Access to tank	N/A	N/A	N//
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MF
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	. N/A
20.	Special Fire Protection Syste Risk, if any: One ABC type fir	em for Protect e extinguisher for	tion of special ound provided.	MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no F6/DFS/MS/GH/2015/NDZ/966 dated 09/06/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Office

Name: - M.K. Sharma Designation: - ADO (CC)

ETM.

301

Ces 5 to 1805

Dy. CFO (NDZ)

m.scell

P.J. letter is

but up for tig

medl