GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 18/18

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Rahul Palace located at 5/3, WEA, Tank Road, Ajmal Khan Road, Karol Bagh, New Delhi- 110005 comprised of basement, ground plus three upper floors, using basement as shops, office & store, ground floor as reception & 02 guest rooms, first & second floor each having 09 guest rooms respectively, third floor having 08 guest rooms (total 28 guest rooms) and a pantry for staff on terrace was granted FSC by this department vide letter No. F6/DFS/MS/GH/2015/SZ/1062 dated 22.06.2015. The premises was re-inspected by the officer concerned of this department on 01/08/2018 in presence of Sh. Nain Singh, manager of the guest house, and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on Add at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

1. Smt. Savita Babbar, (Owner), M/s. Hotel Rahul Palace, 5/3, WEA, Tank Road, Ajmal Khan Road, Karol Bagh, New Delhi- 110005.

2. The Additional C.P. (Lic.), Police Station Defence Colony, 1st.floor, New Delhi.

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in.

1. Name & address of the building : M/s. Hotel Rahul Palace, 5/3, WEA, Tank Road, Ajmal Khan Road, Karol Bagh, New Delhi- 110005.

2. Type of Occupancy : Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/GH/2015/SZ/1062 dated 22.06.2015

5. Fire Safety directives letter No : Nil

6. Date of inspection : 01.08.2018

7. Name of the Inspecting Officers : M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side : Sh. Nain Singh, manager

9. Year of Construction : Before 2001

10. Applicant's letter No. : 3684/Addl. C.P./Lic (H) dated New Delhi the 25.05.2018

The said guest house is comprised of basement, ground plus three upper floors.

Minimum Standards on fire revention and fire safety U/R 33	Fire safety requirements as pe letter dt. 28.06.201		Remarks MR/NMR			
cess to building						
• Road width	06 mts	Provided	MR			
• Gate width	4.5mts	Directly accessible from the road	MR			
Width of internal road	N/A	N/A	N/A			
mber, Width, Type & Arrangemen	nt of Exits					
Number of staircases	-	- ;	-			
• Upper Floors	01	01	MR being old case			
 Basements 	02	02	MR			
Width of staircases	_		-			
• Upper Floors	1.25 mts	1.30-1.44 mts	MR being old case			
• Basements	1.25 mts	1.28, 1.29 mts	MR being old case			
Protection of exits	-					
• Fire check door	N/A	N/A	N/A			
 Pressurization 	N/A	N/A	N/A			
No. of continuous staircases to terrace	01	01	MR			
Width of Corridor	Old case	1.50, 1.32 mts	MR			
Door Size	Old case	0.87 mts	MR being old case			
mpartmentation.						
• Fire check door	N/A	N/A	N/A			
• Sealing of electrical shafts	N/A	Sealed				
• Fire Rating of shaft door	N/A	N/A	N/A			
Water Curtain	N/A	N/A	N/A			
• Fire Dampers	N/A	N/A	N/A			
noke Management System.						
Basements	30 a/c per hou	Exhaust fan provided	MR			
• Upper floors			MR			

5	Fire Extinguishers						
	Total numbers	12	Provided	MR 🏂			
	Types	CO ₂ , ABC, WCO ₂	Provided	MR			
	IS marking	ISI marked	Provided	MR			
6	First-Aid Hose Reels.						
	Total numbers on each floor	01	Provided	MR			
	Length of hose reel hose	30 m	Provided	MR			
	Nozzle diameter	5 mm	Provided	MR			
7	Automatic fire detection and alarming system.						
-	Type of detectors	N/A	N/A	N/A			
	Location of Main Panel	N/A	N/A	N/A			
	Location of Repeater Panel	N/A	N/A	N/A			
	Alternate source of power	Required	Provided (D.G set 62.5 KVA)	MR			
	Hooters' Location	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.						
10	Basement	Required	Provided	MR			
	Upper Floor			NT/A			
	G 1 11 1 C 1 11	N/A	N/A	N/A			
	1 1V/A 1V/I						
11	Internal Hydrants	N/A	27/4	DI/A			
	Size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per floor	N/A	N/A	N/A			
	Hose Box	14/71	N/A	N/A			
12	Yard Hydrants.		N/A	N/A			
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	IN/A	IV/A			
13	Pumping Arrangements.						
	Ground Level						
	Discharge of main Pump	N/A	N/A	N/A			
	➤ Head of Main pump	N/A	N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey Pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	> Standby Pump out put	N/A	N/A	N/A			
	> Standby Pump Head	N/A	N/A	N/A			
	> Auto Starting/ Manual stopp	ing N/A	N/A	N/A			
	Pump House Access	N/A	N/A	N/A			
	Terrace level						
	> Discharge of pump	450 LPN	1 Provided	MR			
	➤ Head of the pump	30 mts	Provided	MR			
	> Power Supply	Dogging	Provided	MP			

			M125				
14	Captive Water Storage for fire fighting.						
	•	Underground tank capacity	N/A	N/A	N/A		
		Draw-off connection	N/A	N/A	N/A		
	>	Fire service inlet	N/A	N/A	N/A		
	>	Access to tank	N/A	N/A	N/A		
E .	•	Overhead Tank capacity	Old Case	Provided (4000 lts)	MR being old ca		
15	Exit	Signage.	Required	Provided	MR		
16	Provision of Lifts.						
	•	Pressurization of Lift Shaft	N/A	N/A	N/A		
	•	Pressurization of Lift lobby	N/A	N/A	N/A		
	•	Communication In lift Car	Required	Provided	MR		
	•	Fireman's Grounding Switch	N/A	N/A	Old lift		
_	•	Lift Signage	Required	Provided	MR		
17	Stand	by power supply	Required	Provided	MR		
18	Refuge Area.						
	>	Total Area	N/A	N/A	N/A		
	>	Location	N/A	N/A	N/A		
19		Control Room					
SEA		Detector System Panel	N/A	N/A	N/A		
	Eu.	Flow Switch Panel	N/A	N/A	N/A		
8/18		PA System Panel	N/A	N/A	N/A		
211 Fire C	A1097 .	Battery backup	Required	Provided	MR		
no	•	Building Floor Plans	N/A	N/A	N/A		
20		Fire Protection Systems for tion of special Risks, if any:	N/A	N/A	N/A		

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2015/SZ/1062 dated 22.06.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

DCFO (SZ)

Signature of the Inspecting Officer Name M.K. CHATTOPADHYAY Div. Officer (South West)