GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 18-57

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Rijak Continental located at 12A/14, WEA, Saraswati Marg, Karol Bagh, New Delhi- 110005 comprised of basement, ground plus four upper floors, using basement as gym khanna, ground floor as reception & shops, first, second & third floor each having 09 guest rooms respectively (total 27 guest rooms) and one staff room with pantry for staff on fourth floor, was granted FSC by this department vide letter No. F6/DFS/MS/GH/2015/SZ/1086 dated 26.06.2015. The premises was re-inspected by the officer concerned of this department on 01/08/2018 in presence of Sh. Veera Kumar, manager of the guest house, and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on SIS at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Dated: SISI IS

Copy to:-

1. Sh. Manjeet Singh, (Owner), M/s. Hotel Rijak Continental, 12A/14, WEA, Saraswati Marg, Karol Bagh, New Delhi- 110005.

2. The Additional C.P. (Lic.), Police Station Defence Colony, 1st floor, New Delhi.

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. Name & address of the building

: M/s. Hotel Rijak Continental, 12A/14, WEA, Saraswati

Marg, Karol Bagh, New Delhi- 05.

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/GH/2015/SZ/1086 dated 26.06.2015

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 01.08.2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side

: Sh. Veera Kumar, manager

9. Year of Construction

: Before 1989

10. Applicant's letter No.

: 3977Addl. CP/LIC(H) dated New Delhi, the 03.07.2018

The said guest house is comprised of basement, ground plus four upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Fire safety requirements as per letter dt. 26.06.2015	Provided at site	Remarks MR/NMR		
1	Access to building					
	Road width	06 mts	Provided	MR		
	Gate width	4.5 mts	Directly accessible	MR		
	Width of internal road	N/A	N/A	N/A		
2	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases	-	- 7			
	• Upper Floors	Old Case	01	MR being old case		
	Basements	Old case	01	MR being old case		
	b. Width of staircases	-	<u>-</u>	f		
	• Upper Floors	Old case	1.19-1.25 mts	MR being old case		
	Basements	Old case	1.20-1.45 mts	MR being old case		
	*** **********************************	_	· -			
	c. Protection of exits • Fire check door	N/A	N/A	N/A		
		N/A	N/A	N/A		
	Pressurization	01	01	MR		
	e. No. of continuous staircases to terrace	Old case	1.18 mts	MR		
	g. Width of Corridor h. Door Size	Old case	0.87 mts	MR being old case		
3	Compartmentation.		э			
	Fire check door	N/A	N/A	N/A		
	Sealing of electrical shafts	N/A	Sealed			
	Fire Rating of shaft door	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.					
	Basements	30 a/c per hour	Exhaust fan provided	MR		

1	Total numbers	14	Provided	MR		
	• Types	CO ₂ , ABC, WCO ₂	Provided	MR		
	IS marking	ISI marked	Provided	MR		
6	First-Aid Hose Reels.					
	Total numbers on each floor	01	Provided	MR		
	Length of hose reel hose	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming					
	Type of detectors	N/A	N/A	N/A		
	Location of Main Panel	N/A	N/A	N/A		
	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power	Required	D.G. set 62.5 KVA	MR		
	Hooters' Location	N/A	N/A	N/A		
8	MOEFA	Required	Provided	MR		
9	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System.					
	Basement	Required	Provided	MR		
	Upper Floor	N/A	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants					
	Size of riser/down-comer	N/A	N/A	N/A		
	Number of hydrants per floor	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
12	Yard Hydrants.					
12	Total number of hydrants N/A		N/A	N/A		
	Hose Box	N/A	N/A	N/A		
13	Pumping Arrangements.					
	Ground Level					
	Discharge of main Pump	N/A	N/A	N/A		
	➤ Head of Main pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
	> Jockey Pump out put	N/A	N/A	N/A		
	Jockey pump head	N/A	N/A	N/A		
	Standby Pump out put	N/A	N/A	N/A		
	Standby Pump HeadAuto Starting/ Manual stopping	ng N/A	N/A	N/A		
	> Pump House Access	N/A	N/A	N/A		
		N/A	N/A	N/A		
	Terrace level					

		b	1/24			
	•	Head of the pump	30 mts	Provided	MR	
		Power Supply	Required	Provided	MR	
		Auto Starting of pump	Required	Provided	MR	
14	Capti	v <mark>e Water Storage for fire fighting</mark>	5.			
	•	Underground tank capacity	N/A	N/A	N/A	
	>	Draw-off connection	N/A	N/A	N/A	
	>	Fire service inlet	N/A	Provided		
	>	Access to tank	N/A	N/A	N/A	
	•	Overhead Tank capacity	Old case	5000 lts	MR, Old case	
15	Exit S	ignage.	Required	Provided	MR	
16	Provision of Lifts.					
	•	Pressurization of Lift Shaft	N/A	N/A	N/A	
	•	Pressurization of Lift lobby	N/A	N/A	N/A	
	•	Communication In lift Car	Required	Provided	MR	
	•	Fireman's Grounding Switch	Required	Provided	MR	
	•	Lift Signage	Required	Provided	MR	
17	Stand	by power supply	Required	Provided	MR	
18	Refuge Area.					
	>	Total Area	N/A	N/A	N/A	
	>	Location	N/A	N/A	N/A	
19	Fire (Control Room			1	
ERD		Detector System Panel	N/A	N/A	N/A	
-ar	2	Flow Switch Panel	N/A	N/A	N/A	
18	\$	PA System Panel	N/A	N/A	N/A	
7	97 97	Battery backup	Required	Provided	MR	
ON		Building Floor Plans	N/A	N/A	N/A	
20		al Fire Protection Systems for ction of special Risks, if any:	N/A	N/A	N/A	

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2015/SZ/1086 dated 26.06.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

887/20/8W

DCFO (SZ)

Sont

Signature of the Inspecting Officer Name M.K. CHATTOPADHYAY Div. Officer (South West)