GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ |869

Dated: -\$/-8/-

FIRE SAFETY CERTIFICATE

Certified that the M/s Aura Palace located at 1414-1415, Gali Sagtrashan, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (03 guest rooms), 1st floor to 3rd floor (07 guest rooms at each floor), total 24 guest rooms owned/occupied by department Palace was granted **FSC** by this No.F6/DFS/MS/GH/2015/NDZ/1360 dated 29/07/15. The premise was re-inspected by the officer concerned of this department on 18/07/18 in the presence of Sh. Suresh Kumar (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 24 guest rooms only at ground + 1^{st} floor + 2^{nd} floor & 3^{rd} floor with effect from ------218118--for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -----at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

2. The Manager, M/s Aura Palace at 1414-1415, Gali Sagtrashan, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1.	Name & address of the Living	CCTION REPORT M/s Aura Palace at 1414-1415, Gali Sagtrashan, Poly
	os of the building	M/s Aura Palace at 1414
2.	Type of occurre	Sagtrashan Dal Gali

2. Type of occupancy:-Sagtrashan, Pahar Ganj. New Delhi. Residential, Sub Division-A-1

Gr. + 03 Upper floors (total 24 Guest rooms) Ground floor (03 guest rooms), 1st floor to 3rd floor (07 guest rooms at each floor).

3. Type of case:-

4. Details of previous FSC:-No. F6/DFS/MS/GH/2015/NDZ/1360 dated 5. Fire safety directives No.-

6. Date of inspection:-N/A

18/06/18

7. Name of the inspecting officer:-8. Name & designation of officer

From the building side:-9. Year of construction:-

Sh. Manoj Kumar Sharma (ADO/CC) Sh. Suresh Kumar (Manager)

10. Applicant's letter No:-Nil dated 06/07/2018.

	i Fractit S letter No:-	3 771				
		Nil	dated 06/	07/2018		
	S.No. Minimum Standards on fire			2010.		
	Prevention and fire safety U/	Requiren	nent/	Dua		Old Cas
	1. Existing		fire safety FIOVI		d at site	Remarks
	Access to Building	arrangem	ents			MR/NMR
	1) Road width			The second secon	-	- NIVIN
	2) Gate width	N/A		04 2004		
	3) Widd 0:	N/A		04 mtr.	*	N/A
	3) Width of internal road 2. Number Westernal road	N/A		N/A		N/A
	Trumper, Width Tyme	A rmo]	V/A		
	A. Number of staircases	Arrangement	t of Exits			N/A
	1. Upper floors					
	2. Basements	01 Nos.	0	1 Nos.		- 10
	B. Width of staircase	N/A	N	11105.		MR
	1 Unpon f			//A		N/A
	1. Upper floors	0.80 mtr.				
	2. Basements	N/A	1.	25 mtr.		MR
	C. Protection of exits	IV/A	N/	'A		
	1. Fire check door					V/A
1	2. Pressurization	N/A	N/	Δ		
	D. No. of continuous staircase to terrace	N/A	N/			V/A
	F Width C	e N/A		N/A N		I/A
	E. Width of corridor	N/A				/A
3.	F. Door size		N/A			
5.	Compartmentation	01 mtr.	01 r	ntr		A
1	1) Fire check door				M	R
	2) Sealing of electrical shafts 3) Fire ratios of the sealing of t	N/A	N/A			
	3) Fire rating 6 directrical shafts	N/A		N/A N		A
	3) Fire rating of shaft door	N/A				1
	4) Water curtain	N/A	N/A		N//	
4.	5) Fire Dampers	N/A	N/A		N/2	
1.	Smoke Management C.	IN/A	N/A			
	- ascincing		The same of the sa	The state of the s	NA	
_	2) Upper floors	30 ACPH	N/A	And the second second		
5.	Fire Extinguishers	12 ACPH			N/A	
-	1) Total numbers		Natura	an an annual section of the section	MR	
	2) Types	10 Nos.				
	2) Types	ARC & CO	10 Nos.	And the second second second second	MR	
	3) ISI marking	ABC & CO2	ABC &	CO2	-	
		Required	Provide	d	MR	
				ш	MR	

6.	First-Aid Hose Reel	i.		4
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection & A	Alarming Syste	em	7
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	Required		
10.	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	in the second		
11.	Internal Hydrants			
11.	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor	1 1/1 1		
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants			
12.	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement			
15.	1) Ground level	N/A	N/A	· NA
	a) Discharge of main	N/A	N/A	NA
	pump	1 302 8		
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump		N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	NA
	f) Stand by pump output		N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	. N/A
	stopping			
	2) Terrace level			
	a) Discharge of pump	450 LPM	450 LPM	MR
	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump		Provided	MR
	Captive Water Storage for I			
14	- Labure mater Storage Ior I		INI/A	N/A
14.		N/A	IN/A	
14.	1) Under ground tank	N/A	N/A	1 30 0 3
14.	Under ground tank capacity			N/A
14.	1) Under ground tank	N/A N/A N/A	N/A N/A	

m

	d) Over head tank capacity	5,000 ltr.	5,000 ltr.	MR
15.	Exit Signage.	Required	Describe	
16.	Provision of Lifts.	required	Provided	MR
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
17.	e) Lift signage	N/A	N/A	N/A
18.	Stand by Power Supply	Required	Provided	MR
10.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
9.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A N/A
	e) Building floor plan	N/A	N/A	N/A
0.	Special Fire Protection System Risk, if any: One ABC type fire	m for Protectio		MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/1360 dated 29/07/15 renewal under rule 35 of the Delhi Fire Service rules

Signature of the Inspecting Office

Name: - M.K. Sharma

Designation: - ADO (CC)

Dy. CFO (NDZ)

F.T. letter is put up for tog

ORO(NDZ) M. SCELL WETE