GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 1883

Dated:

FIRE SAFETY CERTIFICATE

Certified that M/s. Kings Inn located at 14A/7, WEA, Karol Bagh, New Delhi- 110005 comprised of basement, ground plus three upper floors, using basement as storage, ground floor as reception, office, lobby & 01 guest room, first, second & third floor each having 06 guest rooms respectively (total 19 guest rooms) and a pantry for staff in temporary shed on terrace was granted FSC by this department vide letter No. F6/DFS/MS/GH/2015/SZ/1053 dated 19.06.2015. The premises was re-inspected by the officer concerned of this department on 30/07/2018 in presence of Sh. Perminder Singh, owner of the guest house, and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 9/8/17 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on ______at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

Sh. Perminder Singh, (Owner), M/s. Kings Inn, 14A/7, WEA, Karol Bagh, New Delhi- 05.
 The Additional C.P. (Lic.), Police Station Defence Colony, 1st floor, New Delhi.

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in.

THOI BOTTON REI ON

1. Name & address of the building

: M/s. Guest House Kings Inn, 14A/7, WEA, Karol Bagh,

New Delhi- 110005.

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/GH/2015/SZ/1053 dated 19.06.2015

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 30.07.2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side

: Sh. Perminder Singh, owner

9. Year of Construction

: Before 2010

10. Applicant's letter No.

: 3612/Addl. C.P./Lic (H) dated New Delhi the 25.05.2018

The said guest house is comprised of basement, ground plus three upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Fire safety requirements as po letter dt. 19.06.201		Remarks MR/NMR			
1	Access to building						
	• Road width	06 mts	Provided	MR			
	Gate width	4.5mts	Directly accessible from the road	MR			
	Width of internal road	N/A	N/A	N/A			
2	Number, Width, Type & Arrangement of Exits						
	a. Number of staircases	-	- ,	-			
	Upper Floors	01	01	MR being old case			
	Basements	02	02	MR being old case			
	b. Width of staircases	-	-	_			
	Upper Floors	1.25 mts	1.25 mts	MR being old case			
	Basements	Old case	1.20, 1.12 mts.	MR being old case			
	c. Protection of exits	-	•	-			
	Fire check door	N/A	N/A	N/A			
	 Pressurization 	N/A	N/A	N/A			
	e. No. of continuous staircases to terrace	01	01	MR			
	g. Width of Corridor	Old case	2.15, 1.95 mts	MR			
	h. Door Size	Old case	0.79 mts	MR being old case			
	Compartmentation.						
	Fire check door	N/A	N/A	N/A			
	 Sealing of electrical shafts 	N/A	Sealed				
	 Fire Rating of shaft door 	N/A	N/A	N/A			
	Water Curtain	N/A	N/A	N/A			
	• Fire Dampers	N/A	N/A	N/A			
	Smoke Management System.						
	Basements	30 a/c per hour	Exhaust fan provided	MR			
	Unner floors	12 a/c per hour		MD			

	Total numbers	15	Provided	MR			
		CO ₂ , ABC, WCO ₂	Provided	MR			
	• Types	ISI marked	Provided	MR			
	IS marking First-Aid Hose Reels.						
5]		01	Provided	MR			
	Total numbers on each floor	30 m	Provided	MR			
	• Length of hose reel hose	5 mm	Provided	MR			
	Nozzle diameter						
7	Automatic fire detection and alarming	system. N/A	N/A	N/A			
	• Type of detectors	N/A N/A	N/A	N/A			
	Location of Main Panel Output Description Descrip			N/A			
	Location of Repeater Panel	N/A	N/A	MR			
	Alternate source of power	Required	Provided (D.G set 125 KVA)	N/A			
	Hooters' Location	N/A	N/A Provided	MR			
8	MOEFA	Required					
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.	1 21/4	N/A	Area less than			
	• Basement	N/A	IVA	200 sq. mts.			
	• Upper Floor	N/A	N/A`	N/A			
	 Sprinkler above false ceiling 	N/A	N/A	N/A			
11	Internal Hydrants						
	Size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per floor	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
12	Yard Hydrants.						
12	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
13	Ground Level						
	> Discharge of main Pump	N/A	N/A	N/A			
		N/A	N/A	N/A			
		N/A		N/A			
		N/A		N/A			
		N/A N/A		N/A			
	> Jockey pump head	N/A N/A		N/A			
	Standby Pump out put	N/A N/A		N/A			
	Standby Pump Head			N/A			
	Auto Starting/ Manual stopp			N/A			
	Pump House Access	N/A	. IN/A				
	Terrace level		Duraided	MR			
6	Discharge of pump	450 LI	Duaridad	MR			
	Head of the pump	30 m		MR			
	Power Supply	Requi	red Flovided	N/A			

4 0	Captive Water Storage for fire fightin	g.				
	Underground tank capacity	N/A	N/A	N/A		
	> Draw-off connection	N/A	N/A	N/A		
	> Fire service inlet	N/A	N/A	N/A		
	Access to tank	N/A	N/A	N/A		
	Overhead Tank capacity	Old Case	Provided (5000 lts)	MR being old cas		
15 E	Exit S <mark>ignage.</mark>	Required	Provided	MR		
	Provision of Lifts.					
	Pressurization of Lift Shaft	N/A	N/A	N/A		
	Pressurization of Lift lobby	N/A	N/A	N/A		
	Communication In lift Car	Required	Provided	MR		
2	• Fireman's Grounding Switch	Required	Provided	MR		
	• Lift Signage	Required	Provided	MR		
17	Standby power supply	Required	Provided	MR		
18	Refuge Area.			1, -2115		
	> Total Area	N/A	N/A	N/A		
	> Location	N/A	N/A	N/A		
19	Fire Control Room					
	Detector System Panel	N/A	N/A	N/A		
BERL	Flow Switch Panel	N/A	N/A	N/A		
S. C.	PA System Panel	N/A	N/A	N/A		
118	Battery backup	Required	Provided	MR		
2000	Building Floor Plans	N/A	N/A	N/A		
	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	N/A		

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2015/SZ/1053 dated 19.06.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

DCF() (SZ)

DCFO (SZ)

718/8/8

Los

FT/M.

W_1/8"

Name M.K.

Signature of the Inspecting Officer

Div. Officer (South West)

CHATTOPADHYAY