GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 1955

Dated: 23/8/18

FIRE SAFETY CERTIFICATE

Certified that the Suvidha Tourist Lodge Guest House located at 3418-21, Hari Mandir Marg, Pahar Ganj, New Delhi comprised of Ground floor (reception + 02 guest rooms), 1st floor to 4th floor (02 guest rooms at floor), total 10 guest rooms owned/occupied by Suvidha Tourist Lodge Guest House was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/NDZ/1377 dated 30/07/15. The premise was re-inspected by the officer concerned of this department on 09/08/18 in the presence of Mr. Sonu (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 10 guest rooms with effect from 2-2-18-18----for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 23-18----at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- The Manager, Suvidha Tourist Lodge Guest House at 3418-21, Hari Mandir Marg. Pahar Ganj. New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INSPEC	TION REPORT
1.	Name & address of the building	Suvidha Tourist Lodge Guest House at
		3418-21, Hari Mandir Marg, Pahar Ganj,
		New Delhi
2.	Type of occupancy:-	Residential, Sub Division-A-1
		Gr. + 04 Upper floors
		Ground floor (reception + 02 guest rooms), 1 st floor
		to 4 th floor (02 guest rooms at each floor),
3.	Type of case:-	Renewal
4.	Details of previous FSC:-	No. F6/DFS/MS/GH/2015/NDZ/1377 dated
		30/07/15.
5.	Fire safety directives No	N/A
6.	Date of inspection:-	09/08/18
7.	Name of the inspecting officer:-	Sh. Manoj Kumar Sharma (ADO/CC)
8.	Name & designation of officer	
	From the building side:-	Mr. Sonu (Manager)
9.	Year of construction:-	1995
10.	Applicant's letter No:-	Nil dated 24/07/2018.
	11	0110-

10.	rippireant s letter 110.	Till dated 2 ii	0772010.	014 0	
CAL	N	Requirement/	D '11 1 4 '4	Old Case	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Existing fire safety arrangements	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	N/A	N/A	N/A	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arrangement of Exits				
	A. Number of staircases				
	1. Upper floors	01 Nos.	01 Nos.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	0.80 mtr.	0.85mtr.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits		7 7 7 8		
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	N/A	N/A	N/A	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1 mtr.	1 mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	N/A	N/A	N/A	
	2) Upper floors	12 ACPH	Natural	MR	
5.	Fire Extinguishers				
	1) Total numbers	10 Nos.	10 Nos.	MR	
	2) Types	ABC & CO2	ABC & CO2	MR	

First-Aid Hose Reel 1) Total number of eachfloor	21/4		
1) Total number of eachfloor	DT/A		
-) 1000111001	N/A	N/A	N/A
2) Length of hose reel hose	N/A	N/A	N/A
3) Nozzle diameter	N/A	N/A	N/A
Automatic Fire Detection & A	Alarming Sys	stem	
1) Type of detectors	N/A	N/A	N/A
2) Location of main panel	N/A	N/A	N/A
3) Location of repeater panel	N/A	N/A	N/A
4) Alternate source of power	N/A	N/A	N/A
5) Hooter's Location	N/A	N/A	N/A
MOEFA	N/A	N/A	N/A
Public Address System	N/A	N/A	N/A
1) Basement	N/A	N/A	N/A
2) Upper floors	N/A	N/A	N/A
	N/A	N/A	N/A
ceiling			
1) Size of riser/down-comer	N/A	N/A	N/A
2) Number of hydrants per	N/A	N/A	N/A
floor		,	
3) Hose box	N/A	N/A	N/A
Yard Hydrants		,	
1) Total number of hydrants	N/A	N/A	N/A
2) Hose box	N/A	N/A	N/A
Pumping Arrangement			
1) Ground level	N/A	N/A	N/A
a) Discharge of main	N/A	N/A	N/A
pump			
b) Head of main pump	N/A	N/A	N/A
c) Number of main pump	N/A	N/A	N/A
d) Jockey pump out put	N/A	N/A	N/A
e) Jockey pump head	N/A	N/A	N/A
f) Stand by pump output	N/A	N/A	N/A
g) Stand by pump head	N/A	N/A	N/A
h) Auto starting/Manual	N/A	N/A	N/A
stopping			
2) Terrace level			
a) Discharge of pump	N/A	N/A	N/A
b) Head of pump	N/A	N/A	N/A
c) Power supply	N/A	N/A	N/A
d) Auto starting of pump	N/A	N/A	N/A
Captive Water Storage for F	ire Fighting		,
1) Under ground tank	N/A	N/A	N/A
capacity			Z .
a) Draw-off connection	N/A	N/A	N/A
	3) Nozzle diameter Automatic Fire Detection & 1 Type of detectors 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box Yard Hydrants 1) Total number of hydrants 2) Hose box Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump out put e) Jockey pump head f) Stand by pump head f) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for F	3) Nozzle diameter N/A Automatic Fire Detection & Alarming Sy 1) Type of detectors N/A 2) Location of main panel N/A 3) Location of repeater panel N/A 4) Alternate source of power N/A 5) Hooter's Location N/A MOEFA N/A Public Address System N/A Automatic Sprinkler System 1) Basement N/A 2) Upper floors N/A 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer N/A 2) Number of hydrants per floor 3) Hose box N/A Yard Hydrants 1) Total number of hydrants N/A 2) Hose box N/A Pumping Arrangement 1) Ground level N/A a) Discharge of main pump N/A C) Number of main pump N/A d) Jockey pump out put N/A f) Stand by pump output N/A f) Stand by pump head N/A h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump N/A c) Power supply N/A d) Auto starting of pump N/A Captive Water Storage for Fire Fighting	3) Nozzle diameter N/A N/A Automatic Fire Detection & Alarming System 1) Type of detectors N/A N/A 2) Location of main panel N/A N/A 3) Location of repeater panel N/A N/A 4) Alternate source of power N/A N/A 5) Hooter's Location N/A N/A N/A MOEFA N/A N/A N/A Public Address System N/A N/A Automatic Sprinkler System 1) Basement N/A N/A N/A 2) Upper floors N/A N/A 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer N/A N/A 2) Number of hydrants per floor 3) Hose box N/A N/A Yard Hydrants 1) Total number of hydrants 1) Ground level N/A N/A Pumping Arrangement 1) Ground level N/A N/A a) Discharge of main pump N/A N/A d) Jockey pump out put N/A N/A f) Stand by pump head N/A N/A f) Stand by pump head N/A N/A h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump N/A N/A b) Head of pump N/A N/A C) Power supply N/A N/A Captive Water Storage for Fire Fighting

	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	N/A	N/A	N/A
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.		¥	
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Sys Risk, if any:	tem for Prote	ction of special	N/A

The fire protection systems provided in the building were randomly tested, checked and

found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/1377 dated 30/07/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFO(NDZ)

miscell by

F.T. Letter is put up for signs - CO (NDZ) miscell les