## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F.6 / DFS / MS / 2018 / 19 09

Dated: /6/08/2018

## **FIRE SAFETY CERTIFICATE**

## Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on **WWW.dfs.Delhigovt.nic.in**

Issued on ..16.0.8........ at New Delhi

Chief Fire Officer Ph:-011-23414250

Copy to: -

- 1. The Director, Education, Government of N.C.T of Delhi. Old Sectt. Delhi 110054.
- 2. The Principal, Prince Public School, Sector-24, Rohini, Delhi- 110085.

## INSPECTION REPORT

1. Name & address of the building : Prince Public School, Sector-24, Rohini, Delhi- 110085.

2. Type of Occupancy : Educational

3. Type of Case :Renewal (B+G +03 upper floors)

4. Details of previous NOC : F.6/MS/DFS/2005/375 dated 23.02.2005

5. Fire Safety directives letter No : NBC Part-4
6. Date of inspection : 26/07/2018
7. Name of the Inspecting Officers : ADO (RN)

8. Name and designation of officers

from the building side : Mrs. Kamlesh Solanki, Principal

9. Year of Construction : 1991

10. Applicant's letter No. : PPS/18 dated 12.07.2018

Plot Area-800.11 m2

113	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR			
1	Access to building						
	Road width	06m	09m	MR			
	Gate width	4.5m	5m	MR			
	Width of internal road	NA	NA	NA			
2	Number, Width, Type & Arrangement of Exits						
	a. Number of staircases						
	Upper Floors	02	02	MR			
	Basements	02	02	MR			
	b. Width of staircases						
	Upper Floors	1.50m	1.50m & 1.00m	MR(old case)			
	Basements	1.50m	1.50m & 1.00m	MR(old case)			
	c. Protection of exits	NA	NA	NA			
	<ul><li>Fire check door</li><li>Pressurization</li></ul>	NA	NA.	NA			
	d. No. of continuous staircases to terrace	01	02	MR			
	e. Width of Corridor	NA	NA .	NA			
	f. Door Size	l m	01m	MR			

	Compartmentation.				The state of the s
	Fire check door	NA	NA		NA
	Sealing of electrical shafts	NA	NA		NA
	• Fire Rating of shaft door	NA	NA		NA
	• Water Curtain	NA	NA		NA
	Fire Dampers	NA	NA		NA
	Smoke Management System.				
	Basements	30 a/c per hour	Exhaust Fan		MR
	• Upper floors	12 a/c per hour	Natural Ventilated		MR
	Fire Extinguishers				
	Total numbers	15nos	20 nos		MR
	• Types	ABC/Co2	ABC20		MR
	ISI marking	ISI Marked	Yes		MR
	First-Aid Hose Reels.			107	
	Total numbers on each floor	02	Oleach floor	A 100 100 100 100 100 100 100 100 100 10	MR
	<ul> <li>Length of hose reel hose</li> </ul>	30m	30m		MR
	Nozzle diameter	5mm	5nim	A 800 0 4 0	MR
	Automatic fire detection and alarming sys				
	Type of detectors	NA	NA V.	3	NA
	Location of Main Panel	NA	NA		NA
	Location of Repeater Panel	NA	NA	C S	NA
	Alternate source of power	NA	NA NA		NA
	Hooters` Location	NA	NA NA		NA
	MOEFA	NA	NA		NA
	Public Address System.	NA	Provided		NA
	Automatic Sprinkler System.				7613
		Required	Provided		MR
		NA	NA		NA
	<ul><li>Upper Floor</li><li>Sprinkler above false ceiling</li></ul>	NA	NA		NA
	Internal Hydrants		1		i ja
l	internal rigurants	100mm,01	Provided		MR



	Number of hydrout				
	<ul><li>Number of hydrants per floor</li><li>Hose Box</li></ul>	01	01	MR	
12	Yard Hydrants.	01	01	MR	
			1		
	Total number of hydrants	NA	Provided	NA	
	• Hose Box	NA	Provided	NA	
3	Pumping Arrangements.				
	Ground Level				
	Discharge of main Pump	N/A	N/A		
	Head of Main pump			N/A	
	Number of main pumps	N/A N/A	N/A	N/A	
	Jockey Pump out put		N/A	N/A	
	Jockey pump head	NA	NA	NA	
	Standby Pump out put	NA	NA	N <sub>A</sub>	
	Standby Pump Head	N/A	N/A	N/A	
	<ul><li>Auto Starting/ Manual stopping</li><li>Pump House Access</li></ul>	N/A	N/A	N/A	
	Terrace level	N/A	N/A	N/A	
	<ul><li>Discharge of pump</li><li>Head of the pump</li></ul>	450 lpm & 180 lpm	450 lpm &	MR	
	Power Supply	40m	40 m	MR	
	Auto Starting of pump	Required	Provided	MR	
	Canting W. 1. Can	NA	NA	NA	
	Captive Water Storage for fire fighting.				
	Underground tank capacity				
	> Draw-off connection	NA	NA	NA ·	
	Fire service inlet	NA	NA	NA	
	Access to tank	NA	NA	NA	
	Overhead Tank capacity	NA	NA	NA	
F	xit Signage.	10,000 ltr	10000 ltr	MR	
EX	at Signage,	Required	Provided	MR	
Pr	ovision of Lifts.		***	+ 11	
-	Processing	N/A		the state of	
•	ressurization of Lift Shaft		N/A	N/A	
	ressurization of Lift Shaft			1 1/1	
•	Pressurization of Lift lobby	N/A	N/A	N/A	

	<ul> <li>Fireman's Grounding Switch</li> </ul>	N/A		
1	• Lift Signage	IN/A	N/A	N/A
7	Standby power supply	N/A	N/A	N/A
8		N/A	N/A	
3	Refuge Area.	8		N/A
	> Total Area	21/4		
	> Location	N/A	N/A	N/A
17.1		N/A	N/A	N/A
	Detector System Panel     Flow Switch B.	N/A	N/A	N/A
	<ul><li>Flow Switch Panel</li><li>PA System Panel</li></ul>	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
	<ul> <li>Building Floor Plans</li> </ul>	N/A	N/A	N/A
Sp	pecial Fire Protection Systems for	N/A	N/A	N/A
Pr	otection of special Risks, if any:	, N/A	N/A	N/A

The fire protection systems provided in the building were tested/ checked randomly and found in working condition at the time of inspection.

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and fire safety required as stipulated in director of education Circular dated 01.03.2011/ NBC Part-4, it is recommended to renewal of fire safety certificate issued vide this department letter of even no. 375 dated

Signature of the Inspecting Officer

Any KN

Bru I ding er comprised of BK + 03 upper

Blooms. Noc has dready been usued earlier
by This light tetter of even no 375 dt 8 / 2 post

Bubmitted BI

Leading of the blog.