GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

No. F.6/DFS/MS/2018/SZ/ | 98|

Dated: 29/8/18

FIRE SAFETY CERTIFICATE

Certified that the M/s S.K Westend Convention Centre, Plot No.15-16, District Centre, Janak Puri, New Delhi-110058 comprised of Basement, ground floor plus three upper floors owned/ occupied by the M/s S.K Westend Convention Centre was inspected by the officers concerned of this department on 25.07.2018 in the presence of Sh. Nippun Arora (Partner) and found that the owner/occupier have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class Group D "Assembly Building" w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed below.

Issued on 2.3.1.8.1.3... at New Delhi.

(VIPIN KENTAL)
CHIEF FIRE OFFICER

Copy to:-

- The Dy. Health Officer,
 S.D.M.C, Public Health Department, West Zone,
 Vishal Enclave, Rajouri Garden, New Delhi-110027
- Sh. Nippun Arora, M/s S.K Westend Convention Centre, Plot No.15-16, District Centre, Janak Puri, New Delhi-110058.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape arrangements shall be kept unlocked & unobstructed for speedy evacuation of occupants in case of an emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement shall be used as per the building bye laws.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

Comprised of basement, ground floor plus three upper floors. INSPECTION REPORT M/s S.K Westend Convention Centre, Plot No.15-16, District Centre, 1. Name & address of the building: Janak Puri, New Delhi-110058 2. Type of Occupancy **Assembly Building** Type of Case New 4. Details of Previous NOC N.A 5. Fire Safety directives letter No: N.A 6. Date of inspection 25.07.2018 Name of Inspecting Officer D.O. M.K. Chattopadhyay & A.D.O. Sandeep Duggal 8. Name and designation of officers From the building side : Sh. Nippun Arora (Partner) 9. Year of Construction : Before 2010 10. Applicant's letter No. : Nil dated 12.06.2018 S. No. Minimum Standards on fire prevention and UBBL/NBC Provided at Remarks fire safety U/R 33 requirements MR/NMR site 1. Access to building Accessible (09 mtrs.) Road width Provided MR 4.5 mtrs Gate width Directly accessible MR N/A from road N/A Width of internal road N/A 2. Number, Width, Type & Arrangement of Exits a. Number of staircases Upper Floors 03 No's Provided MR Basements 02 No's & 01 Provided MR ramp b. Width of staircases Upper Floor 150 cms Provided MR Basements 150 cms Provided MR c. Protection of exits Fire check door Pressurization Required Provided MR N/A N/A N/A d. No. of continuous staircases to terrace Required Provided MR e. Width of Corridor 150 cms Opening in hall MR Door Size 200 cms 200 cms (02 no.'s) MR 3. Compartmentation Fire check door Provided Required MR Sealing of electrical shafts Required Sealed MR Fire Rating of shaft door N/A N/A N/A Water Curtain N/A N/A N/A Fire Dampers N/A N/A N/A 4. **Smoke Management System** Basements Required Exhaust ducts MR Provided Upper floors Required MR 5. Fire Extinguishers Provided Total numbers on each floor 04 no.'s MR ABC/CO₂/W CO₂ type **Types** Provided MR ISI marked MR IS marking ISI marked 6. First-Aid Hose Reels Total numbers on each floor 01 no. Provided MR Provided MR 30 mtrs Length of hose reel hose

7.	Automatic fire detection and alarming system				
	Type of detectors	Smoke/Heat	Provided	MR	
	 Location of Main Panel 	At entrance	Provided	MR	
	 Location of Repeater Panel 	N/A	N/A	N/A	
	 Alternate source of power 	Required	Provided	MR	
	Hooters' Location	In hall	Provided	MR	
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	N/A	N/A	N/A	
10.	Automatic Sprinkler System	D ' 1	D 111	1.00	
	BasementGround Floor	Required N/A	Provided N/A	MR N/A	
	 Sprinkler above false ceiling 	N/A	N/A	N/A	
11.	Internal Hydrants	IN/A	IN/A	IN/A	
	Size of riser/down-comer	Required 100 mm	Provided	MR	
	 Number of hydrants per floor 	One	Provided	MR	
	Hose Box	One	Provided	MR	
12.	Yard Hydrants				
	Total number of hydrants	N/A	One	N/A	
	Hose Box	N/A	One	N/A	
13.	Pumping Arrangements			The state of the s	
	Ground Level				
	Discharge of main Pump	2280 LPM	Provided	MR	
	> Head of Main pump	60 mtrs	Provided	MR	
	Number of main pumps	One	Provided	MR	
	Jockey Pump out put	180 LPM	Provided	MR	
	> Jockey pump head	60 mtrs	Provided	MR	
	Standby Pump Used	2280 LPM	Provided	MR	
	Standby Pump Head Auto Starting/Manual Stanning	60 mtrs	Provided	MR	
	> Auto Starting/Manual Stopping	Required	Provided	MR	
	> Pump House Access	Required	Provided	MR	
	• Terrace level	•			
	Discharge of pump	900 LPM	Provided	MR	
	Head of the pump	40 mtrs	Provided	MR	
	Power Supply	Required	Provided	MR	
	> Auto Starting of pump	Required	Provided	MR	
14.	Captive Water Storage for fire fighting				
	Underground tank capacity	50,000 ltrs	Provided	MR	
	> Draw-off connection	N/A	N/A	N/A	
	Fire service inletAccess to tank	Required	Provided	MR	
	 Overhead Tank capacity 	Required	Provided	MR	
	overnead rank capacity	10000 ltrs	Provided	MR	
15.	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts.				
	Pressurization of Lift Shaft Chick Life	N/A	N/A	N/A	
	Pressurization of Lift lobby Communication In lift Com	N/A	N/A	N/A	
	Communication In lift CarFireman's Grounding Switch	N/A	N/A	N/A	
	Fireman's Grounding SwitchLift Signage	Required	Provided	MR	
	Zint Oightage	Required	Provided	MR	
17.	Standby power supply	Required	Provided	MR	
18.	Refuge Area.	1			
	> Total Area	N/A	N/A	N/A	
		The second secon		11/11	

N 18

Fire Control Room				
Detector System Panel	N/A	N/A	N/A	
Flow Switch Panel	N/A	N/A	N/A	
	N/A	N/A	N/A	
	N/A	N/A	N/A	
building Floor Plans	N/A	N/A	N/A	
Special Fire Protection System for Protection of special Risks, if any:	N/A	N/A	N/A	
	 Detector System Panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans Special Fire Protection System for Protection	Detector System Panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans Special Fire Protection System for Protection N/A N/A N/A	● Detector System Panel N/A N/A ● Flow Switch Panel N/A N/A ● PA System Panel N/A N/A ● Battery backup N/A N/A ● Building Floor Plans N/A N/A Special Fire Protection System for Protection N/A N/A	

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. The shortcomings communicated by this department vide letter no. ADO/JKP/341 dated 17.10.17 has been complied.

Keeping in view of the above substantial compliance of the minimum standards of fire prevention and fire safety measures as required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Signature of Inspecting Officer

Name: - M.K. Chattopadhyay

Designation:- Divisional Officer

Signature of Inspecting Officer

Name: - Sandeep Duggal

Designation: - Asstt. Divisional Officer

7857 DOKW

Dy. C.F.O. (South Zone)

PESERVICE PESERV

Go St

m. scell

HTM. Veole

F.T. lefter is party for signature phose.

clocs m. scell lie