GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6/DFS/MS/2018/ Motel 2015

Carrie Contract

Dated 31/08/18

FIRE SAFETY CERTIFICATE

Road, opp. Jain Mandir, Jind Pur Delhi-110036 comprised of basement, ground and 01 upper floors owned/occupied by D.S. Motels Pvt. Ltd.(Lee Garden Victorian Palace) was issued fire safety certificate vide letter no. F6./DFS/MS/2014/Motel/WZ/453 dated 07/04/2014. The premise was re-inspected by the officer concerned of this department on 14.08.2018 in the presence of Sh. Tarandeep, Care Taker and observed that all the fire prevention and fire safety arrangements as provided in the premise found in good working condition. The premise have therefore deemed complied with the requirements under rule 33 of the Delhi Fire Service Rules, 2010 and the building premise is fit for occupancy under "Class Assembly Buildings" with effect from 31.1.2.1.2... for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under rule 40, subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010,

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on **WWW.dfs.Delhigovt.nic.in**
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

Issued on 3)/38/18... at New Delhi by

Chief Fire Officer Ph-011-23414250

DIA

Copy to:-

1. M/s D.S. Motels Pvt. Ltd.(Victorian Palace), G.T. Karnal Road, opp. Jain Mandir , Jind Pur, Delhi-36.

INSPECTION REPORT

1. Name & address of the building: D.S.Motels Pvt. Ltd.(Victorian Palace), G.T. Karnal Road, opp. Jain Mandir,

Nangli Poona, Delhi-110036.

2. Type of Occupancy

:Assembly D-5 Basement+ Ground & One upper floor

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/2014/Motel/WZ/453 dated 07/04/2014

5. Fire Safety directives letter No

: F6/DFS/MS/BP/2005/1177 dated 07/06/2014

6. Date of inspection

:14.08.2018

7. Name of the Inspecting Officers

: ADO (RN)

8. Name and designation of officers

from the building side

: Sh. Tarandeep (Care Taker)

9. Year of Construction

.

10. Applicant's letter No.

: Nil dated 02.08.2018

Winimun	n Standards on fire prevention and fire safety U/R 33	NBC/ BBL Requirement	Provided at site	Remarks MR/NMR	
Access to b	uilding				
• Ro	ad width	09m	09m	MR	
• Ga	te width	06m	06m	MR	
	dth of internal road	06m	06m	MR	
Number, Width, Type & Arrangement of Exits					
a. Number of staircases					
• Up	per Floors	02	02	MR	
• Bas	ements	03	03	MR	
b. Width of s	taircases				
• Upp	per Floors	1.50 m each	1.50m & 1.13m	MR(old case)	
Bas c. Protection	ements of exits	1.50m each	1.50m,1.05m & 2.00m	MR(old case)	
• Fire	check door	Required	Provided	MR	
• Pres	surization	NA	NA	NA	
d. No. of con	tinuous staircases to terrace	NA	NA	NA	
e. Width of C	orridor	Required	Provided	MR	
f. Door Size		2.00m	3 exits 1.10, 1.45 & 2m	MR	

	• Fire check door	Required	Provided	MR		
	Sealing of electrical shafts	Required	Provided	MR		
	• Fire Rating of shaft door	NA	NA	NA		
	Water Curtain	NA	NA	NA		
	Fire Dampers	NA	NA	NA		
4	Smoke Management System.					
	• Basements	30 a/c per hour	Exhaust fan	MR		
	• Upper floors	12 a/c per hour	Natural Ventilated	MR		
5	Fire Extinguishers					
	Total numbers	15nos	16 nos	MR		
	• Types	ABC & Co2	ABC-16	MR		
	ISI marking	Yes	Yes	MR		
Ó	First-Aid Hose Reels.					
	Total numbers on each floor	01	01	MR		
	Length of hose reel hose	30m	30m	MR		
	Nozzle diameter	5mm	5mm	MR		
	Automatic fire detection and alarming system.					
	Type of detectors	NA	NA	NA		
	Location of Main Panel	NA	NA	NA		
	Location of Repeater Panel	NA	NA	NA		
	Alternate source of power	NA	NA	NA		
	Hooters' Location	NA	NA	NA		
	MOEFA	Required	Provided	MR		
	Public Address System.	Required	Provided	MR		
)	Automatic Sprinkler System.					
	Basement	Required	Provided	MR		
	• Upper Floor	Required	Provided	MR		
	 Sprinkler above false ceiling 	NA	NA			
	Internal Hydrants		INA	NA		

	Size of riser/down-comer	100mm	Provided	MR	
	Number of hydrants per floorHose Box	02	Provided	MR	
		02	Provided	MR	
2	Yard Hydrants.			<u> </u>	
	Total number of hydrants	02	Provided	MR	
	Hose Box	02	Provided	MR	
13	Pumping Arrangements.	9			
	Ground Level			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
	➤ Discharge of main Pump	2280 lpm	2280 lpm	MR	
	 ➢ Head of Main pump ➢ Number of main pumps 	60m	60m	MR	
	Number of main pumpsJockey Pump out put	2	Provided	MR	
	> Jockey pump head	180 lpm	Provided	MR	
	Standby Pump out put	40 m	Provided	MR	
	> Standby Pump Head	2280 lpm	2280 lpm	MR	
	Auto Starting/ Manual stoppingPump House Access	60m	60m	MR	
	Terrace level	Required	Provided	MR	
	Discharge of pump			I.	
	Head of the pump	NA	NA	NA	
	> Power Supply	NA	NA	NA	
	Auto Starting of pump	NA	NA	NA	
		NA	NA	NA	
4	Captive Water Storage for fire fighting.				
	Underground tank capacity	1,00,000 ltr.	1,00,000 ltr.	MR	
	Draw-off connection	NA	NA	, NA	
	Fire service inlet	NA	NA -	NA	
	Access to tank	NA	NA	NA	
	Overhead Tank capacity	10,000 ltr	10,000 ltr.	MR	
5	Exit Signage.	Required	Provided	MR	
5	Provision of Lifts.				
	Pressurization of Lift Shaft	Required	Lift close in	MR	
	Pressurization of Lift lobby	s -	basement		
		Required	Provided	MR	

	Communication In lift Con			
	Communication in fift Car	Required	Provided	MR
	Thomair 5 Grounding Switch	Required	Provided	MR
	Lift Signage	Required	Provided	MR
7	Standby power supply	Required	Provided	MR
	Refuge Area.			
	Total Area			
	Total Mea	N/A	N/A	N/A
	Location	N/A	N/A	N/A
	Fire Control Room			
- [
	Detector System Panel	N/A	N/A	N/A
	Detector System PanelFlow Switch Panel	N/A N/A	N/A N/A	
		N/A	N/A	N/A
	• Flow Switch Panel		Е	
	Flow Switch PanelPA System Panel	N/A	N/A	N/A
	Flow Switch PanelPA System PanelBatter backup	N/A N/A	N/A N/A	N/A N/A

The fire protection systems provided in the building were tested/ checked randomly and found in good working conditions. The Party has complied all the observations issued vide this department letter of even no. 1415 dated 30.05.2017.

Keeping in view of the satisfactory compliance of the minimum standards on fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. 453 dated 07.04.2014 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Name: - Rajesh Kumar

Designation:- ADO/RN