GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/EH/SZ/2018/2634

FIRE SAFETY CERTIFICATE

Certified that the M/s. Social Affaire Restro Bar located at 17A/12, Gurudwara Road, Karol Bagh, New Delhi- 110005 is running on the ground floor of a building comprised of basement, ground plus three upper floors. The premises was inspected by the officer concerned of this department on 26/07/2018 in presence of Sh. Subrata Dey, General Manager of the restaurant & Bar and found that owner/occupier have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class assembly (restaurant) with effect from Officer concerned of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 25 09 2018 at New Delhi by.

(VIPEN KENTÁL) CHIEF FIRE OFFICER

Dated: 05 09 2018

Copy to:-

 Smt. Jaspal Kaur W/o Sh. Jagmohan Singh, M/s. Social Affaire Restro Bar, 17A/12, Ground Floor, Gurudwara Road, Karol Bagh, New Delhi- 110005.

2. The Deputy Health Officer, North Delhi Municipal Corporation, Karol Bagh Zone, New Delhi- 110005.

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: M/s. Social Affaire Restro Bar, 17A/12, Ground Floor,

Gurudwara Road, Karol Bagh, New Delhi- 110005

2. Type of Occupancy : Assembly (Restaurant)

3. Type of Case : New Case

4. Details of previous NOC : N/A5. Fire Safety directives letter No : N/A.

6. Date of inspection : 26.07.2018

7. Name of the Inspecting Officers: M.K. Chattopadhyay, Divisional Officer (SW)

8. Name and designation of officers

from the building side : Sh. Subrata Dey, General Manager

9. Year of Construction : Before 1994

10. Applicant's letter No. : DHO/KBZ/2018/685 dated 10.07.2018

The said restaurant is running at Ground Floor of a building comprised of basement, ground plus three upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Requirement as BBL-83 / NBC-IV	Provided at site	Remarks MR/NMR			
1	Access to building						
	Road width	06 mts	Provided	MR			
	Gate width	4.5 mts	Directly accessible	MR			
	Width of internal road	N/A	N/A	N/A			
2	Number, Width, Type & Arrangeme	ent of Exits					
	a. Number of staircases	-	- , · ;	_			
	Upper Floors	N/A	Restaurant/Bar at GF				
	Basements	N/A	N/A	N/A			
	b. Width of staircases	-	IVA	N/A			
	 Upper Floors 	N/A	N/A	N/A			
	• Basements	N/A	N/A	N/A			
	c. Protection of exits	-		IN/A			
	Fire check door	N/A	N/A	N/A			
	 Pressurization 	N/A	N/A				
	e. No. of continuous staircases to terrace		01	N/A			
	g. Width of Corridor	N/A	N/A	NI/A			
	h. Door Size	02 mts	2.0 mts, 1.0 mts	N/A MR			
	Compartmentation.		2.0 mts, 1.0 mts	IVIK			
	• Fire check door	N/A	N/A	N/A			
	 Sealing of electrical shafts 	N/A	Sealed	1V/A			
	• Fire Rating of shaft door	N/A	N/A	N/A			
	• Water Curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			
	Smoke Management System.			1 1/4 1			
	Basements	30 a/c per hour	Exhaust fan provided	MR			
	• Upper floors	12 a/c per hour	Natural ventilation	MR			
	Fire Extinguishers						
	 Total numbers 	08	Provided	MR			
			110 rided	IVIK			

		• Types		CO				
		• IS marking	S ₂ Years or an	CO ₂ , ABC type	Provid	ed	MR	
	6	First-Aid Hose Reels.		ISI marked	Provid	ed	MR	
y .	1	Total numbers on each floor	or	0.1				-
8	 Length of hose reel hose Nozzle diameter Automatic fire detection and alarn 		01	01 30 m	Provided Provided Provided		MR	
				50 m			MR	1
			rmina	J IIIII			MR	
		Type of detectors	rilling s					
				N/A	N/A	the throat and a second	N/A	
	Bocation of Main Panel			N/A	N/A		N/A	
		Location of Repeater Panel		N/A N/A			N/A	
		 Alternate source of power 		N/A	N/A			
		 Hooters' Location 		N/A			N/A	
8		MOEFA			N/A		N/A	
9		Public Address System.		Required	Provided	in a soliday	MR	
1() A	Automatic Sprinkler System.		N/A	N/A	in the second	N/A	
		• Basement		Required				
		 Upper floors 			Provided	et de se inne ta que et tra	MR	
		 Sprinkler above false ceiling 		N/A	N/A	ternik disperses	N/A	
11	In	iternal Hydrants		N/A	N/A		N/A	
		Size of riser/down-comer						
		Number of hydrants per floor	l	Required	Provided		MR	
		• Hose Box		01	Provided		MR	
12				01	Provided			
12	Yard Hydrants.						MR	
		Total number of hydrants		N/A	N/A		NT/A	
13	Dus	Hose Box		N/A	N/A		N/A	
15	I UI	nping Arrangements.			IVA		N/A	
		Ground Level Discharge of main p			-			
		Discharge of main PumpHead of Main pump		N/A	N/A		N/A	
		Number of main pumps		N/A	N/A	The same of the sa	N/A	
		Jockey Pump out put		V/A	N/A		N/A	
		Jockey pump head		N/A	N/A		N/A	
-		Standby Pump out put		J/A	N/A	According	N/A	
		Standby Pump Head		J/A	N/A	1	V/A	
		Auto Starting/ Manual stopping		i/A	N/A	1	N/A	
	,	Pump House Access		/A	N/A N/A		J/A	
	•	Terrace level Discharge of records			IV/A	N	I/A	
		Discharge of pump Head of the pump	450	LPM				
	The same of the sa	Toda of the pump	30 r		Provided	M	IR .	

		Power Supply	Required	Provided	MR			
		Auto Starting of pump	Required	Provided	MR			
14	Capti	ve Water Storage for fire fight	ing.					
	•	Underground tank capacity	N/A	N/A	N/A			
	A	Draw-off connection	N/A	N/A	N/A			
		Fire service inlet	N/A	N/A	N/A			
		Access to tank	N/A	N/A	N/A			
	•	Overhead Tank capacity	20,000 lts	Provided	MR			
15	Exit S	ignage.	Required	Provided	MR			
16	Provis	ion of Lifts.			WIK			
	/	Pressurization of Lift Shaft	N/A	N/A	N/A			
		Pressurization of Lift lobby Communication In lift Car	N/A	N/A	N/A			
		Fireman's Grounding Switch	N/A	N/A	N/A			
	•	Lift Signage	N/A	N/A	N/A			
7			N/A	N/A	N/A			
		y power supply	Required	Provided (125 KVA)	MR			
8	Refuge	uge Area.						
		Total Area	N/A	N/A	N/A			
		Location	N/A	N/A	N/A			
)	Fire Co	ntrol Room			11/21			
	•	Detector System Panel	N/A	N/A	N/A			
		Flow Switch Panel	N/A	N/A	N/A			
-	•	PA System Panel	N/A	N/A	N/A			
		Building Floor Pl	N/A	N/A	N/A			
+		Building Floor Plans	N/A	N/A	N/A			
-22	Protectio	Fire Protection Systems for n of special Risks, if any:	Required	Two ABC type fire extinguisher found provided near elect. panel	MR			

. The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules, it is recommended to grant fire safety certificate under Delhi Fire Service Act-2007 & Rules- 2010.

DFA is put up for approval & signature please

M.K. CHATTO ADHYAY Divisional Officer (South West)

of Construction paper Kitchen