GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI

No.F6/DFS/MS/GH/NDZ/2018/ 2063

FIRE SAFETY CERTIFICATE

Certified that the M/s Hotel Taj Mahal located at 747, Church Mission Road, Fatehpuri, Delhi comprised of Ground + 03 Upper floors, Ground floor (Commercial use), 1st floor (10 guest rooms + reception + office + kitchen for staff), 2nd floor (11 guest rooms) and 3rd floor (08 guest rooms), total 29 guest rooms owned/occupied by M/s Hotel Taj Mahal was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/1004 dated The premises was re-inspected by the officer concerned of this department on 10/08/18 in the presence of Sh. Manish (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 29 guest rooms at 1st to 3rd floor only with effect from -1919 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 19-118---at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service O/L M

Copy to:-

- 1. The Addl. Commissioner of Police (Lic). First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager, M/s Hotel Taj Mahal at 747, Church Mission Road, Fatehpuri, Delhi. Condition for the validity of fire safety certificate
 - 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
 - 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
 - 3. The trained fire fighting staff should be available round the clock.
 - 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
 - 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
 - 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
 - 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
 - 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' | sub rule (I) of rule 37 | along with a copy of this Certificate, six month prior to its expiry".

YA Yan and and and and and and and and and a		_	-	-	_
INSPECTION	R	ED	0	D	Г
	1/			1/	

1. Name & address of the building M/s Hotel Taj Mahal at 747, Church Mission

Road, Fatehpuri, Delhi

2. Type of occupancy:-Residential, Sub Division-A-1

Gr. + 03 Upper floors (total 29 Guest rooms) Ground floor (Commercial use), 1st floor (10 guest rooms + reception + office + kitchen for staff), 2nd floor (11 guest rooms) and 3rd floor (08 guest rooms)

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/2015/1004 dated 15/06/15.

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

N/A

10/08/18

Sh. Manoj Kumar Sharma (ADO/CC)

Sh. Manish (Manager)

Old

3907/Addl. C.P/Lic. (H) dated 08/06/2018.

S.No.	Minimum Standards and C D in the C.17 Etc. (H) dated 08/06/2018.				
	Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	N/A	18 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3) Width of internal road	N/A	NI/A	N/A	
2.	Number, Width Type & Ar	rangement of	Evite	IN/A	
	A. Number of staircases	8			
	1. Upper floors	02 Nos.	02 Nos.	NAD	
	2. Basements	N/A	N/A	MR	
	B. Width of staircase		IV/A	N/A	
	1. Upper floors	0.80 mtr.	1 & 1.25 mtr.	MD	
	2. Basements	N/A	NI/A	MR	
	C. Protection of exits		IN/A	N/A	
	1. Fire check door	N/A	N/A	21/4	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	N/A	02	N/A	
	staircase to terrace		02	N/A	
	E. Width of corridor	N/A	N/A	21/4	
	F. Door size	1 mtr.	1 mtr.	N/A	
	Compartmentation		1 IIICI.	MR	
	1) Fire check door	N/A	N/A	NT/ A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
	Smoke Management System		IV/A	N/A	
	1) Basements	30 ACPH	N/A	NI /A	
	2) Upper floors	12 ACPH	N/A	N/A	
	Fire Extinguishers		1 1//1	N/A	
	1) Total numbers	10 Nos.	10 Nos.	MD	
		·	TO INUS.	MR	

	2) Types	ABC & CO2		
	3) ISI marking			
6.	First-Aid Hose Reel	Required	Provided	MR
	1) Total number of eachfloor	r 01		
	2) Length of hose reel hose		01	MR
	3) Nozzle diameter	30 mtr.	30 mtr.	MR
7.	Automatic Fire Detection of	05 mm	05 mm	MR
	Automatic Fire Detection & 1) Type of detectors	& Alarming Sys		
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location		N/A	N/A
8.	MOFFA	N/A	N/A	N/A
9.	MOEFA	N/A	N/A	N/A
10.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	1		IVII
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	
11	ceiling		1.477	N/A
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	DI/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor		1 1/ / /	N/A
10	3) Hose box	N/A	N/A	27/4
12.	Yard Hydrants		IVA	N/A
	1) Total number of hydrants	N/A	N/A	
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement		IV/A	N/A
	1) Ground level	N/A	NI/A	
	a) Discharge of main	N/A	N/A	N/A
	pump	14/74	N/A	,N/A
	b) Head of main pump	N/A	NIZA	
	c) Number of main pump	N/A N/A	N/A	N/A
	d) Jockey pump out put	27/1	N/A	N/A
	e) Jockey pump head	27/1	N/A	N/A
	f) Stand by pump output	27/1	N/A	N/A
	g) Stand by pump head	2.1.	N/A	N/A
	h) Auto starting/Manual		N/A	N/A
	stopping	N/A	N/A	N/A
	2) Terrace level			
	a) Discharge of pump	225 1 D3 4		
	b) Head of pump	20	225 LPM	MR
	c) Power supply	-	30 mtr.	MR
	d) A	D	Provided	MR
4.		Required F	Provided	MR
	Captive Water Storage for Fire			
	Under ground tank capacity	N/A	V/A	N/A
H	a) D 00			
	a) Draw-off connection	J/A N	I/A	N/A

	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	N/A
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
9	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	. N/A
20.	Special Fire Protection Syst Risk, if any:	tem for Protec	ction of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/1004 dated 15/06/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFO/NDZ

m.scell response

F.f. letter is put up for hy