## GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001 Fax No. 011-23412593, Ph. 011-23412225

No. F6/DFS/MS/School/2018/SZ/ 2122

## **FIRE SAFETY CERTIFICATE**

Certified that **Sarvodaya Vidyalaya No-1** located at Sec-2,R.K.Puram,New Delhi-110022 comprised of ground plus two upper floors (one block), ground plus one upper floors (one block) both block are interconnected owned/occupied by Director of Education was granted Fire Safety Certificate by this department vide letter No. F.6/DFS/MS/2015/SZ/851 Dated 26/05/2015. The premises was reinspected by officer concerned of this department on 24/08/2018 in presence of Mrs. Rupa Singh (Principal) and observed that the said School building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class "**Educational Building**" Group-B, with effect from the date of issue of this certificate for a period of **Three years** in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 17/9/18 at New Delhi by

(Vipin Kental)
Chief Fire Officer

Copy to: -

- 1. The Principal, Sarvodaya Vidyalaya No-1, Sec-2, R.K. Puram, New Delhi-110022
- 2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi.

## Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. This Certificate cannot be treated as regularization of unauthorized construction, if any.
- 5. The Owner/Occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules, 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 6. The Owner/Occupier shall apply for renewal of this Fire Safety Certificate to the Director in the form 'J' [sub rule (1) of rule 37] along with copy of this certificate, six months prior to its expiry. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.

-	Name & Address of the Building					
1	Name & Address of the Building	Sarvodaya Vidyalaya No. 1 G. 2 B. 7				
	- JPC OI Occupancy					
	Building Comprised of	Culcationa	l, Group-B (School)			
	4 Type of Coss	U + U2 (One Block) G+1(One F		lock) both bi		
	1 Jpc of Case	Parad	interconnect.			
	Betails of Previous NOC	Renewal				
	6 Fire Safety Directives Letter No 7 Date of Ingressi	F6/DFS/MS/2015/SZ/851 Dated 26/05/2015				
	Date of Inspection					
	Name of the Inspecting Officers	24-08-2018				
1	Name & Designation of Office	Mehmood, A	ADO (SJ)			
1	Holli the building side	Mrs. Rupa S	ingh (Principal)			
1	Year of construction	10(2.0.00				
	Tippiicant letter No	1962 & 2010				
S. N	Stalldards on Fine D.	1663/SV.No1/R.K.Puram Sec2 dated 09.07		07 2019		
1	The Safety U/R 33		Provided at Site	Remarks		
1	Access to Building.	NOC		MR/NMI		
	<ul> <li>Road width</li> </ul>			1411/14141		
	Gate width	6 mtr	Provided	MR		
	Width of internal road	5m	5m	MR		
2	Number, width, type & arrangement of e	NA-	-NA-			
	a) Number of Staircase	exits.	-	-NA-		
	Upper floors.					
	Basement floor.	Three	Three Three			
	b) Width of Staircast	-NA-	-NA-	MR		
	Jack of Staff Case		-INA-	-NA-		
	<ul><li>Upper floors</li><li>Basement floor</li></ul>	1.5 mtr	G+2 1 (2)			
	c) Protection of oxide	-NA-	G+2- 1.62 m each G+1- 1.50	m MR		
	- rotection of exits		-NA-	-NA-		
	Fire check door	-NA-		я		
	Pressurization	-NA-	-NA-	-NA-		
	d) No. of continuous staircase to terrace		-NA-	-NA-		
	-7 Width of corridor	-NA-	-NA-	-NA-		
_	f) Door size	1.5m	Provided	MR		
3	Compartmentation.	1 m	Provided	MR		
	• Fire check door.			IVIR		
	Sealing of electrical shafts.	-NA-	-NA-	NIA		
	• Fire rating of shaft door.	-NA-	-NA-	-NA-		
	Water curtain	-NA-	-NA-			
	• Fire dampers.	-NA-	-NA-	-NA-		
4.	Smoke Management system.	-NA-	-NA-	-NA-		
	Basement	N. C.	1 1/1 1-	-NA-		
	Upper floors	30 ACPH	-NA-	27.		
5.	Fire Extinguishers.	12 ACPH	-NA-	-NA-		
	Total must		-IVA-	-NA-		
	• Total numbers	18 Nos	22 NI			
	Types	ABC / CO2	23 Nos	MR		
		ISI marked	ABC & Co2	MR		
	• ISI Marking		Provided	MR		
	First Aid Hose Reels.	marked				
•	First Aid Hose Reels.  Total numbers on each floor.					
	First Aid Hose Reels.  Total numbers on each floor.	Two	Provided	MR		
	First Aid Hose Reels.		Provided Provided	MR MR		

	• Location	-NA-	-NA-	-NA-
		N. I. A.		5 B
	• Total area			
	Refuge Area	-NA-	-NA-	-NA-
7.	Standby Power Supply	-NA-	-NA-	-NA-
	Lift signage.	-NA-	-NA-	-NA-
	<ul><li>Communication in lift car.</li><li>Fireman's switch.</li></ul>	-NA-	-NA-	-NA-
	Pressurization of lift lobby.     Communication in 159.	-NA-	-NA-	-NA-
	Pressurization of lift shaft.  Pressurization of lift 1.1.1.	-NA-	-NA-	-NA-
				IVIK
	Provision of Lifts.	Required	Provided	MR
5.	Exit Signage.	10,000 Ltr	Provided	MR
	Overhead tank capacity.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
	<ul><li>Draw-off connection.</li><li>Fire Service Inlet.</li></ul>	-NA-	-NA-	-NA-
	Underground tank capacity.      Draw-off connect:	-NA-	-NA-	-NA-
	• Underground to !!	-	Trovided	MIK
14.	Captive water storage for fire fighting.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	MR
	Power supply.	40m	40 M each	MR
	Head of pump.	450 LPM	450 LPM X 2	MR
	> Discharge of pump.			-11/A-
	Terrace Level	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
	Auto Starting / Manual Stopping	-NA-	-NA-	-NA-
	Standby Pump head	-NA-	-NA-	-NA-
	Standby Pump output	-NA-	-NA-	-NA-
	Jockey Pump head	-NA-	-NA-	-NA-
	Jockey Pump output	-NA-	-NA-	-NA-
	Number of main pumps	-NA-	-NA-	-NA-
	Head of main pump	-NA-	-NA-	-NA-
	Discharge of main pump	NT A		
	Ground Level			
13.	Pumping arrangements.	-1NA-	-NA-	-NA-
12	• Hose box.	-NA-	-NA-	-NA-
	<ul> <li>Total number of hydrants.</li> </ul>	-NA-	N. I.	
14.	Yard Hydrants.	1111	-NA-	-NA-
12.	TIOSC DOX.	-NA-		-NA-
	rumber of flydrant per floor	-NA-	-NA-	-NA-
	Size of Riser/Down-comer	-NA-	-NA-	D.T.A.
-41	Size of Picce/D		1111	-NA
11.	• Sprinkler above false ceiling Internal Hydrants.	-NA-	-NA-	
	• Sprinkler -1	-NA-	-NA-	-NA
	<ul><li>Upper floors</li></ul>	-NA-	-NA-	-NA
	Automatic Sprinkler System  Basement		1121	-NA
10.	Automatic Sprinkley S.	-NA-	-NA-	-NA
9.	Public Address System	-NA-	-NA-	-NA
8.	MOEFA	-NA-	-NA-	
	<ul><li>Alternate source of power</li><li>Hooter's location</li></ul>	-NA-	-NA-	-NA
	• Location of Repeater Panel	-NA-	-NA-	-NA
	Location of Main Panel     Location of Main Panel	-NA-	-NA-	-NA
1				
	• Type of detectors	-NA-	-NA-	77.

19.	Fire Control Room.			
	<ul> <li>Detector system panel.</li> <li>Flow switch panel.</li> <li>PA system panel.</li> </ul>	-NA- -NA-	-NA- -NA-	-NA-
	<ul> <li>Battery backup.</li> <li>Building floor plan.</li> <li>Special Fire Protection System for the Protection of special Risk, if any.</li> <li>The Fire protection systems provided in</li> </ul>	-NA-	-NA- -NA-	-NA-
		-NA-	-NA- ABC type fire extinguisher provided near electrical panel	-NA-

on systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rule, FSC issued vide letter No. F.6/DFS/MS/2015/SZ/851 dated 26/05/2015, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Mehmood Design: ADO (SJ)

A. Bot. Seller Book of Signorine Glosse

A. Dot. Seller Book of Signorine Glosse

12/7/18 Morris