GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 2 19 6

Dated: -27/9/18-

FIRE SAFETY CERTIFICATE

Certified that the Maha Laxmi Guest House located at 2682/8, Chuna Mandi, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floor, Ground floor (Reception + 01 office + 01 guest rooms), 1st floor to 3rd floor (04 guest rooms at each floor) and 4th floor (02 guest rooms), total 15 guest rooms owned/occupied by Maha Laxmi Guest House was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/NDZ/1394 dated 04/08/15. The premises was re-inspected by the officer concerned of this department on 14/09/18 in the presence of Mr. Balbir Singh (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 15 guest rooms only with effect from -2-7-19-1-3----for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -- 2-7-1-8---at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager, Maha Laxmi Guest House at 2682/8, Chuna Mandi, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

		CTION REPO	<u>KI</u>	00/0 (01			
1.	Name & address of the building		i Guest House at 26	82/8, Chuna			
		Mandi, Pahar Ganj, New Delhi Residential, Sub Division-A-1 Ground + 04 upper floor, total 15 guest rooms Ground floor (Reception + 01 office + 01 guest rooms), 1st floor to 3rd floor (04 guest rooms at each					
2.	Type of occupancy:-						
			floor (02 guest rooms)				
3.	Type of case:-	Renewal					
	Details of previous FSC:-	No. F6/DFS/MS/GH/2015/NDZ/1394 dated 04/08/15.					
_	E' - Cota dinastivas No						
	J. The safety directives 1.5						
	Bute of hispection.						
/.	Name of the inspecting officer:- Sh. Manoj Kumar Sharma (ADO/CC) Name & designation of officer						
٥.	From the building side:-	Mr Balbir	Singh (Manager)				
0	Year of construction:-	0					
). Applicant's letter No:-	Nil dated 30/08/2018.					
S.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks			
5.110.	Prevention and fire safety	Existing fire		MR/NMR			
	U/R 33	safety		=			
		arrangements	•	1			
1.	Access to Building	27/4	3,60 mtr.	MR			
	1) Road width	N/A		N/A			
	2) Gate width	N/A	N/A				
	3) Width of internal road	N/A	N/A	N/A			
2.	Number, Width Type & Arra	angement of E	xits				
	A. Number of staircases) (D			
	1. Upper floors	01 Nos.	01 Nos.	MR			
	2. Basements	N/A	N/A	N/A			
	B. Width of staircase			100			
	1. Upper floors	0.80 mtr.	1.15 mtr.	MR			
	2. Basements	N/A	N/A	N/A			
	C. Protection of exits	1		77/4			
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous	N/A	N/A	N/A			
	staircase to terrace	×		27/4			
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size	01 mtr.	1.06 mtr.	MR			
3.	Compartmentation			77/4			
	1) Fire check door	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
4.	Smoke Management System						
53	1) Basements	30 ACPH	N/A	N/A			
	2) Upper floors	12 ACPH	Natural	MR			

5.	Tring ID	1			
5.	Fire Extinguishers				
	1) Total numbers	10 Nos.	10 Nos.	MR	
	2) Types	ABC & CO2	ABC & CO2	MR	
-	3) ISI marking	Required	Provided	MR	
6.	First-Aid Hose Reel				
	1) Total number of eachfloor	01	01	MR	
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR	
_	3) Nozzle diameter	05 mm	05 mm	MR	
7.	Automatic Fire Detection & Alarming System				
	1) Type of detectors	N/A	N/A	N/A	
	2) Location of main panel	N/A	N/A	N/A	
	3) Location of repeater panel	N/A	N/A	N/A	
	4) Alternate source of power	N/A	N/A	N/A	
	5) Hooter's Location	N/A	N/A	N/A	
8.	MOEFA	N/A	N/A	N/A	
9.	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System		1.0.1000	1411/	
	1) Basement	N/A	N/A	N/A	
	2) Upper floors	N/A	N/A	N/A N/A	
	3) Sprinkler above false	N/A	N/A	N/A	
2	ceiling		1472	IN/A	
11.	Internal Hydrants			3	
	1) Size of riser/down-comer	N/A	N/A	N/A	
	2) Number of hydrants per	N/A	N/A	N/A	
	floor		11/11	IVA	
	3) Hose box	N/A	N/A	N/A	
12.	Yard Hydrants		1777	IN/A	
	1) Total number of hydrants	N/A	N/A	N/A	
	2) Hose box	N/A	N/A	N/A	
3.	Pumping Arrangement			TVIA	
	1) Ground level	N/A	N/A	N/A	
	a) Discharge of main	N/A	N/A	N/A N/A	
	pump		14/11	IN/A	
	b) Head of main pump	N/A	N/A	N/A	
	c) Number of main pump	N/A	N/A	N/A	
·	d) Jockey pump out put	N/A	N/A	N/A	
	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump output	N/A	N/A	N/A	
	g) Stand by pump head	N/A	N/A	N/A	
	h) Auto starting/Manual	N/A	N/A	N/A N/A	
	stopping	14/11	14/14	IN/A	
	2) Terrace level			8	
	a) Discharge of pump	225 LPM	225 LPM	MD	
	b) Head of pump	30 mtr.	30 mtr.	MR	
	c) Power supply	Required	Provided Provided	MR	
	d) Auto starting of pump			MR	
	-) Traco starting of pullip	required	Provided	MR	

My

14.	Captive Water Storage for Fire Fighting				
2	1) Under ground tank capacity	N/A	N/A	N/A	
	a) Draw-off connection	N/A	N/A	N/A	
	b) Fire service inlet	N/A	N/A	N/A	
	c) Access to tank	N/A	N/A	N/A	
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR	
15.	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts.			IVIIC	
	a) Pressurization of lift shaft	N/A	N/A	N/A	
	b) Pressurization of lift lobby	N/A	N/A	N/A	
	c) Communication in lift car	N/A	N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
1=	e) Lift signage	N/A	N/A	N/A	
17.	Stand by Power Supply	Required	Provided	MR	
18.	Refuge Area	N/A	N/A	N/A	
	Total area location	N/A	N/A	N/A	
19.	Fire Control Room	N/A	N/A	N/A	
	a) Detector system panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
_	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A	
	e) Building floor plan	N/A	N/A	N/A	
20.	Special Fire Protection Syster Risk, if any:	m for Protect	ion of special	N/A	

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire as required under the rules the FSC issued vide measures F6/DFS/MS/GH/2015/NDZ/1394 dated 04/08/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation: - ADO (CC)

Dy. CFO/NDZ

chown CFCP- miscell F710.
W2019.

G. F.-T. Letter is put up fu