GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 2435

Dated: 30/10/18

FIRE SAFETY CERTIFICATE

Certified that the Maurya Assam Guest House located at 7963, Arakashan Road, Pahar Ganj, New Delhi comprised of Ground + 02 upper floor, Ground floor (Reception + 01 guest rooms), 1st floor (03 guest rooms), 2nd floor (03 guest rooms), total 07 guest rooms owned/occupied by Maurya Assam Guest House was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/NDZ/1322 dated 22/07/15. The premises was re-inspected by the officer concerned of this department on 14/09/18 in the presence of Sh. Kunal Sharma (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 07 guest rooms only with effect from -2 period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 32 to 1-12--- at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager, Maurya Assam Guest House at 7963, Arakashan Road, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

N/22

	INS	SPECTION REP	PORT				
1	INSPECTION REPORT Name & address of the building Maurya Assam Guest House at 7963,						
			n Road Pahar Cani	Now Dalls:			
2	Type of occupancy:-	Arakashan Road, Pahar Ganj, New Delhi					
	Type of occupancy:- Residential, Sub Division-A-1 Ground + 02 upper floor, total 07 guest rooms						
	Ground floor (Reception + 01 guest rooms), 1 st floor (03 guest rooms)						
ž	Type of case:- Renewal						
2	Details of previous FSC:- No. F6/DFS/MS/GH/2015/NDZ/1322 dated 22/07/15.						
5	Fire safety directives No N/A Date of inspection:- 14/09/18 Name of the inspecting officer:- Sh. Manoj Kumar Sharma (ADO/CC)						
6							
7							
8	Name & designation of office	r	U 201				
	From the building side:-	Sh. Kunal	Sharma (Manager)				
	. Year of construction:-		(·····································				
1	0. Applicant's letter No:-	Nil dated 0	04/09/2018.				
S.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks			
	Prevention and fire safety	Existing fire	a so vided at Site	MR/NMR			
	U/R 33	safety	41	TVITOTATION			
Ι,	Access to Building	arrangements					
	1) Road width	N/A	06 mtr.	MR			
	2) Gate width	N/A	N/A	N/A			
	3) Width of internal road	N/A	N/A				
1				N/A			
	Number, Width Type & Arrangement of Exits A. Number of staircases						
	1. Upper floors	01 Nos.	01.21	1.00			
	2. Basements	N/A	01 Nos.	MR			
	B. Width of staircase	IN/A	N/A	N/A			
	1. Upper floors	0.00	0.00				
	2. Basements	0.80 mtr.	0.93 mtr.	MR			
	C. Protection of exits	N/A	N/A	N/A			
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous	N/A	N/A	N/A			
	staircase to terrace						
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size	01 mtr.	1.06 mtr.	MR			
	Compartmentation			3.0			
	1) Fire check door	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
	Smoke Management System	1	1 1/ 2 k	IN/A			
	1) Basements	30 ACPH	N/A	N/A			
	2) Upper floors	12 ACPH	Natural	MR			
	Fire Extinguishers		1 ratural	IVII			
200	1) Total numbers	08 Nos.	08 Nos.	MD			
	2) Types	ABC & CO2	ABC & CO2	MR MR			
	3) ISI marking	Required	Provided Provided	MR			
	8	required	TTOVIGEG	MR			

6.	First-Aid Hose Reel			
0.	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &			IVIIC
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	N/A	N/A	N/A
10.	Automatic Sprinkler System	IVA	IN/A	IN/A
10.	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	1 1// 1	1 1/17	1 1/ 1/2
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor	- M. 7676		
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants			
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement			
, , , , , , , , , , , , , , , , , , , ,	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	·N/A
	pump	=		_
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	Ñ/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping			
	2) Terrace level	*		
	a) Discharge of pump	450 LPM	450 LPM	MR
	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR
14.	Captive Water Storage for Fire Fighting			
	1) Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A

m

_	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.		Tiovided	IVIK
50	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
_	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
× ·	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	m for Protect	ion of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire measures as required under the rules the FSC issued vide F6/DFS/MS/GH/2015/NDZ/1322 dated 22/07/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFONDZ

- CF.P. M. SCELL FT 160.

1/22/X.

F. F. Letter is put up for biggs pl

Mush