## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 2433

Dated: 30/10/18

## **FIRE SAFETY CERTIFICATE**

Certified that the Sky View Guest House located at 4721, Main Bazar, Shora Kothi, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (04 guest rooms + Reception), 1st floor (06 guest rooms), 2nd floor & 3rd floor (07 guest rooms at each floor), 4th floor found sealed, total 24 guest rooms owned/occupied by Sky View Guest House was granted **FSC** by this department No.F6/DFS/MS/GH/2015/NDZ/1568 dated 31/08/15. The premise was re-inspected by the officer concerned of this department on 16/10/18 in the presence of Mr. Imran (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 24 guest rooms only with effect from --- 30+10/-12----- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 30/10/12----at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

 The Manager, Sky View Guest House at 4721, Main Bazar, Shora Kothi, Pahar Ganj, New Delhi.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

· ·	INS	PECTION REPO	ORT				
1.	Name & address of the building			1 Main Razor			
	1/		Sky View Guest House at 4721, Main Bazar Shora Kothi, Pahar Ganj, New Delhi				
2.	Type of occupancy:-		l, Sub Division-A-				
	Gr. + 04 Upper floors (total 24 Guest rooms)						
	Ground floor (04 guest rooms + Reception), 1 <sup>st</sup> floor (06 guest rooms), 2 <sup>nd</sup> floor & 3 <sup>rd</sup> floor (07 guest rooms at each floor), 4 <sup>th</sup> floor found sealed Renewal						
							3.
							Details of previous FSC:-
	31/08/15.						
5.	Fire safety directives No						
	Date of inspection:-	16/10/18					
7.	Name of the inspecting officer:- Sh. Manoj Kumar Sharma (ADO/CC)						
8.	Name & designation of officer						
	From the building side:-	Mr. Imran	(Manager)				
	Year of construction:-	2006					
10.	Applicant's letter No:-	Nil dated 05/1	0/2018.				
				Old Case			
S.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks			
	Prevention and fire safety	Existing fire safety arrangements		MR/NMR			
	U/R 33						
1.	Access to Building						
	1) Road width	N/A	N/A	N/A			
	2) Gate width	N/A	N/A	N/A			
	3) Width of internal road	N/A	N/A	N/A			
2.	Number, Width Type & Arr	angement of Ex	tits				
	A. Number of staircases						
	1. Upper floors	01 Nos.	01 Nos.	MR			
	2. Basements	N/A	N/A	N/A			
	B. Width of staircase						
	1. Upper floors	0.80 mtr.	1.15 mtr.	MR			
	2. Basements	N/A	N/A	N/A			
	C. Protection of exits						
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous	N/A	N/A	N/A			
	staircase to terrace						
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size	1.0 mtr.	1.0 mtr.	MR			
3.	Compartmentation						
	1) Fire check door	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
4.	Smoke Management System						
	1) Basements	30 ACPH	N/A	N/A			
	0) 11 (7		The state of the s				
	2) Upper floors	12 a/c per	Natural	MR			

5.	Fire Extinguishers			
	1) Total numbers	10 Nos.	10 Nos.	
	2) Types	ABC & CO		MR
	3) ISI marking	Required	7 00 002	
6.	First-Aid Hose Reel	required	Provided	MR
1	1) Total number of eachfloo	r 01	0.1	
	2) Length of hose reel hose	30 mtr.	01	MR
	3) Nozzle diameter	05	30 mtr.	MR
7.	Automatic Fire Detection &	Pr Alexania G	05 mm	MR
	1) Type of detectors			
	2) Location of main panel	N/A N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A N/A	N/A	N/A
	5) Hooter's Location	The state of the s	N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	N/A	N/A	N/A
10.	Automatic Sprinkl	Required	Provided	MR
	Automatic Sprinkler System  1) Basement			
		N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false ceiling	N/A	N/A	N/A
11.	Intownal II			1 1/7 1
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per floor	N/A	N/A	N/A
				IN/A
2.	3) Hose box	N/A	N/A	N/A
4.	Yard Hydrants			IN/A
	1) Total number of hydrants	N/A	N/A	N/A
3.	2) Hose box	N/A	N/A	N/A
J.	Pumping Arrangement			IN/A
	1) Ground level	N/A	N/A	NI/A
	a) Discharge of main	N/A	N/A	N/A
	pump		IVA	N/A
	b) Head of main pump	N/A	N/A	21/4
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A		N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping	IVA	N/A	N/A
	2) Terrace level			
	a) Discharge of pump	225 LPM	227 1 22	
	b) Head of pump		225 LPM	MR
	c) Power supply	P .	30 mtr.	MR
	d) Auto starting of pump	D	Provided	MR
	, starting of pump	Required	Provided	MR

4.	Captive Water Storage for F	ire Fighting		NI/A
	Under ground tank     capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2,500 ltr.	2,500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
-	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Sys Risk, if any:	stem for Prote	ection of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire measures as required under the rules the FSC issued vide letter no. safety F6/DFS/MS/GH/2015/NDZ/1568 dated 31/08/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation: - ADO (CC)

Bloloform CER Miscell FTM.

24/x./20/x.

F.T. Letter is put up of