## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 2 3 8 9

Dated : 25/10/18

## FIRE SAFETY CERTIFICATE

Certified that the Guruvas Guest House located at 1049 & 982, Main Bazar, Kumharan, Wali Gali, Pahar Ganj, New Delhi comprised of Lower Ground floor (office), Upper ground floor (reception + 04 guest rooms), 1<sup>st</sup> floor to 3<sup>rd</sup> floor (05 guest rooms), total 19 guest rooms owned/occupied by Guruvas Guest House was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/1761 dated 30/09/15. The premises was reinspected by the officer concerned of this department on 13/10/15 in the presence of Sh. Rajesh and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 19 guest rooms only with effect from ---2-5-1+5----- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued --- 25-10-178--- at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

## Copy to:-

- 1. The Add. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager, Guruvas Guest House, 1049 & 982, Main Bazar, Kumharan Wali Gali, Pahar Ganj, New Delhi.

## Condition for the validity of fire safety certificate

- 1. at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

2110 **INSPECTION REPORT** Name & address of the building:-Guruvas Guest House located at 1049 & 982. Main Bazar, Kumharan wali Gali, Mantola, Pahar Ganj, New Delhi 2. Type of occupancy:-Residential, Sub Division-A-1 L Gr. + U Gr. + 03 Upper floors (total 19 Guest rooms) 3. Type of case:-4. Details of previous FSC:-No. F6/DFS/MS/GH/2015/1761 dated 30/09/15. 5. Fire safety directives No.-N/A 6. Date of inspection:-13/10/18 7. Name of the inspecting officer:-Sh. Manoj Kumar Sharma (ADO/CC) 8. Name & designation of officer From the building side:-Sh. Rajesh 9. Year of construction:-2004 10. Applicant's letter No:-No. Nil dated 04/10/18 Old Case

S.No. Minimum Standards on fire Requirement Provided at site Remarks Prevention and fire safety Existing fire MR/NMR U/R 33 safety arrangements 1. Access to Building 1) Road width Main road N/A N/A 06 mtr. 2) Gate width N/A N/A N/A 3) Width of internal road N/A N/A N/A 2. Number, Width Type & Arrangement of Exits A. Number of staircases 1. Upper floors 01 Nos. 01 Nos. MR 2. Basements N/A N/A N/A B. Width of staircase 1. Upper floors 1.25 mtr. 1.25 mtr. MR 2. Basements N/A N/A N/A C. Protection of exits 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A D. No. of continuous 01 01 MR staircase to terrace E. Width of corridor 1 mtr. 1.10 mtr. MR F. Door size 1 mtr. 1 mtr. MR 3. Compartmentation 1) Fire check door N/A N/A N/A 2) Sealing of electrical shafts N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers N/A N/A N/A 4. Smoke Management System 1) Basements 30 ACPH N/A N/A 2) Upper floors Natural Ventilation 12 a/c per MR hour

5.	Fire Extinguishers			
J.	1) Total numbers	10 Nos.	10 N	
	2) Types	ABC & CO2	10 Nos.	MR
	3) ISI marking		ABC & CO2	MR
6.	First-Aid Hose Reel	Required	Provided	MR
	1) Total number of eachfloor	01	0.1	
	2) Length of hose reel hose	30 m	01	MR
	3) Nozzle diameter		30 m	MR
7.		05 mm	05 mm	MR
/•	Automatic Fire Detection &  1) Type of detectors		The state of the s	
	2) Location of main panel	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
8.	5) Hooter's Location	N/A	N/A	N/A
9.	MOEFA	Required	Provided	MR
10.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
11.	ceiling	-		
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor		. 1	
10	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants		- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	
	1) Total number of hydrants	N/A	N/A	N/A
10	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement			
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump			
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pum		N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump outpu	t N/A	N/A	N/A
	- J paring outope.	t IN/A	1 4/ 2 1	
	g) Stand by pump head	N/A	N/A	
		N/A		N/A
	g) Stand by pump head	N/A	N/A	
	<ul><li>g) Stand by pump head</li><li>h) Auto starting/Manual</li></ul>	N/A	N/A	N/A
	g) Stand by pump head h) Auto starting/Manual stopping	N/A	N/A N/A	N/A N/A
	g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level	N/A N/A	N/A N/A 450 LPM	N/A N/A
	g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump	N/A N/A 450 LPM 30 mtr	N/A N/A 450 LPM 30 mtr	N/A N/A MR MR
	g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply	N/A N/A 450 LPM 30 mtr Required	N/A N/A 450 LPM 30 mtr Provided	N/A N/A  MR MR MR
14.	g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply	N/A N/A 450 LPM 30 mtr Required Required	N/A N/A 450 LPM 30 mtr	N/A N/A MR MR

capacity N/A N/A N/A Draw-off connection N/A N/A N/A b) Fire service inlet N/A N/A N/A c) Access to tank MR 5000 ltr. 5000 ltr. d) Over head tank capacity MR Provided Required Exit Signage. 15. Provision of Lifts. 16. N/A N/A N/A a) Pressurization of lift shaft N/A N/A N/A b) Pressurization of lift lobby N/A N/A N/A c) Communication in lift car N/A N/A N/A d) Fireman's switch N/A N/A N/A e) Lift signage Provided MR Required Stand by Power Supply 17. N/A N/A N/A Refuge Area 18. N/A N/A N/A Total area location N/A N/A N/A Fire Control Room 19. N/A N/A N/A a) Detector system panel N/A N/A N/A Flow switch panel N/A N/A N/A PA system panel N/A N/A N/A Battery backup N/A N/A N/A e) Building floor plan Special Fire Protection System for Protection of special NA 20.

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/1761 dated 30/09/2015 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFO/NDZ

NIV

Risk, if any:

-01.071

809/06 NPZ F-t. letter is put up for 609