GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No. F6/DFS/MS/NDZ/2018/ 2380

Dated: - 23/10/18

FIRE SAFETY CERTIFICATE

Certified that the M/s Usha Gas Service site No. 4, Rajghat Power House, New Delhi comprised of single story building, owned/occupied by M/S Usha Gas Service was granted FSC by this department vide letter No. F6/DFS/MS/LPG/2015/NDZ/1889 dated 19/10/2015. The premises was re-inspected by the officer concerned of this department on 15/10/18 in the presence of Sh. Ajay (Manager) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class ${\bf Hazardous}\ {\bf Group}\ {\bf J}$ with effect from 23 to three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -2-110-179----at New Delhi by.

Chief Fire Officer Delhi Fire Service

Copy to:-

1. The Manager, M/s Usha Gas Service, Site No. 4, Rajghat Power House, New Delhi.

2. The Chief Area Manager, Indian Oil Corporation Ltd.,

6th floor, Surya Kiran Building, 19, K.G. Marg, New Delhi.

Condition for the validity of fire safety certificate

1. "No Smoking" and "Not to use Mobile Phone" sign board should be displayed in such a manner as to be easily readable by all persons.

2. No trade Susceptible to Cause Ignition Petroleum vapors by generating heat, mechanical/electric spark should be allowed within the premises and its vicinity.

3. 04 no's of co2 gas type ISI capacity of 4.5 kg. 02 no's of ABC stored pressure power type ISI capacity 05 kg and 01 numbers of AFFF type ISI capacity 50 ltrs provided should be maintained in proper working order all the time.

4. The working employed at the petrol pump must be taught the correct method of operation

and maintenance of record of the extinguishers be ensured.

5. Overhead electric cable not passing across the licensed premises.

6. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.

7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

| | ~ | 7 | | | |
|-------|--|---------------------------------|------------------|--|--|
| 1 | INSI | PECTION REP | | The second secon | |
| 1. | Name & address of the buildin | | | | |
| 2 | The contract of the contract o | | ise, New Delhi | | |
| 2. | Type of occupancy:- | Hazardous Group J | | | |
| 2 | Trust | Single story building | | | |
| | Type of case:- | Renewal | | | |
| 4. | Details of previous NOC:- | No. F6/DFS/MS/2015/LPG/NDZ/1889 | | | |
| 5 | Fire sofaty directives No | dated 19/10/2015. | | | |
| | Fire safety directives No Date of inspection:- | N/A | | | |
| 7 | Name of the inspecting officer | 15/10/18 | | | |
| | Name & designation of officer | | | | |
| 0. | From the building side:- | | | | |
| 9. | Year of construction:- | Sh. Ajay | | | |
| | Applicant's letter No:- | No Nil dat | ted 27.09.18. | | |
| S.No. | Minimum Standards on fire | Requirement | Provided at site | Remarks | |
| | Prevention and fire safety U/R 33 | Existing fire | and the same | MR/NMR | |
| | | safety | - | | |
| 1. | Access to Building | arrangements | | | |
| 1.0 | | | | 111111111111111111111111111111111111111 | |
| | 1) Road width | 06 mtr. | 15 mtr. | MR | |
| | 2) Gate width | Accessible | Accessible | MR | |
| | 2) Width of internal 1 | 27/4 | directly | | |
| 2. | 3) Width of internal road | N/A | N/A | N/A | |
| 4. | Number, Width Type & Arr A. Number of staircases | angement of E | xits | | |
| | | DI/A | 71/4 | | |
| | Upper floors Basements | N/A | N/A | N/A | |
| | B. Width of staircase | N/A | N/A | N/A | |
| | | NI/A | N//A | | |
| 2 | Upper floors Basements | N/A | N/A | N/A | |
| - | | N/A | N/A | N/A | |
| | C. Protection of exits | NI/A | | | |
| | 1. Fire check door | N/A | N/A | N/A | |
| | 2. Pressurization | N/A | N/A | N/A | |
| • | D. No. of continuous | N/A | N/A | N/A | |
| - | staircase to terrace | NT/A | 71/4 | | |
| | E. Width of corridor | N/A | N/A | N/A | |
| | F. Door size | N/A | N/A | N/A | |

| | and the safety O/R 33 | safety arrangements | | MR/NMR | |
|----|---------------------------------|------------------------|---------------------|---------|--|
| 1. | Access to Building | | | - | |
| | 1) Road width | 06 mtr. | 15 mtr. | MR | |
| | 2) Gate width | Accessible | Accessible directly | MR | |
| | 3)Width of internal road | N/A | N/A | N/A | |
| 2. | Number, Width Type & Art | rangement of I | Exits | | |
| | A. Number of staircases | | | | |
| | 1. Upper floors | N/A | N/A | N/A | |
| | 2. Basements | N/A | N/A | N/A | |
| | B. Width of staircase | | | 1.00.00 | |
| | 1. Upper floors | N/A | N/A | N/A | |
| | 2. Basements | N/A | N/A | N/A | |
| | C. Protection of exits | | | 1 | |
| | 1. Fire check door | N/A | N/A | N/A | |
| | 2. Pressurization | N/A | N/A | N/A | |
| | D. No. of continuous | N/A | N/A | N/A | |
| | staircase to terrace | | 11/11 | I W A | |
| | E. Width of corridor | N/A | N/A | N/A | |
| | F. Door size | N/A | N/A | N/A | |
| 3. | Compartmentation | | 1011 | 11074 | |
| | 1) Fire check door | N/A | N/A | N/A | |
| | 2) Sealing of electrical shafts | N/A | N/A | N/A | |
| | 3) Fire rating of shaft door | N/A | N/A | N/A | |
| | 4) Water curtain | N/A | N/A | N/A | |
| | 5) Fire Dampers | N/A | N/A | N/A | |
| 4. | Smoke Management System | | | | |
| | 1) Basements | N/A | N/A | N/A | |
| | 2) Upper floors | N/A | N/A | N/A | |
| 5. | Fire Extinguishers | | | 1.07 | |
| | 1) Total numbers | 03 | 03 | MR | |
| | 2) Types | Required | Provided | MR | |
| | 3) ISI marking | Required | Provided | MR | |
| 6. | First-Aid Hose Reel | | | | |
| | 1) Total number of eachfloor | N/A | N/A | N/A | |
| | 2) Length of hose reel hose | N/A | N/A | N/A | |
| | 3) Nozzle diameter | N/A | N/A | N/A | |
| | | | | | |

1/10

| 7. | Automatic Fire Detection & A | Marming Sys | tem | |
|-----|---|-------------|-----------------|------------|
| 7. | 1) Type of detectors | N/A | N/A | N/A |
| | 2) Location of main panel | N/A | N/A | N/A |
| | | N/A | N/A | N/A |
| | 4) Alternate source of power | N/A | N/A | N/A |
| | 5) Hooter's Location | N/A | N/A | N/A |
| 0 | | N/A | N/A | N/A |
| 8. | MOEFA | | | N/A |
| 9. | Public Address System | N/A | N/A | IN/A |
| 10. | Automatic Sprinkler System | 27/4 | 27/4 | NI/A |
| | 1) Basement | N/A | N/A | N/A |
| | 2) Upper floors | N/A | N/A | N/A |
| | 3) Sprinkler above false | N/A | N/A | N/A |
| | ceiling | | | |
| 11. | Internal Hydrants | 27/ | | |
| | 1) Size of riser/down-comer | N/A | N/A | N/A |
| | 2) Number of hydrants per | N/A | N/A | N/A |
| | floor | | | |
| | 3) Hose box | N/A | N/A | N/A |
| 12. | Yard Hydrants | | | |
| | 1) Total number of hydrants | N/A | N/A | N/A |
| | 2) Hose box | N/A | N/A | N/A |
| 13. | Pumping Arrangement | | | |
| | 1) Ground level | N/A | N/A | N/A |
| | a) Discharge of main | N/A | N/A | N/A |
| | pump | | | |
| | b) Head of main pump | N/A | N/A | N/A |
| | c) Number of main pump | N/A | N/A | N/A |
| | d) Jockey pump out put | N/A | N/A | N/A |
| | e) Jockey pump head | N/A | N/A | N/A |
| | f) Stand by pump output | N/A | N/A | N/A |
| | g) Stand by pump head | N/A | N/A | N/A |
| | h) Auto starting/Manual | N/A | N/A | N/A |
| | stopping | 1 1/1 2 | | |
| | 2) Terrace level | | | |
| | a) Discharge of pump | N/A ' | N/A | N/A |
| | b) Head of pump | N/A | N/A | N/A |
| | c) Power supply | N/A | N/A | N/A |
| | d) Auto starting of pump | N/A | N/A | N/A |
| 14. | | | IN/A | I M A |
| 14. | Captive Water Storage for F 1) Under ground tank | N/A | N/A | N/A |
| | | IN/A | IN/A | IVA |
| | capacity | NI/A | N/A | N/A |
| | a) Draw-off connection | N/A | | N/A N/A |
| | b) Fire service inlet | N/A | N/A | N/A |
| | c) Access to tank | N/A | N/A | |
| | d) Over head tank | N/A | N/A | N/A |
| | capacity | D 1 | D '1 1 | NAID. |
| 15. | No Smoking Signage | Required | Provided | MR |
| 4.5 | English & Hindi | | English & Hindi | |
| 16. | Provision of Lifts. | | | |
| | a) Pressurization of lift | N/A | N/A | N/A |
| | shaft | | v | |
| | b) Pressurization of lift | N/A | N/A | N/A |
| | lobby | | | |
| | c) Communication in | N/A | N/A | N/A |

| | lift car | | | |
|-----|---|--------------|-----------------|------------|
| | d) Fireman's switch | N/A | N/A | NI/A |
| - | e) Lift signage | N/A | N/A | N/A |
| 17. | Stand by Power Supply | N/A | N/A | N/A |
| 18. | Refuge Area | N/A | N/A | N/A N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 0. | Special Fire Protection Syst Risk, if any: Provided Fire but | em for Prote | otion of and it | MR |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. No. No. Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFONDZ

m. crol

FTM

181x

P.T. Sitter

is but

polor org

Cho (NDZ)

Miscell West

mess!