## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001 Fax No. 011-23412593, Ph. 011-23412225

No. F.6/DFS/MS/School/2018/SZ/ 2 2 6 [

Dated: 8-11.0/18

## **FIRE SAFETY CERTIFICATE**

Certified that Cambridge Public School located at Ring Road, Sriniwas Puri, New Delhi-110065, comprised of ground plus two upper floors owned/occupied by Cambridge Public School was granted Fire Safety Certificate by this department vide letter No. F6/DFS/MS/School/2015/SZ/1619 Dated 08/09/2015. The premises was re-inspection by officer concerned by this department on 18/09/2015 in the presence of Mr. Rampal (Estate Manager) and observed that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class "Education Building" Group—B, with effect from the date of issue of this certificate for period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of conditions under rule 38 Delhi Fire Service Rules, 2010.

Issued Stopfe at New Delhi by

(Vipin Kental) Chief Fire Officer

Copy to: -

- 1. The Principal, Cambridge Public School, Ring Road, Sriniwas Puri, New Delhi-110065
- 2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054

## **Conditions for the validity of Fire Safety Certificate**

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

	INSPECTION REPORT					
1	Name & Address of the Building	The state of the s				
	l same same same same same same same same	Cambridge Public School, Ring Road, Srin		Sriniwas		
2	Type of Occupancy	Puri, New Delhi-110065 Educational, Group–B (School)				
3	Building Comprised of	G+02 upper floo	оир-в (School)			
-4	Type of Case	Renewal	1			
5	Details of Previous NOC		ool/2015/SZ/1619 Dated	00/00/2015		
6	Fire Safety Directives Letter No	Nil	001/2013/3Z/1019 Dated	08/09/2015		
7	Date of Inspection	18-09-2018				
8	Name of the Inspecting Officers	Mehmood, ADO (SJ)				
9	Name & Designation of Officers	Mr. Rampal (Estate Manager)				
	from the building side	(Estate Manager)				
10	Year of construction	1990				
11	Applicant letter No.	CS/7836/2018 dated 16.07.2018				
S. No.	Minimum standards on Fire Prevention	As Per Old	Provided at Site	Remarks		
	and Fire Safety U/R 33	NOC	1 Tovided at Site	MR/NMR		
1	Access to Building.			WHOTHIN		
	Road width	6 mtr	12m	MR		
	Gate width	4.5m	Provided	MR		
	Width of internal road	-NA-	-NA-	-NA-		
2	Number, width, type & arrangement of ex		1111	11/1-		
	a) Number of Staircase					
	Upper floors.	04 no's	04 no's	MR		
	Basement floor.	-NA-	-NA-	-NA-		
	b) Width of Staircase	A 14 A	1171	-11//-		
	> Upper floors	1.5 mtr	1.50m X 2 & 1.25m X2	. MR		
20	Basement floor	-NA-	-NA-	-NA-		
	e) Protection of exits	1471	-11/12-	-INA-		
	Fire check door	-NA-	-NA-	-NA-		
	Pressurization	-NA-	-NA-	-NA-		
	d) No. of continuous staircase to terrace	03 no's				
	e) Width of corridor	1.5m	Provided Provided	MR		
	f) Door size	1.5m	Provided	MR		
3	Compartmentation.	1111	Provided	MR		
	Fire check door.	-NA-	-NA-	NIA		
	<ul> <li>Sealing of electrical shafts.</li> </ul>	-NA-	-NA-	-NA-		
	<ul> <li>Fire rating of shaft door.</li> </ul>	-NA-	-NA-	-NA-		
	Water curtain	-NA-	-NA-	-NA-		
_	• Fire dampers.	-NA-	-NA-	-NA-		
4. •	Smoke Management system.	11/1-	-INA-	-NA-		
	Basement	30 ACPH	-NA-	NIA		
	Upper floors	12 ACPH	-NA-	-NA-		
5.	Fire Extinguishers.	12 ACI II	-INA-	-NA-		
	Total numbers	39 Nos	39 Nos	MD		
	• Types	ABC / CO2	ABC & Co2	MR		
	ISI Marking	ISI marked	Provided	MR		
6.	First Aid Hose Reels.	151 markeu	riovided	MR		
J.	Total numbers on each floor.	04 no's	Drovided 04 ?	MD		
	·		Provided 04 no's	MR		
-	Length of hose-reel hose.	30m	Provided	MR		
1	Nozzle Diameter	5mm	Provided			

7.	Automatic fire detection & alarming system.			-
	Type of detectors	-NA-	NIA	7.7.1
	<ul> <li>Location of Main Panel</li> </ul>	-NA-	-NA-	-NA-
	Location of Repeater Panel	-NA-	-NA-	-NA-
	Alternate source of power	-NA-	-NA-	-NA-
	Hooter's location		-NA-	-NA-
8.	MOEFA	-NA-		
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	Required	Provided	MR
100	Basement	NIA	N. I	ALC LANCE OF THE PARTY OF THE P
	Upper floors	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
11.	• Sprinkler above false ceiling  Internal Hydrants.	-NA-	-NA-	-NA-
11.				and the second
	Size of Riser/Down-comer	-NA-	-NA-	-NA-
	Number of Hydrant per floor	-NA-	-NA-	-NA-
10	Hose box.	-NA-	-NA-	-NA-
12.	Yard Hydrants.			
	<ul> <li>Total number of hydrants.</li> </ul>	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13.	Pumping arrangements.			
	Ground Level			
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
0	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.	-NA-	-NA-	-NA-
	Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting / Manual Stopping.	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
	Terrace Level		11/1	-INA-
	Discharge of pump.	450 LPM	450 LPM	MR
	➤ Head of pump.	40m	40 m	MR
	Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.	2.00 0.00	Trovided	IVIK
	Underground tank capacity.	-NA-	-NA-	-NA-
	Draw-off connection.	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
	<ul> <li>Overhead tank capacity.</li> </ul>	10,000 Ltr	Provided	MR
15.	Exit Signage.	Required	Provided	
16.	Provision of Lifts.	110401100	TTOVIUCU	MR
	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	Communication in lift car.	-NA-	-NA-	-NA-
	• Fireman's switch.	-NA-	-NA-	-NA-
	Lift signage.	-NA-	-NA-	
17.	Standby Power Supply	-NA-		-NA-
18.	Refuge Area	-11/17-	-NA-	-NA-
	Total area	-NA-	NIA	274
	• Location		-NA-	-NA-
	Location	-NA-	-NA-	-NA-

19.	Fire Control Room.			
	<ul> <li>Detector system panel.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Flow switch panel.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>PA system panel.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Battery backup.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Building floor plan.</li> </ul>	-NA-	-NA-	-NA-
20.	Special Fire Protection System for the	-NA-	ABC type fire extinguisher	-NA-
	Protection of special Risk, if any.		provided near electrical panel	

The Fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and safety measures as required under the rule, FSC issued vide letter No. F6/DF\$/MS/School/2015/SZ/1619 Dated 08/09/2015, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Mehmood

Design: ADO (SJ)

of SM miscell Film.

A 6.76 lenie burns for Signature Steam

Crocsep miscell 25/10.