GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 2271

Dated: -7-112-12

FIRE SAFETY CERTIFICATE

Certified that the Lord's Guest House located at 51, Main Bazar, Pahar Gnaj, New Delhi comprised of Ground (Reception + Hall), 1st floor to 4th floor (05 guest rooms at each floor), total 20 guest rooms owned/occupied by Lord's Guest House was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/NDZ/1495 dated 18/08/15. The premise was re-inspected by the officer concerned of this department on 25/09/18 in the presence of Mr. Ravinder Singh (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 for 20 guest rooms with effect from April 2 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

2. The Manager,

Lord's Guest House at 51, Main Bazar, Pahar Gnaj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

TATORY	-		
INCOL	CTIC	TIKE	EPORT
TTADL		IIN K	PPOPI

1. Name & address of the building Lord's Guest House at 51, Main Bazar,

Pahar Gnaj, New Delhi 2. Type of occupancy:-

Gr. + 04 Upper floors (total 20 Guest rooms) Ground (Reception + Hall), 1st floor to 4th floor

(05 guest rooms at each floor)

3. Type of case:-

4. Details of previous FSC:-

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Residential, Sub Division-A-1

Renewal

No. F6/DFS/MS/GH/2015/NDZ/1495 dated

18/08/15. N/A

25/09/18

Sh. Manoj Kumar Sharma (ADO/CC)

Mr. Ravinder Singh (Manager)

2002

Nil dated 12/09/2018

		Mil dated j	2/09/2018.		
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safet arrangements	Provided at site	Old Case Remarks MR/NMR	
1.	Access to Building	arrangements		WINTIVIK	
	1) Road width	N/A	06.14		
	2) Gate width	N/A	06 Mtr.	MR	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number Width Type & A.	IN/A	N/A	N/A	
	Number, Width Type & Ar A. Number of staircases	rangement of E	xits		
	1. Upper floors	01.31			
	2. Basements	01 Nos.	01 Nos.	MR	
	B. Width of staircase	N/A	N/A	N/A	
	1. Upper floors	0.00			
	2. Basements	0.80 mtr.	1.25 mtr.	MR	
	C. Protection of exits	N/A	N/A	N/A	
	1. Fire check door	N/A		1	
	2. Pressurization		N/A	N/A	
T I	D. No. of continuous staircase to terrace	N/A	N/A	N/A	
-		N/A	N/A	N/A	
-	E. Width of corridor	N/A	N/A	N/A	
,	F. Door size	1 mtr.	1 mtr.	MR	
	Compartmentation				
-	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
	Smoke Management System				
	1) Basements	30 ACPH	N/A	N/A	
	2) Upper floors	12 ACPH	Natural	MR	
	Fire Extinguishers				
	1) Total numbers	10 Nos.	10 Nos.	MR	
	2) Types	ABC & CO2	150	MR	
1 3	3) ISI marking	TO .		MR	

6.	First-Aid Hose Reel			
	1) Total number of eachfl	0.1		
	2) Length of hose reel has	oor 01 se 30 m	01	MR
-	3) Nozzle diameter	0.5	30 m	MR
7.	Automatic Fire Detection	n & Alami	05 mm	MR
	2) Location of main panel	NI/A	N/A	N/A
	3) Location of repeater par	IN/A	N/A	N/A
	4) Alternate source of now		N/A	N/A
	5) Hooter's Location		N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	N/A	N/A	N/A
10.	Automatic Sprinkler Syst	Require	ed Provided	MR
	1) Basement			IVIIC
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	N/A	N/A	N/A
11.	Internal Hydrants		_	IVA
	1) Size of riser/down-comer			
	2) Number of hard		N/A	N/A
	2) Number of hydrants per floor	N/A	N/A	N/A
	3) Hose box			IN/A
12.	Yard Hydrants	N/A	N/A	N/A
	1) Total number of	-		IN/A
	1) Total number of hydrants 2) Hose box	N/A	N/A	N/A
13.	Pumping A	N/A	N/A	N/A N/A
	Pumping Arrangement 1) Ground level			IN/A
	oreand icver	N/A	N/A	NI/A
	a) Discharge of main	N/A	N/A	N/A
	pump		11/11	N/A
	b) Head of main pump	N/A	N/A	NI/A
	c) Number of main pump	p N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
,	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
-	stopping		IVA	N/A
-	2) Terrace level			
-	a) Discharge of pump	225 LPM	225 LPM	
10	b) Head of pump	30 mtr.	30 mtr.	MR
-	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	D		MR
	Captive Water Storage for Fire Fight:		MR	
	1) Onder ground tank	N/A		
_	capacity	- 1/ 4 1	N/A	N/A
	a) Draw-off connection	N/A	NI/A	
	b) Fire service inlet	N/A	N/A	N/A
	(1) 1	N/A	N/A	N/A
		11/11	N/A	N/A

	d) Over head tank capacity	2,500 ltr.	2,500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
1	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	N/A		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/1495 dated 18/08/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Office

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFO(NDZ)

184/06 Mescell Film.

184/06 Mescell Film.

184/06 Mescell Film.

Sput up for sign

a Ro (1)22