GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001 Fax No. 011-23412593, Ph. 011-23412225

No. F6/DFS/MS/School/2018/SZ/ 23 c8

Dated: 1.7. 1.9. 18

FIRE SAFETY CERTIFICATE

Certified that the **Guru Nanak Public School** located at Gurudwara Building, Sadar Bazar Delhi Cantt, New Delhi-110010, building comprised of **Ground + 3 Upper floor** Owned/Occupied by Gurudwara Committee was inspected by officer concerned of this department on 07.06.2018 in the presence of Mr. Mukesh Kumar (Accountant) of the school and found that said school building have complied with the fire prevention and fire safety arrangements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class "**Educational Building, Group-B**" as above with effect from 17/15/2018 for a period of **Three years** subject to compliance of the condition mentioned below.

Issued on 1.7.1. of 1.8..... at New Delhi by

Vipin Kental Chief Fire Officer

Copy to: -

- 1. The Principal, Guru Nanak Public School, Gurudwara Building, Sadar Bazar, Delhi Cantt, New Delhi-110010.
- 2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety and means of escape facilities shall be maintained in good working condition at all time. Any lapse rendering the fire safety or means of evacuation facilities non-functional shall be the responsibility of the management.
- 2. Building Sanctioning authority may verify any deviation with regard to construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null & void.
- 3. The staff shall be trained for operating fire fighting system and mock evacuation drill be conducted at regular interval and record be maintained.
- 4. This Certificate cannot be treated as regularization of unauthorized construction, if any.
- 5. The Owner/Occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules, 2010. The form is available on www.dfs.delhigovt.nic.in.
- 6. The Owner/Occupier shall apply for renewal of this Fire Safety Certificate to the Director in the form 'J' [sub rule (1) of rule 37] along with copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in.

| 17 | | ON REPORT | 0.1.1.0.1 | D. '1 1' | | |
|--------|--|--|-------------------------------|---|--|--|
| 1 | Name & Address of the Building | Guru Nank Public School, Gurudwara Building, Sadar Bazar, Delhi Cantt, New Delhi-110010 | | | | |
| 2 | Type of Occupancy | | Educational, Group-B (School) | | | |
| 3 | Building Comprised of | Ground + 03 upper floors. | | | | |
| | Type of Case | New New | | | | |
| 5 | Details of Previous NOC | Nil | | | | |
| | Fire Safety Directives Letter No | Nil | | | | |
| 6 | | 02-07-2018 | | | | |
| 7 | Date of Inspection Name of the Inspecting Officers | Mehmood, ADO (SJ) | | | | |
| 8 | Name & Designation of Officers | Mrs. Ramanjit Kaur (Principal) | | | | |
| 9 | | 19113. Ramanjit Radi (1711101pai) | | | | |
| 10 | from the building side Year of construction | 1990 | | | | |
| 10 | | | 9/187 dated 15.06.2018 | | | |
| 11 | Applicant letter No. Minimum standards on Fire Prevention | BBL / NBC | Provided at Site | Remarks | | |
| S. No. | Control of the contro | requirements | 1 Tovided at Site | MR/NMR | | |
| - | and Fire Safety U/R 33 | requirements | | 111111111111111111111111111111111111111 | | |
| 1 | Access to Building. | 6 mtr | Provided | MR | | |
| | Road width | -NA- | -NA- | -NA- | | |
| | • Gate width | -NA- | -NA- | -NA- | | |
| | Width of internal road | | -11//- | -1471 | | |
| 2 | Number, width, type & arrangement of ex | (its. | | | | |
| | a) Number of Staircase | | Two | MR | | |
| | Upper floors. | One | | | | |
| | Basement floor. | -NA- | -NA- | -NA- | | |
| | b) Width of Staircase | * | | | | |
| | > Upper floors | 1.5 mtr | 1.30m & 0.90m | MR | | |
| | > Basement floor | -NA- | -NA- | -NA | | |
| | c) Protection of exits | | | | | |
| | > Fire check door | -NA- | -NA- | -NA- | | |
| | > Pressurization | -NA- | -NA- | -NA- | | |
| | | -NA- | -NA- | -NA- | | |
| | | 1.5m | Provided | MR | | |
| | | 1m | Provided | MR | | |
| 2 | f) Door size Compartmentation. | 1111 | | | | |
| 3 | | -NA- | -NA- | -NA- | | |
| | • Fire check door. | -NA- | -NA- | -NA- | | |
| | Sealing of electrical shafts. | -NA- | -NA- | -NA- | | |
| | • Fire rating of shaft door. | -NA- | -NA- | -NA- | | |
| | Water curtain | -NA- | -NA- | -NA- | | |
| | Fire dampers. | -INA- | -INA- | -142 k | | |
| 4. | Smoke Management system. | 20 A CDII | -NA- | -NA- | | |
| | Basement | 30 ACPH | -NA- | -NA- | | |
| | Upper floors | 12 ACPH | -NA- | -INA- | | |
| | Fire Extinguishers. | 1637 | 1/31 | MR | | |
| 5. | | 16 Noa | 16 Nos | MR | | |
| 5. | Total numbers | 16 Nos | ADC 0- C-2 | | | |
| 5. | | ABC / CO2 | ABC & Co2 | | | |
| 5. | Total numbers | | ABC & Co2 Provided | MR | | |
| 5. | Total numbers Types ISI Marking First Aid Hose Reels. | ABC / CO2 ISI marked | Provided | MR | | |
| | Total numbersTypesISI Marking | ABC / CO2 | Provided Provided | MR MR | | |
| | Total numbers Types ISI Marking First Aid Hose Reels. | ABC / CO2 ISI marked | Provided | MR | | |

| 7 A | automatic fire detection & alarming system. | | | |
|--------------|---|------------|----------------------|----------------------|
| / / | Type of detectors | -NA- | -NA- | -NA- |
| | Location of Main Panel | -NA- | -NA- | -NA- |
| 4 | Location of Repeater Panel | -NA- | -NA- | -NA- |
| | Alternate source of power | -NA- | -NA- | -NA- |
| | Hooter's location | -NA- | -NA- -NA- -NA- | -NA- -NA- -NA- |
| 0 1 | | -NA- | | |
| | MOEFA | -NA- | | |
| | Public Address System | -1471 | | |
| 10. A | Automatic Sprinkler System | -NA- | -NA- | -NA- |
| | Basement | -NA- | -NA- | -NA- |
| | • Upper floors | -NA- | -NA- | -NA- |
| | Sprinkler above false ceiling | -11/1- | 1172 | |
| 11. I | Internal Hydrants. | NIA | -NA- | -NA- |
| | Size of Riser/Down-comer | -NA- | | -NA- |
| | Number of Hydrant per floor | -NA- | -NA- | |
| | Hose box. | -NA- | -NA- | -NA- |
| 12. Y | Yard Hydrants. | | | 274 |
| | Total number of hydrants. | -NA- | -NA- | -NA- |
| | Hose box. | -NA- | -NA- | -NA- |
| 13. | Pumping arrangements. | | | |
| | Ground Level | | | |
| | Discharge of main pump. | -NA- | -NA- | -NA- |
| | > Head of main pump. | -NA- | -NA- | -NA- |
| | Number of main pumps. | -NA- | -NA- | -NA- |
| | > Jockey Pump output. | -NA- | -NA- | -NA- |
| | > Jockey Pump head. | -NA- | -NA- | -NA- |
| | Standby Pump output. | -NA- | -NA- | -NA- |
| 1 | Standby Pump head. | -NA- | -NA- | -NA- |
| | Auto Starting / Manual Stopping. | -NA- | -NA- | -NA- |
| | Pump house access. | -NA- | -NA- | -NA- |
| - | Terrace Level | | e e | |
| | > Discharge of pump. | 450 LPM | Provided | MR |
| | Head of pump. | 40m | Provided | MR |
| | > Power supply. | Required | Provided | MR |
| | Auto starting of pump. | Required | Provided | MR |
| 14. | Captive water storage for fire fighting. | | | |
| 17. | Underground tank capacity. | -NA- | -NA- | -NA- |
| | > Draw-off connection. | -NA- | -NA- | -NA- |
| | Fire Service Inlet. | -NA- | -NA- | -NA- |
| | Access to tank. | -NA- | -NA- | -NA- |
| | Overhead tank capacity. | 10,000 Ltr | Provided | MR |
| 15. | Exit Signage. | Required | Provided | MR |
| 16. | Provision of Lifts. | | | |
| 10. | Pressurization of lift shaft. | -NA- | -NA- | -NA- |
| | D Clift lables | -NA- | -NA- | -NA- |
| | C ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' | -NA- | -NA- | -NA |
| | | -NA- | -NA- | -NA |
| | • Fireman's switch. | -NA- | -NA- | -NA |
| | • Lift signage. | -NA- | -NA- | -NA |
| 17. | Standby Power Supply | -11/1- | 1111 | |
| 18. | Refuge Area | -NA- | -NA- | -NA |
| | Total area | | | -NA |
| | Location | -NA- | -NA- | -INA |

| 19. | Fire | ire Control Room. | | | | | |
|--|---|-------------------------------------|------|--------------------------------|------|--|--|
| | | • Detector system panel. | -NA- | -NA- | -NA- | | |
| | Flow switch panel. PA system panel. Battery backup. Building floor plan. | -NA- | -NA- | -NA- | | | |
| | | -NA- | -NA- | -NA- | | | |
| | | -NA- | -NA- | -NA- | | | |
| | | -NA- | -NA- | -NA- | | | |
| 20. | Spe | cial Fire Protection System for the | -NA- | ABC type fire extinguisher | -NA- | | |
| | Protection of special Risk, if any. | | | provided near electrical panel | | | |
| the state of the s | | | | | | | |

The Fire protection systems provided in the building were tested, checked at random and found functional at the time of inspection. The shortcomings communicated vide letter 04/11/2015,17/05/2018 have been complied

Keeping in view the substantial satisfactory compliance of the minimum standards on fire prevention and fire safety measures as required the rules, it is recommended to issue Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules, 2010

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Office

Name: Mehmood Design: ADO (SJ)

Speak on the YOC paper on file of print nls. gof Traspection note of DBE in DFA.

The order dorning to placed on 10 and the AFA amonded as doriented grown for your approval blease Jamost

Do lesson