GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 2323

Dated : 1-5-1-0-18

FIRE SAFETY CERTIFICATE

Issued 15 10 18 at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager.
 - "Relax International" Guest House at 8225/6, Arakashan Road, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

		NSPECTION I	REPORT				
	1. Name & address of the built	lding "Relay	International"				
			International" Gues	t House at 8225/			
	2. Type of occupancy:-	Reside	shan Road, Pahar Ga ential, Sub Division	anj, New Delhi.			
		Gr. + 04	Upper floors (total 18	-A-1			
		Oround	HOUL LUZ BIJEST roome	1 of All ath a			
		(or gues	1 100111S at each floor) as	nd tomes - a			
	3. Type of case:-	(04 guest rooms at each floor) and terrace floor (02 guest rooms is sealed with brick wall)					
	A Dotoile of						
	5 21 5 NIS OI 1/20 1.3 NI 1/2 NI						
	5 Fire safety dimentia N						
	1) late of increati						
	7. Name of the inspecting officer:- 8. Name & designation of officer Sh. Manoj Kumar Sharma (ADO/CC)						
	From the building of						
	9. Year of construction:-	9. Year of construction: Mr. Pankaj (Manager)					
	10. Applicant's letter No:-	NIII 1	1.40				
	11 110,-	Nil dated	1 13/09/18.				
S.N	No. Minimum Standards on fire	Doguin	,	Old Case			
	Prevention and fire safety	Requirement/ Existing fire	Provided at sit	te Remarks			
	U/R 33	safety		MR/NMR			
1.		arrangements					
	Access to Building 1) Road width						
	2) Gate width	N/A	N/A	N/A			
		N/A	N/A	N/A			
2.	3) Width of internal road	N/A	N/A	N/A			
4.	Number, Width Type & An	rrangement of	Exits	IN/A			
	11. Ivalidel of Staircases						
	1. Upper floors	01 Nos.	01 Nos.	MD			
	2. Basements	N/A	N/A	MR			
	B. Width of staircase		14/74	N/A			
	1. Upper floors	0.80 mtr.	1.15 mtr.	1.65			
	2. Basements	N/A	N/A	MR			
	C. Protection of exits		IN/A	N/A			
	1. Fire check door	N/A	N/A				
	2. Pressurization	N/A		N/A			
	D. No. of continuous	01	N/A	N/A			
	staircase to terrace		01	MR			
	E. Width of corridor	N/A	NI/A				
	F. Door size	01 mtr.	N/A	N/A			
8.	Compartmentation	Joi mu.	01 mtr.	M/R			
	1) Fire check door	N/A	27/4				
	2) Sealing of electrical shafts	N/A N/A	N/A	N/A			
	3) Fire rating of shaft door	N/A N/A	N/A	N/A			
	4) Water curtain		N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
	Smoke Management System	N/A	N/A	N/A			
	1) Basements	20 A CDYY					
	2) Upper floors	30 ACPH 12 ACPH	N/A Natural	N/A			

			\				
5.	Fire Extinguishers						
	1) Total numbers	12 Nos.	12 Nos.	MR			
	2) Types	ABC & CO2	ABC & CO2	MR			
	3) ISI marking	Required	Provided	MR			
6.	First-Aid Hose Reel						
	1) Total number of eachfloor	01	01	MŘ			
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR			
	3) Nozzle diameter	05 mm	05 mm	MR			
7.	Automatic Fire Detection & Alarming System						
	1) Type of detectors	N/A	N/A	N/A			
	2) Location of main panel	N/A	N/A	N/A			
	3) Location of repeater panel	N/A	N/A	N/A			
	4) Alternate source of power	N/A	N/A	N/A			
	5) Hooter's Location	N/A	N/A	N/A			
8.	MOEFA	N/A	N/A	N/A			
9.	Public Address System	Required	Provided	MR			
10.	Automatic Sprinkler System						
	1) Basement	N/A	N/A	N/A			
	2) Upper floors	N/A	N/A	N/A			
	3) Sprinkler above false	N/A	N/A	N/A			
	ceiling						
11.	Internal Hydrants	1		27/4			
	1) Size of riser/down-comer	N/A	N/A	N/A			
	2) Number of hydrants per	N/A	N/A	N/A			
	floor			I NI/A			
	3) Hose box	N/A	N/A	N/A			
12.	Yard Hydrants	27/4	DI/A	NI/A			
	1) Total number of hydrants	N/A	N/A	N/A			
	2) Hose box	N/A	N/A	N/A			
13.	Pumping Arrangement	21/1	27/4	DI/A			
	1) Ground level	N/A	N/A	N/A			
	a) Discharge of main	N/A	N/A	N/A			
	pump	DT/A	NI/A	N/A			
	b) Head of main pump	N/A	N/A	N/A N/A			
	c) Number of main pur		N/A	N/A N/A			
	d) Jockey pump out pu		N/A	N/A N/A			
	e) Jockey pump head	N/A	N/A	N/A N/A			
	f) Stand by pump outp		N/A N/A	N/A N/A			
	g) Stand by pump head		N/A N/A	N/A			
	h) Auto starting/Manua	al N/A	IN/A	IN/A			
	stopping						
	2) Terrace level	225 LPM	225 LPM	MR			
	a) Discharge of pump		30 mtr.	MR			
	b) Head of pump	30 mtr.		MR			
	c) Power supplyd) Auto starting of pun	Required Required		MR			
	d) Auto starting of pun	ID Vedalled	TTOVIUCU	TATI			

4	Captive Water Storage for F	ire Fighting		21/4
4.	1) Under ground tank capacity	N/A	N/A	N/A
	CC cation	N/A	N/A	N/A
	1 .	N/A	N/A	N/A
	t- touls	N/A	N/A	N/A
	d) Over head tank	2500 ltr.	2500 ltr.	MR
2000	capacity	Required	Provided	MR
15.	Exit Signage.	Require		
16.	Provision of Lifts. a) Pressurization of lift	N/A	N/A	N/A
	shaft b) Pressurization of lift	N/A	N/A	N/A
	c) Communication in	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	N/A	N/A	N/A
18.	Refuge Area Total area location	N/A	N/A	N/A
10	Fire Control Room	N/A	N/A	N/A
19.	a) Detector system	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	D) Flow Switch panel	N/A	N/A	N/A
	c) PA system panel d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Sy Risk, if any: ABC & CO ²	stem for Prot	ection of special	MR

The fire protection systems provided in the building were randomly tested,

checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/1821 dated 09/10/2015 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFONDZ

SZ

X. CFA- M.SCOU W. 10[X,