## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 2329

Dated :- 45/10/18-

## **FIRE SAFETY CERTIFICATE**

Certified that the Sonu Guest House located at 4563, Main Bazar, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (Reception + 03 guest house), 1<sup>st</sup> floor to 3<sup>rd</sup> floor (03 guest rooms at each floor), total 12 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/NDZ/1752 dated 18/09/15. The premises was re-inspected by the officer concerned of this department on 04/10/18 in the presence of Mr. Virender (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 12 guest rooms only with effect from -1-5/1-2--for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

## Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter no. 4306/Addl. C.P./ Lic.(H) dated 15/09/18.
- 2. The Manager, Sonu Guest House at 4563, Main Bazar, Pahar Ganj, New Delhi.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INC	PECTION REPO	)DT			
1	Name & address of the building			(.t. D		
	Traine & address of the building		st House at 4563, M	iain Bazar,		
2	Type of occupancy:-	Pasidentia	j, New Delhi			
	Type of occupancy:-  Residential, Sub Division-A-1  Gr. + 03 Upper floors (total 12 Guest rooms)					
		Ground floor	(Reception + 03 guest	house). 1 <sup>st</sup> floor		
		to 3 <sup>rd</sup> floor (	03 guest rooms at each	floor)		
1	Type of case:-	Renewal				
4.	Details of previous FSC:-	No. F6/DF	S/MS/GH/2014/ND	Z/1752 dated		
_	T1 0 11 1	18/09/15.				
1	Fire safety directives No	N/A				
	Date of inspection:-	04/10/18				
	Name of the inspecting officer		Kumar Sharma (A)	DO/CC)		
	Name & designation of officer					
	he building side:-		der (Manager)			
	Year of construction:-	1989	~			
10.	Applicant's letter No:-	4306/Addł.	C.P./ Lic.(H) dated			
S.No.	Minimum Standards on fire	Requirement/	Provided at site	Old Case Remarks		
	Prevention and fire safety	Existing fire	1 Tovided at site	MR/NMR		
	U/R 33	safety		IVIK/INIVIK		
1.		arrangements				
1.	Access to Building					
	1) Road width	N/A	06 mtr.	N/A		
	2) Gate width	N/A	N/A	N/A		
	3) Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arr	angement of E	xits			
	A. Number of staircases		x *			
	1. Upper floors	01 Nos.	01 Nos.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase			0		
	1. Upper floors	0.80 mtr.	0.80 mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits		5. 8. 8 a	0		
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	N/A	N/A	N/A		
	staircase to terrace					
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	01 mtr.	01 mtr.	01 mtr.		
3.	Compartmentation	-				
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	30 ACPH	N/A	N/A		
	2) Upper floors	12 ACPH	Natural	MR		

Mu

5.	Fire Extinguishers		· · · · · · · · · · · · · · · · · · ·	T		+		
	1) Total numbers	T 0	8 Nos.	08	8 Nos.	+	MR	
	2) Types		BC & CO2	-	BC & CO2		MR	
	3) ISI marking	-	equired	-	rovided	-	MR	
6.	First-Aid Hose Reel			1				
	1) Total number of eachfloor	01	1	0	1		MR	
	2) Length of hose reel hose	30	mtr.	30	30 mtr.		MR	
	3) Nozzle diameter	-	05 mm		05 mm		MR	
7.	Automatic Fire Detection &	Ala	rming Syste	em	-	+		
			/A		/A		N/A	
	2) Location of main panel	N	/A	N	N/A		N/A	
	3) Location of repeater panel	N	/A	N.	/A	]	N/A	
	4) Alternate source of power	N,	/A	N	/A		N/A	
	5) Hooter's Location	N/A		N/A			N/A	
8.	MOEFA	N	/A	N	/A	1	N/A	
9.	Public Address System		/A		/A		N/A	
10.	Automatic Sprinkler System		· · · · · · · · · · · · · · · · · · ·	1				
	1) Basement	N	/A	N	/A		N/A	
	2) Upper floors	N	/A	_	/A	-	N/A	
	3) Sprinkler above false	N	/A	N/A		-	N/A	
	ceiling							
11.	Internal Hydrants							
	1) Size of riser/down-comer	N/A		N/A		1	N/A	
	2) Number of hydrants per	N/	N/A		N/A		N/A	
	floor		2					
	3) Hose box	N/	N/A		N/A		N/A	
12.	Yard Hydrants						0	
	1) Total number of hydrants	N/		N/	'A	1	N/A	
	2) Hose box	N/	'A	N/	'A	1	V/A	
13.	Pumping Arrangement		2	, ,	- A			
	1) Ground level		N/A		N/A		N/A	
	a) Discharge of main		N/A		N/A		N/A	
	pump				-2.		:	
	b) Head of main pump		N/A		N/A	1	N/A	
	c) Number of main pun	np	N/A		N/A		N/A	
	d) Jockey pump out put		N/A		N/A	-	N/A	
	e) Jockey pump head		N/A N/A		Charles on the Control	N/A		
	f) Stand by pump outpu		N/A		N/A		N/A	
	g) Stand by pump head		N/A		N/A		N/A	
	h) Auto starting/Manua	1	N/A		N/A	The state of the s	N/A	
	stopping					Constitution of		
	2) Terrace level							
	a) Discharge of pump				180 LPM		MR	
	b) Head of pump		30 mtr. 30 mtr.		Control of the Control	MR		
	b) Head of pump		0 0 111111	Provided				
	c) Power supply		Required				MR	
		p					MR MR	

m

14.	Captive Water Storage for	Fire Fighting		
	1) Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
1.	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			TVIIC
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
1=	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any: ABC & CO <sup>2</sup>	m for Protect	ion of special	MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/1752 dated 18/09/2015 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFONDZ A De 789/06 NPZ CFED MSCEU FT/M.

11/X. 12/X.

11/X. 12/X.

16/X.