## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 2457

Dated: 38 (olia

## FIRE SAFETY CERTIFICATE

Certified that the Mourya Dx. Guest House located at 9919-9923, Gali No.6, Multani Dhanda, Sadar Thana Road, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (02 guest room + reception + shops), 1<sup>st</sup> floor to 3<sup>rd</sup> floor (08 guest rooms at each floor) and 4<sup>th</sup> floor (02 guest rooms + 01 staff room + kitchen for staff + D.G. set) total 28 guest rooms owned/occupied by Mourya Dx. Guest House was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/NDZ/1488 dated 17/08/15. The premises was re-inspected by the officer concerned of this department on 20/10/18 in the presence of Sh. Jitender (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 28 guest rooms only with effect from sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued \_3//10/18 at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

2. The Manager,

Mourya Dx. Guest House, 9919-9923, Gali No.6, Multani Dhanda, Sadar Thana Road, Pahar Ganj, New Delhi

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

**INSPECTION REPORT** 

1. Name & address of the building:-

Mourya Dx. Guest House located at 9919-9923, Gali No.6, Multani Dhanda, Sadar Thana Road, Pahar Ganj, New Delhi

Residential, Sub Division-A-1

2. Type of occupancy:-

Gr. + 04 Upper floors (total 28 Guest rooms) Ground floor (02 guest room + reception + shops), 1st floor to 3rd floor (08 guest rooms at each floor) and 4th floor (02 guest rooms + 01 staff room + kitchen for

staff + D.G. set).

3. Type of case:-

4. Details of previous FSC:-

Renewal No. F6/DFS/MS/GH/2015/NDZ/1488 dated

17/08/15.

5. Fire safety directives No.-

6. Date of inspection:-

N/A 20/10/18

7. Name of the inspecting officer:-

Sh. Manoj Kumar Sharma (ADO/CC)

8. Name & designation of officer

From the building side:-

9. Year of construction:-10. Applicant's letter No:-

Sh. Jitender (Manager)

Nil dated 05/10/2018.

10.	Applicant 3 letter 110.			Old Case
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building			
	1) Road width	N/A	02 mtr.	MR
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arra	angement of E	exits	
	A. Number of staircases			
	1. Upper floors	01 Nos.	01 Nos.	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase			
	1. Upper floors	0.80 mtr.	1.25 mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits		•	
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous	01	01	MR
	staircase to terrace			
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	1 mtr.	1 mtr.	MR
3.	Compartmentation			
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A

4.	Smoke Management System			
	1) Basements	30 ACPH	N/A	I NI/A
	2) Upper floors	12 a/c per	Natural	N/A
		hour	Ivaturar	MR
5.	Fire Extinguishers			
	1) Total numbers	12 Nos.	12 Nos.	MD
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided Provided	MR
6.	First-Aid Hose Reel	required	TTOVICE	MR
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	
7.	Automatic Fire Detection &	Alarming Syst	om (1)	MR
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	-
	3) Location of repeater panel	N/A	N/A	N/A N/A
	4) Alternate source of power	N/A	N/A	N/A N/A
	5) Hooter's Location	N/A	N/A	N/A N/A
8.	MOEFA	Required	Provided	
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	Required	Provided	MR
	1) Basement	N/A	N/A	21/4
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	14/71	IN/A	N/A
11.	Internal Hydrants	L		
	1) Size of riser/down-comer	N/A	N/A	'NI/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor	1 1/1 1	IVA	N/A
	3) Hose box	N/A	N/A	NI/A
12.	Yard Hydrants	N/A		
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A N/A
3.	Pumping Arrangement		11/11	INA
	1) Ground level	N/A	N/A	NI/A
	a) Discharge of main	N/A	N/A	N/A
	pump	17/11	1 1//1	N/A
	b) Head of main pump	N/A	N/A	NI/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping	1 1/1 1	1 4/ 74	N/A
	2) Terrace level			
	a) Discharge of pump	225 LPM	225 LP	MAD
	b) Head of pump	30 mtr.	30 mtr.	MR
	, panip	JO IIII.	ou mu.	MR

	c) Power supply	Required	Provided	MR		
4.4	d) Auto starting of pump		Provided	MR		
14.	Captive Water Storage for Fire Fighting					
	1) Under ground tank	N/A	N/A	N/A		
	capacity					
	a) Draw-off connection	N/A	N/A	N/A		
	b) Fire service inlet	N/A	N/A	N/A		
	c) Access to tank	N/A	N/A	N/A		
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.	Tregation	Tiovided	IVIK		
	a) Pressurization of lift shaft	N/A	N/A	N/A		
	b) Pressurization of lift lobby	N/A	N/A	N/A		
	c) Communication in lift car	Required	Provided	MR		
	d) Fireman's switch	Required	Provided	MR		
	e) Lift signage	Required	Provided	MR		
17.	Stand by Power Supply	Required	Provided	MR		
18.	Refuge Area	N/A	N/A	N/A		
	Total area location	N/A	N/A	N/A		
19.	Fire Control Room	N/A	N/A	N/A		
	a) Detector system panel	N/A	N/A	·N/A		
	b) Flow switch panel	N/A	N/A	N/A		
	c) PA system panel	N/A	N/A	N/A		
	d) Battery backup	N/A	N/A	N/A		
	e) Building floor plan	N/A	N/A	N/A		
20.	Special Fire Protection System Risk, if any:	m for Protecti	on of special	NA		

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/NDZ/2015/1488 dated 17/08/2015 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFO/NDZ

F.J. letter is por