FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [SEE SUB-RULE (1) OF RULE 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6 Off and Low EH was 2475

Dated: 2 / // /2018

FIRE SAFETY CERTIFICATE

Certified that the Tippling Street (A Unit of D.K. Plaza) located at A-12 Vishal Enclave Rajouri Garden, New Delhi. Now running on 1st & 2nd Floor only in a building comprising Basement, Ground, 1st Floor & 2nd Floor & 3rd Floor only owned / occupied by D.K. Plaza Restaurant has already been issued Fire Safety Certificate Vide Letter No. F6/DFS/MS/EH/2015/WZ/1479 dated 14/08/2015 (for Ground & 2 Upper Floors only). The premises / building was re-inspected by the officer concerned of this department on 17/10/2018 in the presence of Mr. Kawal Jeet Singh (Partner) and found that the building / premises have deemed complied with the Fire prevention and Fire Safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building / premises is fit for the occupancy period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 2 11. 18..... at New Delhi by.

CHIEF FIRE OFFICER.

Copy to:

- 1. Kewaljeet Singh (Partner), Tippling Street (A Unit of D.K. Plaza), A-12 Vishal Enclave Rajouri Garden, New Delhi
- 2. Dy. Health Officer, SDMC, Vishal Enclave, Rajouri Garden, New Delhi-110027.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Fire Safety Certificate is valid for 1st & 2nd Floor only.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 8. Basement shall be used strictly as per BBL.

12.	Yard Hydrants.						
	Total number of	N/A		N/A	N/A		
	hydrants	N/A		N/A	N/A		
	Hose Box						
13.	Pumping Arrangements.		1				
	Ground Level						
	Discharge of main pump	NR	NR		NR		
	Head of Main pump	NR	NR		NR		
	Number of main pumps	NR NR		-	NR		
	Jockey Pump out put	NR	NR NR NR		NR NR NR		
	Jockey pump head	NR					
	Standby pump out put	NR					
	Standby pump Head	NR					
	Auto Starting/Manual	NR	NR		NR		
	stopping Pump Hose Access	NR	NR		NR		
	Terrace level	IVIN	INK .		IVIN		
	Discharge of pump	450 LPM	450	LPM x 2	M.R		
	> Head of the pump	40 MH		MH	M.R		
	Power supply	Required	Pro	vided	M.R		
	1 ower suppry	required		ovided	M.R		
	Auto Starting of numn	required		11000			
	Auto Starting of pump	required					
14.	Auto Starting of pump Captive Water Storage for fire fi						
14.	Captive Water Storage for fire fi	ghting.		11			
14.	Captive Water Storage for fire fi Underground tank capacity	ghting.	N	R	NR		
14.	Captive Water Storage for fire fi Underground tank capacity > Draw -off connection	ghting. NR NR	N	3	NR NR		
14.	Captive Water Storage for fire fi Underground tank capacity	ghting. NR NR Required	NI NI Pi	R Povided	NR NR MR		
14.	Captive Water Storage for fire fi Underground tank capacity > Draw -off connection	ghting. NR NR Required Required	NI NI P1	R R Povided	NR NR		
	Captive Water Storage for fire fi Underground tank capacity > Draw -off connection > Fire service inlet > Access to tank > Overhead Tank Capacity	ghting. NR NR Required Required 10,000 ltr	NI NI PI PI 10	R Povided Povided	NR NR MR MR		
14.	Captive Water Storage for fire fi Underground tank capacity > Draw -off connection > Fire service inlet > Access to tank	ghting. NR NR Required Required	NI NI PI PI 10	R R Povided	NR NR MR		
	Captive Water Storage for fire fi Underground tank capacity > Draw -off connection > Fire service inlet > Access to tank > Overhead Tank Capacity	ghting. NR NR Required Required 10,000 ltr	NI NI PI PI 10	R Povided Povided	NR NR MR MR		
15	Captive Water Storage for fire fi Underground tank capacity > Draw -off connection > Fire service inlet > Access to tank > Overhead Tank Capacity Exit Signage.	ghting. NR NR Required Required 10,000 ltr	NI NI Pi Pi	R Povided Povided	NR NR MR MR		
15	Captive Water Storage for fire fi Underground tank capacity > Draw -off connection > Fire service inlet > Access to tank > Overhead Tank Capacity Exit Signage. Provision of Lifts	Required Required 10,000 ltr Required	NI NI PI 10 PI	R Povided Povided 1,000 ltr Ovided	NR NR MR MR MR MR MR.		
15	Captive Water Storage for fire fi Underground tank capacity > Draw -off connection > Fire service inlet > Access to tank > Overhead Tank Capacity Exit Signage. Provision of Lifts • Pressurization of Lift Shaft	ghting. NR NR Required 10,000 ltr Required N/A	NI NI P1 P1 10 P1 N N	R Provided Provided Provided Provided Provided Provided Provided	NR NR MR MR MR MR N/A		
15	Captive Water Storage for fire fi Underground tank capacity > Draw -off connection > Fire service inlet > Access to tank > Overhead Tank Capacity Exit Signage. Provision of Lifts • Pressurization of Lift Shaft • Pressurization of Lift lobby • Communication In lift Car • Fireman's Grounding	Required 10,000 ltr Required N/A N/A	NI NI PI 10 PI N N N	R R rovided rovided 0,000 ltr rovided //A	NR NR MR MR MR MR N/A N/A		
15	Captive Water Storage for fire fi Underground tank capacity Draw -off connection Fire service inlet Access to tank Overhead Tank Capacity Exit Signage. Provision of Lifts Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch	Required Required 10,000 ltr Required N/A N/A N/A N/A	NI NI PI 10 PI N N N N	rovided rovided rovided rovided /A /A /A	NR NR MR MR MR MR N/A N/A N/A N/A		
15	Captive Water Storage for fire fi Underground tank capacity > Draw -off connection > Fire service inlet > Access to tank > Overhead Tank Capacity Exit Signage. Provision of Lifts • Pressurization of Lift Shaft • Pressurization of Lift lobby • Communication In lift Car • Fireman's Grounding	Required 10,000 ltr Required N/A N/A N/A	NI NI PI 10 PI N N N N	rovided rovided 0,000 ltr rovided //A	NR NR MR MR MR MR N/A N/A N/A		
15	Captive Water Storage for fire fi Underground tank capacity Draw -off connection Fire service inlet Access to tank Overhead Tank Capacity Exit Signage. Provision of Lifts Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch	Required Required 10,000 ltr Required N/A N/A N/A N/A	NI NI PI 10 PI N N N N	rovided rovided rovided rovided /A /A /A	NR NR MR MR MR MR N/A N/A N/A N/A		
15	Captive Water Storage for fire fi Underground tank capacity Draw -off connection Fire service inlet Access to tank Overhead Tank Capacity Exit Signage. Provision of Lifts Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch	Required Required 10,000 ltr Required N/A N/A N/A N/A	NI NI PI 10 PI N N N N	rovided rovided rovided rovided /A /A /A	NR NR MR MR MR MR N/A N/A N/A N/A		
15	Captive Water Storage for fire fi Underground tank capacity Draw -off connection Fire service inlet Access to tank Overhead Tank Capacity Exit Signage. Provision of Lifts Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch	Required Required 10,000 ltr Required N/A N/A N/A N/A	NI NI PI 10 PI N N N N	rovided rovided rovided rovided /A /A /A	NR NR MR MR MR MR N/A N/A N/A N/A		
15	Captive Water Storage for fire fi Underground tank capacity Draw -off connection Fire service inlet Access to tank Overhead Tank Capacity Exit Signage. Provision of Lifts Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch	Required Required 10,000 ltr Required N/A N/A N/A N/A	NI NI PI 10 PI N N N N	rovided rovided rovided rovided /A /A /A	NR NR MR MR MR MR N/A N/A N/A N/A		

1 77	C. II			113
17.	Standby power supply	Required	Provided	M.R
18.	Refuge Area			
	> Total Area	N/A	N/A	N/A
	Location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	Detector System Panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	PA system Panel	N/A	N/A	N/A
	> Battery backup	N/A	N/A	N/A
	➤ Building Floor plans	N/A	N/A	N/A
20.	Special Fire Protection Systems for Protection of special Risks, if any:	N.R.	Ŋ.R.	N.R.

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. No. F6/DFS/MS/EH/2015/WZ/1479 dated 14/08/2015 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

D. O(copst)

Signature of the Inspecting Officer

Name : Ashok Kumar Jaiswal Designation : A.D.O. (Jwala Puri)

Dytho (1/2)

29/10/18

Spoken with

put 4,

4

INSPECTION REPORT

1. Name &address of the building : Tippling Street (A Unit of D.K. Plaza), A-12,

Vishal Enclave, Rajouri Garden, New Delhi-110027.

2. Type of Occupancy : Assembly / Restaurant (Eating House)

3. Type of Case : Renewal (Now Restaurant at 1st & 2nd Floor only in a building

comprising Basement, Ground & Three Upper Floors)

4. Details of previous NOC : F6/DFS/MS/EH/2015/WZ/1479 dated 14/08/2015

(Issued for Ground Floor, 1st Floor & 2nd Floor only)

5. Fire Safety directives letter No. : NBC (Part-IV)

6. Date of inspection : 17.10.2018

7. Name of the Inspecting Officers : A. K. Jaiswal (ADO JWP)

8. Name and designation of officers

From the building side : Sh. Kawal Jeet Singh

9. Year of Construction : 2004

10. Applicant's letter No. : Nil dated 11/09/2018

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	NBC- Requir		Provided at site	Remarks MR/NMR		
1.	Access to building						
	Road width	09mtr		On Main Road	M.R.		
	Gate width	On main ro	ad	On Main Road	MR		
	Width of internal road	N/A		N/A	N/A.		
2.	Number, Width, Type & Arrangement of Exits						
	a. Number of staircases						
	Upper Floor	2	2		MR		
	Basement	N/A	N/A		N/A		
	b. Width of staircases			n 10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
	 Upper Floors 	Old Case	0.85 mt	r x 2	MR (Old Case)		
	Basement	N/A	N/A	0	N/A		
	c. Protection of exits				*		
	Fire check doorPressurization	N/A	N/A		N/A		
		N/A	N/A		N/A		
	d. No. of continuous staircases to terrace	1	1	_	MR		
	e. Width of Corridor	N/A	N/A		N/A		
	f. Door size	2.00m x 1 1.00m x 1	2.00m ×		MR		



	. Compartmentation						
				5			
	 Fire check door 		N/A		V/A	NI/A	
	 Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 4. Smoke Management System.				V/A	N/A N/A	
6					N/A	N/A	
			N/A	N/A N/A		N/A	
4					7/0	N/A	
	The Management System	•	*				
	Basements		N/A		/A	N/A	
	Upper floors		Required				
_			Required		ovided	MR	
5.	Fire Extinguishers						
	Total numbers		6	7			
	• Types					M.R.	
			ABC & CO ₂ type	Provided		M.R.	
	IS marking		SI marks required	provided		M.R.	
6.	First-Aid Hose Reel.						
	 Total numbers on each floor Length of hose reel hose 30 mtr. 			1		MR	
			0 mtr.	30 mtr.		MR	
-	Nozzle diameter	5 mm		5 mm		MR	
7.	Automatic fire detection and a		IVIIC				
	Location of Main Panel		N/A			N/A	
			N/A			N/A	
			N/A			N/A	
	 Location of Repeater Panel 			N/A		N/A	
			N/A			N/A	
	 Alternate source of power 	N/A					
	 Hooter's Location 	IN/.	A	N/A		N/A	
8.	MOEFA					1	
	MOEFA		Required		ided	M.R.	
9.	Public Address System.	N/A		N/A			
10.			1.071			N/A	
10.	Automatic Sprinkler system						
	• Basement	N/A		D. /-			
	• Upper Floor	N/A		N/A Provided		N/A	
	Sprinkler above false				aed	N/A	
1.1	ceiling	~ W 4 A		N/A		N/A	
11.	Internal Hydrants						
	comer				ded	MD	
1.					ueu	MR	
	Number of hydrants per floorHose Box		1			MR	
	- HOSC BOX	1		1		MD	
						MR	

