GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 2517

Dated:----

FIRE SAFETY CERTIFICATE

Issued ---- $\frac{12}{11}\frac{13}{13}$ -- at New Delhi by.

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service

of m

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

2. The Manager,

Bhartia Guest House at 3439, Dariba Pan, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INSI	PECTION REP	ORT				
1.	Name & address of the building Bhartia Guest House located at 3439,						
	Dariba Pan, Pahar Ganj, New Delhi						
2.	Type of occupancy:-		al, Sub Division-A-				
	Gr. +4 Upper floors (24 Guest rooms) Ground floor (04 guest rooms + reception), 1 st floor to 4 th floor (05 guest rooms at each floor)						
2							
	Type of case:-	Renewal					
4.	 4. Details of previous FSC:- No. F6/DFS/MS/EH/2015/NDZ/1905 dated 23/10/15. 5. Fire safety directives No Date of inspection:- Name of the inspecting officer:- Sh. M.K. Sharma (ADO/CC) 						
_							
8.	Name & designation of officer						
	From the building side:-	Sh. Naresh	Kumar (Manager)				
	Year of construction:-	2001					
10	. Applicant's letter No:-	Nil dated 12/	10/18				
				Old Case			
S.No.	Minimum Standards on fire	Requirement	Provided at site	Remarks			
	Prevention and fire safety	Existing fire safety		MR/NMR			
	U/R 33	arrangements		-			
1.	Access to Building						
	1) Road width	N/A	1.5 mtr. gate	MR			
		-	near main road				
	2) Gate width	N/A	N/A	N/A			
	3) Width of internal road	N/A	N/A	N/A			
2.	Number, Width Type & Arr	angement of E	xits				
	A. Number of staircases						
	1. Upper floors	01 Nos.	01 Nos.	MR			
	2. Basements	N/A	N/A	·N/A			
	B. Width of staircase						
	1. Upper floors	1.5 mtr.	1.46 to 1.5 mtr.	MR			
		30 2000					
	2. Basements	N/A	N/A	N/A			
	C. Protection of exits						
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous	01	01	MR			
	staircase to terrace		90° 100'				
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size	1 mtr.	1 mtr.	MR			
3.	Compartmentation						
	1) Fire check door	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
١.	Smoke Management System	1 1/2 1	1 1// 1	13/73			
	1) Basements	30 ACPH	N/A	N/A			
	1 / Dascincias						
	2) Upper floors	12 a/c per	Natural	MR			

Fire Extinguishers 1) Total numbers 2) Types	10 Nos.	10 Nos.	MR			
2) Types	1000000					
	ABC & CO2	ABC & CO2	MR			
3) ISI marking	Required	Provided	MR			
First-Aid Hose Reel						
1) Total number of eachfloor	01	01	MR			
	30 m	30 m	MR			
3) Nozzle diameter	5 mm	5 mm	MR			
Automatic Fire Detection & Alarming System						
	N/A	N/A	N/A			
	N/A	N/A	N/A			
	N/A	N/A	N/A			
	N/A	N/A	N/A			
	N/A	N/A	N/A			
,	N/A	Provided	N/A			
	N/A	Provided	N/A			
	<u> </u>					
1) Basement	N/A	N/A	N/A			
	N/A	N/A	N/A			
	N/A	N/A	N/A			
ceiling		6				
Internal Hydrants	3					
1) Size of riser/down-comer	N/A	N/A	N/A			
	N/A	N/A	N/A			
	2					
	N/A	N/A	N/A			
	5	3 4 3 9	<u> </u>			
	N/A	N/A	N/A			
	N/A	N/A	N/A			
			X 2			
	N/A	N/A	N/A			
		N/A	N/A			
	N/A	N/A	N/A			
		N/A	N/A			
	1	N/A	N/A			
	N/A	N/A	N/A			
		N/A	N/A			
		N/A	N/A			
		N/A	N/A			
	450 LPM	450 LPM	MR			
	30 mtr.	30 mtr.	MR			
		Provided	MR			
		Provided	MR			
a, ridio builting of pull	T - 124 - 114					
	First-Aid Hose Reel 1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter Automatic Fire Detection & A 1) Type of detectors 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box Yard Hydrants 1) Total number of hydrants 2) Hose box Pumping Arrangement 1) Ground level a) Discharge of main pump c) Number of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump out put e) Jockey pump head f) Stand by pump head h) Auto starting/Manua stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply	First-Aid Hose Reel 1) Total number of eachfloor 2) Length of hose reel hose 3) Mozzle diameter 5 mm Automatic Fire Detection & Alarming Syste 1) Type of detectors N/A 2) Location of main panel N/A 3) Location of repeater panel N/A 4) Alternate source of power N/A Public Address System Automatic Sprinkler System 1) Basement N/A 2) Upper floors N/A 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer N/A Yard Hydrants 1) Total number of hydrants N/A Pumping Arrangement 1) Ground level A) Discharge of main pump N/A N/A N/A Pumping Arrangement N/A N/A N/A Pumping Arrangement N/A N/A Pumping Arrangement N/A N/A N/A N/A N/A N/A N/A N/	Total number of eachfloor 01			

14.	Captive Water Storage for Fire Fighting					
	1) Under ground tank capacity	N/A	N/A	N/A		
	a) Draw-off connection	N/A	N/A	N/A		
	b) Fire service inlet	N/A	N/A	N/A		
	c) Access to tank	N/A	N/A	N/A		
	d) Over head tank capacity	5000 ltrs.	5000 Ltr.	MR		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.					
	a) Pressurization of lift shaft	N/A	N/A	N/A		
	b) Pressurization of lift lobby	N/A	N/A	N/A		
	c) Communication in lift car	N/A	N/A	N/A		
	d) Fireman's switch	N/A	N/A	N/A		
	e) Lift signage	N/A	N/A	N/A		
17.	Stand by Power Supply	Required	Provided	MR		
18.	Refuge Area	N/A	N/A	N/A		
	Total area location	N/A	N/A	N/A		
19.	Fire Control Room	N/A	N/A	N/A		
	a) Detector system panel	N/A	N/A	N/A		
	b) Flow switch panel	N/A	N/A	N/A		
	c) PA system panel	N/A	N/A	N/A		
	d) Battery backup	N/A	N/A	N/A		
	e) Building floor plan	N/A	N/A	N/A		
20.	Special Fire Protection Syste Risk, if any:	m for Protect	ion of special	NA		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire measures as required under the rules the FSC issued vide letter no. safety F6/DFS/MS/EH/2015/NDZ/1905 dated 23/10/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Office

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFO/NDZ

P. M. SCELL FT/D.