GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 2524

FIRE SAFETY CERTIFICATE

Certified that the Hotel Neelam Place Dx. Guest House located at 7977, Arakashan Road, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (Reception + 01 office + Internet cafe with separate entry), 1st floor to 3rd floor (06 guest rooms at each floor), 4th floor (02 staff rooms + kitchen for staff + DG set) and terrace (01 staff room + kitchen sealed + water tank), total 18 guest rooms owned/occupied by Hotel Neelam Place Dx. Guest House was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/NDZ/1691 dated 15/09/15. The premises was reinspected by the officer concerned of this department on 23/10/18 in the presence of Sh. Dinesh (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued — 12/11/18 at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service okm

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

2. The Manager,

Hotel Neelam Place Dx. Guest House at 7977, Arakashan Road, Pahar Ganj, New Delhi Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	11	ISPE	CTIC)NF	REP	ORT
--	----	-------------	------	-----	-----	-----

1. Name & address of the building

Hotel Neelam Place Dx. Guest House at 7977, Arakashan Road, Pahar Ganj, New Delhi

2. Type of occupancy:- Residential, Sub Division-A-1

Gr. +04 Upper floors (total 18 Guest rooms) Ground floor (Reception +01 office + Internet cafe with separate entry), 1st floor to 3rd floor (06 guest rooms at each floor), 4th floor (02 staff rooms + kitchen for staff + DG set) and terrace (01 staff room

+ kitchen sealed + water tank)

3. Type of case:-

4. Details of previous FSC:-

Renewal No. F6/DFS/MS/GH/2015/NDZ/1691 dated

15/09/15.

5. Fire safety directives No.-

6. Date of inspection:-

N/A 23/10/18

7. Name of the inspecting officer:-

8. Name & designation of officer

Sh. Manoj Kumar Sharma (ADO/CC)

From the building side:9. Year of construction:-

Sh. Dinesh (Manager) 2001

10. Applicant's letter No:-

No. Nil dated 16/10/2018.

10.	Applicant's letter No:-	No. Nil date	d 16/10/2018.				
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety	Provided at site	Old Case Remarks MR/NMR			
1.	Access to Building	arrangements					
	1) Road width	N/A	06 mtr.	NA			
	2) Gate width	N/A	N/A	N/A			
	3) Width of internal road	N/A	N/A				
2.	Number, Width Type & Ar			N/A			
	A. Number of staircases	angement of j	EXIIS				
	1. Upper floors	01 Nos.	01 Nos.	MR			
	2. Basements	N/A	N/A	N/A			
	B. Width of staircase	1 1/11	IV/A	N//\			
	1. Upper floors	0.80 mtr.	1.20 Mtr.	MR			
	2. Basements	N/A	N/A	N/A			
	C. Protection of exits			1.07.1			
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous staircase to terrace	N/A	N/A	N/A			
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size	1 mtr.	1 mtr.	MR			
3.	Compartmentation						
	1) Fire check door	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
	3) Fire rating of shaft door	N/A	N/A	N/A.			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
	Smoke Management System						
	1) Basements	30 ACPH	N/A	N/A			
	2) Upper floors	12 a/c per hour		MR			

	T		1.					-	
5.	Fi	re Extinguishers	1						
1) 7		Total numbers 10 No		Nos.	10	Nos.	M	R	
		Types		C & CO2	AB	C & CO2	M	R	
		ISI marking	Required		Pro	vided	MR		
5.									
1)		Total number of eachfloor	01		01		M	R .	
		Length of hose reel hose	30 r	ntr.	30	mtr.	M	MR	
		Nozzle diameter	05 r	nm	05	mm	M	R	
7.		itomatic Fire Detection &	Aları	ming Syste	em				
	_	Type of detectors	N/A		N/	A	N	A	
		2) Location of main panel N/A			N/.	A	N	N/A	
		Location of repeater panel	N/A	1	N/	Α		/A	
		Alternate source of power	N/A	1	N/A N/A			N/A	
		Hooter's Location	N/A	A			N.	/A	
8.	/	OEFA	Rec	quired	Pro	ovided	M	R	
9.		iblic Address System		uired	Provided		MR		
10.	Automatic Sprinkler System								
		1) Basement N/A 2) Upper floors N/A		A	N/	A		/A	
				A	N/A		-	N/A	
3)		Sprinkler above false	N/A	A	N/	/A	N	/A	
		iling							
		ternal Hydrants				S. Control of the Con			
	1) Size of riser/down-comer N/A		4	N/A		N/A			
		Number of hydrants per	N/A	4	N/	A	N/A	/A	
	fle	oor							
12. Yard		Hose box	N/A	4	N/A		N/A		
		Yard Hydrants		/A N/A) NI/A		
		1) 100011111111111111111111111111111111				N/A N/A			
	2)	Hose box	N/A	4	N/	A	IN	1/A	
13.		Pumping Arrangement		^					
		1) Ground level		N/A		N/A	•	N/A	
		a) Discharge of main		N/A N/		N/A		N/A	
		pump				2.7/4		N. 1/A	
		b) Head of main pump		N/A		N/A		N/A	
	c) Number of main pump		N/A		N/A		N/A		
		d) Jockey pump out put		N/A N/A			N/A		
		e) Jockey pump head		N/A N/A			N/A		
		f) Stand by pump output		N/A N/A			N/A		
		g) Stand by pump head		N/A N/A			N/A		
		h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump		N/A N/A 180 LPM 180 LPM			N/A		
							NAD:		
							MR		
		b) Head of pump		30 mtr. 30 mtr.			MR		
¥		c) Power supplyd) Auto starting of pump		Required Provided Required Provided			MR		
				D					

14.	Captive Water Storage for I	ire Fighting		
0 = 0	Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syst Risk, if any:	em for Protec	ction of special	NA

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/1691 dated 15/09/2015 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

DERO (NDZ) 1/2 CEQ- MSCELL F710. W3T)