## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 2272

Dated: -9/10/18

## FIRE SAFETY CERTIFICATE

Certified that the M/s Ashoka Guest House located at 1969-71, Katra Lochaoo Singh, Fountain, Chandani Chowk, Delhi comprised of Ground (Reception + Commercial), 1st floor to 3rd floor (11 guest rooms at each floor) and 4th floor (01 store + 01 staff room + 01 generator room), total 33 guest rooms owned/occupied by M/s Ashoka this department **FSC** by Guest House was granted The premise was re-inspected by the No.F6/DFS/MS/GH/2015/NDZ/1683 dated 15/09/15. officer concerned of this department on 22/09/18 in the presence of Mohd. Samir (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 for 33 guest rooms with effect from -9+10+18----for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -- ?- 1-6) +8----at New Delhi by.

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager, M/s Ashoka Guest House at 1969-71, Katra Lochaoo Singh, Fountain, Chandani Chowk, Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

DICDECONTOR	-
INSPECTION REPORT	
TOT DOT NEPUK	

1. Name & address of the building

M/s Ashoka Guest House at 1969-71, Katra Lochaoo Singh, Fountain, Chandani Chowk,

Delhi

2. Type of occupancy:-

Residential, Sub Division-A-1

Gr. + 04 Upper floors (total 33 Guest rooms)

Ground (Reception + Commercial), 1st floor to 3rd floor (11 guest rooms at each floor) and 4th floor (01 store + 01 staff room + 01

3. Type of case:-

Renewal

4. Details of previous FSC:-

No. F6/DFS/MS/GH/2015/NDZ/1683 dated 15/09/15.

5. Fire safety directives No.-

N/A

6. Date of inspection:-

22/09/18

7. Name of the inspecting officer:-

Sh. Manoj Kumar Sharma (ADO/CC)

8. Name & designation of officer From the building side:-

Mohd. Samir (Manager)

9. Year of construction:-

1988

10. Applicant's letter No:-

Nil dated 07/09/2018.

S.No.	Minima			Old Case
	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safetarrangements	Provided at site	e Remarks MR/NMR
1.	Access to Building	diffunction		IVIICINIVIN
	1) Road width	N/A	08 feet	) (D
	2) Gate width	N/A	N/A	MR
	3) Width of internal road	N/A	NI/A	N/A
2.	Number, Width Type & Ar	rangement of F	vite N/A	N/A
	A. Number of staircases	- Magement of E	AILS	
	1. Upper floors	01 Nos.	01 Nos.	MD
	2. Basements	N/A	N/A	MR
	B. Width of staircase		TWA	N/A
	1. Upper floors	0.80 mtr.	1.19 mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits		11/11	IN/A
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	01	01	MR
	E. Width of corridor	N/A	N/A	
-	F. Door size	0.80 mtr.	0.90 mtr.	N/A MR
3.	Compartmentation		0.50 IIII.	IVIK
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
-	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
1.	Smoke Management System			14/11
	1) Basements	30 ACPH	N/A	N/A
	2) Upper floors	12 ACPH		MR
	Pina P. C.			
•	Fire Extinguishers			

5.	Fire Extinguishers		V	
	1) Total numbers	12 Nos.	12 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel	· · · · · · · · · · · · · · · · · · ·		
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 m	30 m	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &	Alarming Syste	em	
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			
,	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	s	a a	
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor			
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants	·		2
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement			
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump			
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump		N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual stopping	N/A	N/A	N/A
	2) Terrace level			
	a) Discharge of pump	225 LPM	225 LPM	MR
	b) Head of pump	25 mtr.	25 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump		Provided	MR

14.	Captive Water Storage for Fire Fighting				
	Under ground tank     capacity	N/A	N/A	N/A	
	a) Draw-off connection	N/A	N/A	N/A	
	b) Fire service inlet	N/A	N/A	N/A	
	c) Access to tank	N/A	N/A	N/A	
	d) Over head tank capacity	2,500 ltr.	2,500 ltr.	MR	
15.	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts.		El Company		
	a) Pressurization of lift shaft	N/A	N/A	N/A	
	b) Pressurization of lift lobby	N/A	N/A	N/A	
	c) Communication in lift car	N/A	N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
	e) Lift signage	N/A	N/A	N/A	
17.	Stand by Power Supply	Required	Provided	MR	
18.	Refuge Area	N/A	N/A	N/A	
	Total area location	N/A	N/A	N/A	
19.	Fire Control Room	N/A	N/A	N/A	
	a) Detector system panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A	
	e) Building floor plan	N/A	N/A	N/A	
20.	Special Fire Protection Syste Risk, if any:	m for Protect	tion of special	N/A	

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/1683 dated 15/09/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFO (NDZ) In.

CF.G. M-Sell F1b.

Willo.

1881 OF NOZ PI Letter is part up

APRILE.