GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6 / DFS / MS / School/2018 / 2506

Dated: 9/11/2018

FIRE SAFETY CERTIFICATE

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.Delhigovt.nic.in

(Adul Garg)
Chief Fire Officer
Ph:-011-23414250

Copy to: -

1. The Director, Education, Government of N.C.T of Delhi. Old Sectt. Delhi - 110054.

The Principal, M.C Primary School, Nehru Kutir, Malka Ganj, Delhi-110007.

INSPECTION REPORT

1. Name & address of the building

Type of Occupancy

: M.C Primary School, Nehru Kutir, Malka Ganj, Delhi-110007.

:Educational

3. Type of Case

:Renewal (Ground plus 02 upper floors)

4. Details of previous NOC

:F6/DFS/MS/2015/School/WZ/72

Dated: 15/01/2015

5. Fire Safety directives letter No

: NBC Part-IV

6. Date of inspection

: 25/10/2018

7. Name of the Inspecting Officers

: ADO (RN)

8. Name and designation of officers

from the building side

: Mrs. Nirmala Malik (Principal)

9. Year of Construction

: 2011

10. Applicant's letter No.

: Nil dated: 14.09.2018

Plot Area-2500 m2

Covered Area:1145.m2

	fire safe	on fire prevention and ty U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR
1	Access to building				
	 Road width 		06m	0.5	2.
	Gate width			06m	MR
	Width of interns	al road	4.5m	4.5m	MR
		& Arrangement of Exits	NA	NA	NA
	a. Number of staircases	Triangement of Exits			
	• Upper Floors			2 2 2	
	Basements		02	02	MR
	b. Width of staircases		NA	NA	NA
	• Upper Floors		-4-6		
	• Basements		1.5 m	1.65 m each	MR
	c. Protection of exits		NA	NA	NA
	Fire check door				
	 Pressurization 		NA	NA	NA
	d. No. of continuous staire	cases to terrace	NA	NA	NA
	e. Width of Corridor		01	02	MR
	f. Door Size		2m	2.20m	MR
	Compartmentation.		1 m	1.05m double door	MR

	Fire check door	NA	NA	NA		
	 Sealing of electrical shafts 	NA	NA	NA		
	• Fire Rating of shaft door	NA	NA	NA		
	Water Curtain	NA	NA	NA		
	Fire Dampers	NA	NA			
4	Smoke Management System.	INA	INA I	NA		
	Basements	30 a/c per hour	NA _	NA		
	• Upper floors	12 a/c per hour	Natural Ventilated	MR		
5	Fire Extinguishers					
	Total numbers	06nos	08nos	MR		
	• Types	ABC/Co2	ABC-08	MR		
	ISI marking	ISI Marked	Provided	MR		
6	First-Aid Hose Reels.					
	Total numbers on each floor	01	01	MR		
	 Length of hose reel hose 	30m	30m	MR		
	Nozzle diameter	5mm	5mm	MR		
7	Automatic fire detection and alarming system.					
	Type of detectors	NA	NA	NA		
	 Location of Main Panel 	NA	NA	NA		
	Location of Repeater Panel	NA	NA	NA		
	Alternate source of power	NA	NA	NA		
	Hooters' Location	NA	NA	NA		
8	MOEFA	NA	NA	NA		
9	Public Address System.	IVA	NA .	INA		
10	Automatic Sprinkler System.					
	Basement	NA	NA I	NA		
	Street Substitution of the Street Substitution o	NA	NA NA	NA NA		
	• Upper Floor	NA	NA	NA		
11	Sprinkler above false ceiling		l'			
1 1	Internal Hydrants	<u> </u>		16		
	Size of riser/down-comer	NA	NA	NA		
	Number of hydrants per floorHose Box	NA	NA	NA		
10		NA	NA	NA		
12	Yard Hydrants.					
	Total number of hydrants	NA	NA	NA		



		• Hose Box	NA	NA	NA		
13	Pumping Arrangements.						
	-						
		• Ground Level			-		
		Discharge of main Pump	N/A	N/A	DI/A		
		Head of Main pump			N/A		
		Number of main pumps	N/A	N/A	N/A		
	1	Jockey Pump out put	N/A	N/A	N/A		
		Jockey pump head	NA	NA	NA		
		Standby Pump out put	NA	NA	NA		
		Standby Pump Head	N/A	N/A			
		Auto Starting/ Manual stoppingPump House Access			N/A		
		Terrace level	N/A	N/A	N/A		
			N/A	N/A	N/A		
		 Discharge of pump Head of the pump 					
		er the pump	450lpm	4501pm	MR		
		tower suppry	40m	40m	MR		
	1	Auto Starting of pump	Required	Provided	MR		
4	- 1		Required	Provided	MR		
4	Capti	aptive Water Storage for fire fighting.					
	•	Underground tank capacity	NA	NA	NA		
	>	Draw-off connection	NA	NA			
	>	Fire service inlet	NA	NA	NA		
	>	Access to tank	NA	NA NA	NA		
	•	Overhead Tank capacity			NA		
5	Evit C:	gnage.	10,000 ltrs	10,000 ltr	MR		
	1		Required	Provided	MR		
5	Provision of Lifts.						
	•	Pressurization of Lift Shaft	N/A	N/A	N/A		
	•	Pressurization of Lift lobby	N/A	N/A	N/A		
	•	Communication In lift Car	N/A				
	•	Fireman's Grounding Switch		N/A	N/A		
	•	Lift Signage	N/A	N/A	N/A		
	Standl		N/A	N/A	N/A		
		y power supply	N/A	N/A	N/A		
	Refuge	Area.					



				1
	> Total Area	N/A	N/A	N/A
	Location	N/A	N/A	N/A
19	Fire Control Room			
	Detector System Panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	PA System PanelBatter backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A
		N/A	N/A	N/A
20	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	N/A

The fire protection systems provided in the building were tested/ checked randomly and found in working condition at the time of inspection.

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and fire safety required as stipulated in Director of Education Circular / NBC Part 4, the FSC issued vide letter of even no 72 dated 15.01.2015 renewal under rule 35 of the Delhi Fire Service Rules, 2010 is recommended

Signature of the Inspecting Officer

Name:- Rajesh Kumar Designation:- ADO/RN

To west Allolis

As exproved, f.t. tetter is forther production of 1 1

08/11/18

pul