GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DLEHI - 110 001

No. F.6/DFS/MS/FH/SZ/2018/ 2532

Dated: 15/11/18

FIRE SAFETY CERTIFICATE

Certified that the **The Mor Bagh Hospitality Farm House**, located at Khasra No. 582, 686/2, 687, 709 & 710, Village Gadaipur, Farm House No. 01, Bandh Road, 4th Avenue Road, New Delhi-110074 comprised of Sunken basement & ground floor. The Farm House was inspected by the officer concerned of this department on 09/11/2018 in the presence of Sh. Rakesh Kumar (Authorized Signatory) & found to have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010and that the building is fit for occupancy class D "Assembly Building Farm House" with effect 15/11/2018 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010.

(Vipin Kental) Chief Fire Officer Ph:-011-23412235

Copy to:-

- 1. The Assistant Engineer (Bldg), SDMC, South Zone, Green Park, New Delhi {Ref: Letter No. D/279/AE (Bldg.)/SZ/2018 dated 26/04/2018}
- 2. Sh. Rakesh Kumar (Authorized Signatory), The Mor Bagh Hospitality Farm House, Khasra No. 582, 686/2, 687, 709 & 710, Village Gadaipur, Farm House No. 01, Bandh Road, 4th Avenue Road, New Delhi-110074

Conditions for the validity of fire safety certificate:

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. The owner/ occupier shall submit a declaration **every year** in **Form 'K'** provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on http://delhi.gov.in/wps/wcm/connect/doit fire/FIRE/Home/Forms
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in **Form 'J'** [sub rule (1) of rule 37] along with a copy of this Certificate, **six months** prior to its expiry."

	T	VSPE	CTION DEPORT	r				
1.	Name & address of the building :	INSPECTION REPORT : Mor Bagh Hospitality at Khasra No. 582, 686/2, 687, 709 & 710, Village Gadaipur, Farm House No. 01, Bandh Road, 4 th Avenue Road, New Delhi-110074						
	Type of Occupancy :			up "D" (Farm House)				
		: New						
	was a	: NA : F6/DFS/MS/BP/2018/3989 dated 24/09/2018						
		09/11.	/2018	989 dated 24/09/2018				
7.]	Name of Inspecting Officer :	A.K.						
	Name and designation of officers							
	From the building side : Year of Construction :	Sh. Ra	akesh Kumar (Au	thorized Signatory)				
		1990	[Sunken basemer	nt & ground floor]				
S.	Minimum Standards on fire preven	ition	BBL/NBC	2 dated 31/10/2018 Provided at site		Dameaulea		
Vo.	and fire safety U/R 33	ILIOII	Requirement	r rovided at site		Remarks MR/NMR		
	Access to building					TYTIVITY		
	 Road width 		9 m	30m/18m	pi'	MR		
	• Gate width		6 m	Provided		MR		
	• Width of internal road		-NA-	-NA-	1	-NA-		
•	Number, Width, Type & Arrangema. Number of staircases	ent of	Exits					
	×		N. F. A.		-	T		
	Upper FloorsBasements		-NA-	-NA-		-NA-		
	b. Width of staircases		One	Provided		MR		
	The second secon							
	• Upper Floor		-NA-	-NA-		-NA-		
	Basements Distriction of the second		1.25m	1.65m		MR		
	c. Protection of exits • Fire check door							
	Pressurization		-NA-	-NA-		-NA-		
	d. No. of continuous staircases to ter	race	-NA-	-NA-		-NA-		
	e. Width of Corridor	race	One	0.75m (Spiral-RCC) GF to Terr	ace	MR		
	f. Door Size		-NA-	-NA-		-NA-		
•	c c	18	lm	Provided (final exit)		MR		
	Compartmentation							
	Fire check door		-NA-	-NA-	1, 2	-NA-		
	• Sealing of electrical shafts		-NA-	-NA-		-NA-		
	Fire Rating of shaft doorWater Curtain		-NA-	-NA-		-NA-		
	• Fire Dampers	-	-NA-	-NA-	-	-NA-		
	The Dampers		-NA-	-NA-	,	-NA-		
•	Smoke Management System		3	1.11	-	111/1		
	• Basements		-NA-	Natural Ventilation	-	-NA-		
	Upper floors		-NA-	Natural Ventilation		-NA-		
	Fire Extinguishers	* / *	4 . 4 . 4 . 5	raturar v chimanon		-1NA-		
	Total numbers		Required	4 No's		MR		
	Types		ABC/W.Co ₂ / Co ₂	2/2/		MR		
	 IS marking 		Required	Provided		MR		
ż	First-Aid Hose Reels	ě,	21 21	1 TOVICE		IVIIX		
	 Total numbers on each floor 		One	Provided		MR -		
	Length of hose reel hoseNozzle diameter		30 m	Provided		MR		
	Nozzle diameter	Dy. C	5 mm /	Provided	1	MR		
	Automatic fire detection and alarmi	ng sys	tem		1.	The same of the sa		
	Automatic fire detection and alarmic Type of detectors Location of Main Panel Location of Repeater Panel	Par	-NA-	-NA-	K	-NA-		
	Location of Main Panel	Black	-NA-	-NA-	1	NA-		
	 Alternate source of power 	~ + O /	-NA-	-NA-	奏	PONA		
	 Hooters' Location 		-NA-	-NA-		-NA-		
1		-	-NA-	And the same of th	1			

3.	MOEF	A	Required	Provided	MR		
).	THE RESERVE THE PERSON NAMED IN COLUMN 2 IS NOT THE OWNER.	Address System	-NA-	-NA-	-NA-		
0.	AND DESCRIPTION OF THE OWNER, THE	atic Sprinkler System	L				
		Basement	-NA-	-NA-	-NA-		
	•	Ground Floor	-NA-	-NA-	-NA-		
	•	Sprinkler above false ceiling	-NA-	-NA-	-NA-		
11.	Internal Hydrants						
	•	Size of riser/down-comer	100 mm	Provided	MR		
	•	Number of hydrants per floor	One	Provided	MR		
	•	Hose Box	One	Provided	MR		
12.	Yard Hydrants						
	•	Total number of hydrants	-NA-	3 No's provided	-NA-		
	•	Hose Box	-NA-	3 No's provided	-NA-		
13.	Pumpi	ng Arrangements					
	•	Ground Level	8		·		
		Discharge of main Pump	-NA-	-NA-	-NA-		
		> Head of Main pump	-NA-	-NA-	-NA-		
		Number of main pumps	-NA-	-NA-	-NA-		
	n (> Jockey Pump out put	-NA-	-NA-	-NA-		
		> Jockey pump head	-NA-	-NA-	-NA-		
		Standby Pump out put		-NA-	-NA-		
		Standby Pump Head	-NA-	-NA-	-NA-		
		> Auto Starting/Manual	-NA-				
		Stopping	-NA-	-NA-	-NA-		
		> Pump House Access	-NA-	-NA-	-NA-		
		Terrace level					
	Discharge of pump	450 LPM	Provided	MR			
		> Head of the pump	40 mtr	Provided	MR		
		Power Supply	Required	Provided	MR		
		> Auto Starting of pump	Required	Provided	MR		
14.	Captive Water Storage for fire fighting						
			-NA-	-NA-	-NA-		
		> Draw-off connection	-NA-	-NA-	-NA-		
		> Fire service inlet	-NA-	-NA-	-NA-		
		> Access to tank		-NA-	-NA-		
	•	Overhead Tank capacity	-NA- 20000 Ltr.	Provided	MR		
1 ~	E :4 C	X	Required	Provided	MR		
15.		Signage.	Required				
16.	Provi	sion of Lifts.		NY A	NIA		
	•	Pressurization of Lift Shaft	-NA-	-NA-	-NA-		
	•	Pressurization of Lift lobby	-NA-	-NÀ-	-NA-		
	•	Communication In lift Car	-NA-	-NA-	-NA-		
	•	Fireman's Grounding Switch	-NA-	-NA-	-NA-		
	•	Lift Signage	-NA-	-NA-	-NA-		
17	Stone	Thy nowar supply	Required	Provided	MR		
17.			Required	A TOTAGO			
18.			-NA-	-NA-	-NA-		
			-NA-	-NA-	-NA-		
19.	, Dodger						
17.	Fire !	COLLI DI INDUILI		-NA-	-NA-		
1		D / / C / - D 1	NIA		1 11 7		
	Fire		-NA-		NTA		
		Flow Switch Panel	-NA-	-NA-			
		Flow Switch Panel PA System Panel			-NA-		
	•	Flow Switch Panel	-NA-	-NA-			

20. Special Fire Protection System for Protection of special Risks, if any:	-NA-	-NA-	-NA-
			* * * * * * * * * * * * * * * * * * * *

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view of the above substantial compliance of the minimum standards of fire prevention and fire safety measures as required under the rules it is recommended under Rule 35(3) to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Accordingly Form 'H' is shape of DFA is put up for approval under Rule 35(4).

Signature of Inspecting Officer

Name: A. K. Malik
Designation: DO (SD)

Dy. CFO (SZ)

Lapril 1210

CANSM

ms cell

14/1/

198/cfo 52

