# FORM 'H'

#### FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

**NEW DELHI** 

No. F6/DFS/MS/WZ/2018/ 2577

Dated: 30/11 /2018

#### FIRE SAFETY CERTIFICATE

Issued on ...} at New Delhi by.

Chief Fire Officer,
Delhi Fire Service

# Copy to:

 The Authorized Person, Shopping Mall, Community Centre, Block- A Shalimar Bagh New Delhi-110088

# Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 9. All the doors, Exits and internal roads must be kept free from any obstruction.

#### **INSPECTION REPORT**

 Name & address of the building: Shopping Mall, Community Centre Located at Block- A Shalimar Bagh New Delhi-110088

2. Type of Occupancy

: Class F (Mercantile)

3. Type of Case

: Renewal

4. Details of previous FSC : L. No. F6/DFS/MS/2015/WZ/1035 dated 18-06-15

5. Fire Safety directives Letter No. F6/DFS/MS/BP/2004/2443 dated 14-10-2004

6. Date of inspection

: 29/10/2018

7. Name of the Inspecting Officer: ADO (WP) & DO/W

8. Name and designation of Officer

from the building side : Sh. Abhishek Sharma

9. Year of Construction

: 2006

10. Applicant's letter No.

: Nil Dated-Nil

S	Minimum standards on fire		quirement	S	Provided at site	Re	Remarks		
N	prevention and fire safety	As	N/23			M	R/NMR		
0	U/R 33								
1.	Access of building								
	• Road width		12 m		24mtr	MR			
	Gate width		4.5 m 6 m		5m Provided		MR		
	Width of internal ro	ad			Provided		R		
2.	Number, width, Type & Art	Number, width, Type & Arrangements of exits							
	a. Number of staircase	S			9				
	<ul> <li>Upper floors</li> </ul>				vided	M	MR		
	<ul> <li>Basements</li> </ul>	16			rovided		MR		
	b. Width of staircases								
	<ul> <li>Upper floors</li> </ul>		2x2m &8x1.5m F		ovided (Old case)	MR (	MR (Old case)		
	<ul> <li>Basements</li> </ul>	2x2n	n&14x1.5m	Pr			MR(Old Case)		
	c. Protection of exits			- 1	I.				
	<ul> <li>Fire check door</li> </ul>	Req	Required Required Required 1.5m		Provided		MR		
	<ul> <li>Pressurization</li> </ul>	Req			Provided Provided Provided		MR		
	d. No of continuous staircase to terrace	Req					MR		
	e. Width Of Corridor						MR		
	f. Door Size	1.5n			Provided		MR		
3.	Compartmentation								
	<ul> <li>Fire check door</li> <li>Sealing of electrical shaft</li> <li>Fire Rating of shaft door</li> </ul>				Provided		MR		
					Provided		MR		
			Required		Provided		MR		
	Water Curtain     Fire Democra		Required		Provided		MR		
	<ul> <li>Fire Dampers</li> </ul>		Required		Provided		MR		
1.	Smoke managements Systen	n							
	<ul> <li>Basements</li> </ul>	R			Provided		MR		
	<ul> <li>Upper floors</li> </ul>	R			rovided		MR		
j	Fire Extinguishers								
	<ul> <li>Total numbers</li> </ul>	5	50 ABC, CO2 &		Provided		MR		
	<ul> <li>Types</li> </ul>	A			Provided		MR		
	IS marking	1	CO2		Provided		MR		
		IS	ISI marked						

6.	First -	- Aid Hose Reels		yelloud a company	- Committee				
	•	Total numbers on each f	loor	4	Pre	ovided		MR	
	•	Length of hose reel hose		30m	Pı	rovided		MR	
	•	Nozzle diameter		5 mm	Pro	ovided		MR	
7.	Auton	natic fire detection and ala	rming	system				¥.	
	•	Type of detectors		Smoke & H	leat	Provided	1	MR	
	•	Location of Main Panel		Ground floor Provided		Provided		MR	
	•	Location of Repeater Pa	nel	el Ground floor		Provided		MR	
	•	Alternate source of power				Provided		MR	
	•	Hooters' Location		Required Provided			MR		
8.	MOEI	FA		Required Provided			MR		
9.	Public	Address System		Required		Provided		MR	
10	Auton	natic Sprinkler System	-						
	•	Basements	Requ	equired Provided		MR	MR		
	•	Upper Floor	Requ	Required		Provided		MR	
	•	Sprinkler above false	Requ	equired		Provided		MR	
		ceiling							
11	Intern	al Hydrants							
	•	<ul><li>Size of riser/down- comer</li><li>Number of hydrants per floor</li></ul>		150 mm	Fu	Functional		MR	
	•					Provided	MR		
	•	Hose Box		4		Provided	MR		
12	Yard I	Hydrants							
	•	Total number of hyds	6		Prov		MR		
	•	Hose Box	6		Prov	Provided		MR	
13	Pumpi	ing Arrangements						7	
	•	Ground Level				· · · · · · · · · · · · · · · · · · ·			
	•	Discharge of main pump	-	00lpm		nctional	MR		
	<b>A</b>	Head of main pump		m		Provided Provided Functional		MR MR MR	
	A	Number of main pumps Jockey pump out put	3	100 1					
	A	Jockey pump head	_	vo180 lpm m		Provided		MR	
	>	Standby Pump out put		00 lpm		Functional		MR	
	A	Standby Pump Head		mtr		Provided		MR	
	>	Auto Staring/Manual		quired		Provided			
		stopping		required					
		Pump House Access	Re	Required		Provided		MR	
	•	Terrace level		-					
	<b>A</b>	Discharge of pump	NA	NA		NA		NA	
	>	Head of the pump	NA	A	NA.	NA		NA	
		Power supply	NA		NA	NA		NA	
	>	Auto starting of pump				NA	NA		
14	Captiv	ve water Storage for fire fi	ghting	5					
•		II. J	20	0.000 1:4	D	vidad	- N	(D	
190	>	Under ground tank cpty Draw of connection		0,000 litres	Provided Provided		MR MR		
		Fire service inlet		1					
		Access to tank	-	quired quired		Provided Provided Provided ovided		MR MR MR	
	•	Overhead Tank capacity	-	000 litres					
15	Exit S	ignage						MR	
16		ion of Lifts	1						
	>	Pressurization of Lift Sh	aft	Required	Pro	Provided		MR	
	>	Pressurization of lift lob	by	Required		Provided in basment		MR	
	>	Communication in lift C	ar	Required	Pro	Provided		MR	
	>	Fireman's Grounding		Required	Pro	Provided		MR	
	Switch								
		Lift Signage		Required	Pro	vided	M	IR	
								THE REAL PROPERTY.	

17	G4 11 1	Degrained	Provided	MR				
17	Standby power supply	Required	Provided	IVIIX				
18	Refuge Area							
	> Total area	NA	NA	NA				
	> Location	NA	NA	NA				
19	Fire control room							
	Detector system panel	Required	Provided	MR				
	Flow Switch Panel	Required	Provided	MR				
	PA System Panel	Required	Provided	MR				
	Battery backup	Required	Provided	MR				
	Building Floor Plans	Required	Provided	MR				
20	Special Fire Protection Systems	Required	Co2 Flooding in	MR				
١.	for Protection of special Risks, if		DG Room					
	any;							

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/2015/WZ/1035 dated 18-06-15 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Signature of the Inspecting Office

Name Udos Vir Singh Designation Abolup

Name Sh Mozegh Verna

Designation Dolu

Apolupi for the letter is botop ton