GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 2/93

Dated :----03/12/18

FIRE SAFETY CERTIFICATE

Certified that the D Inn Guest House located at 3685-89, 3691-92 & 3703/XV, Gali Dariba Pan, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (reception + 02 guest rooms +01 office), 1st floor to 3rd floor (05 guest rooms at each floor) and terrace floor (Mumty + water tank + open terrace) total 17 guest rooms owned/occupied by D Inn Guest House was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/NDZ/1775 dated 01/10/15. The premises was re-inspected by the officer concerned of this department on 15/11/18 in the presence of Mr. Farooq (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 17 guest rooms only with effect from ---23/+24/3----for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued ---- at New Delhi by.

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager,

D Inn Guest House 3685-89, 3691-92 & 3703/XV, Gali Dariba Pan, Pahar Ganj, New Delhi Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPE	CTION	REPORT
TIANIT		

Name & address of the building:-

D Inn Guest House located at 3685-89, 3691-92 & 3703/XV, Gali Dariba Pan, Pahar Ganj,

New Delhi

2. Type of occupancy:-

Residential, Sub Division-A-1

Gr. + 04 Upper floors (total 17 Guest rooms) Ground floor (reception + 02 guest rooms +01 office), 1st floor to 3rd floor (05 guest rooms at each floor) and terrace floor (Mumty + water tank + open terrace)

3. Type of case:-

No. F6/DFS/MS/GH/2015/NDZ/1775 dated

01/10/15.

5. Fire safety directives No.-

4. Details of previous FSC:-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

15/11/18

Sh. Manoj Kumar Sharma (ADO/CC)

Mr. Farooq (Manager)

2007

N/A

Nil dated 05/11/2018

0.21		70	X	Old Case	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	Remarks MR/NMR	
1.	Access to Building		*		
	1) Road width	N/A	N/A	N/A	
	2) Gate width	N/A	N/A	N/A	
	3) Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arrangement of Exits				
	A. Number of staircases				
	1. Upper floors	01 Nos.	01 Nos.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	1.25 mtr.	1.33 to 1.5 mtr.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits			11/11	
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	01	01	MR	
	E. Width of corridor	1 mtr.	1.28 mtr.	MR	
	F. Door size	1 mtr.	225 MM X 81MM	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
l	Smoke Management System				
	1) Basements	30 ACPH	N/A	N/A	

	2) Upper floors	12 ACPH	Natural Ventilation			
5.	Fire Extinguishers	12 ACI II	ivatural ventilation	MR		
	1) Total numbers	08 Nos.	00.31			
	2) Types	ABC & CO2	08 Nos.	MR		
	3) ISI marking			MR		
6.	First-Aid Hose Reel	Required	Provided	MR		
	1) Total number of each floor 101					
	2) Length of hose reel hose	30 m	01	MR		
	3) Nozzle diameter		30 m	MR		
7.	Automatic Fire Detection 6	05 mm	05 mm	MR		
	Automatic Fire Detection & Alarming System 1) Type of detectors N/A N/A N/A					
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of remarks	N/A	N/A	N/A		
	3) Location of repeater panel		N/A	N/A		
	4) Alternate source of power 5) Hostor's Least'	N/A	N/A	N/A		
3.	5) Hooter's Location MOEFA	N/A	N/A	N/A		
).		Required	Provided	MR		
0.	Public Address System	Required	Provided	MR		
U.	Automatic Sprinkler System		1			
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
1	ceiling					
1.	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor			1471		
_	3) Hose box	N/A	N/A	N/A		
2.	Yard Hydrants	Yard Hydrants				
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A		N/A		
13.	Pumping Arrangement			IVA		
	1) Ground level	N/A	N/A	DT/A		
	a) Discharge of main	N/A	N/A	N/A		
	pump	11/11	IVA	N/A		
	b) Head of main pump	N/A	N/A	DIA		
	c) Number of main pum	p N/A	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A		N/A		
	f) Stand by pump output	t N/A	N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual	N/A	N/A	N/A		
	stopping	IN/A	N/A	N/A		
	2) Terrace level					
	a) Discharge of pump	450 T D3 4	170 7 ===			
	b) Head of pump	450 LPM	450 LPM	MR		
	c) Power supply	30 mtr	30 mtr	MR		
	d) Auto starting of pump	Required Required	Provided	MR		
		1 12 - 1	Provided	MR		

14.	Captive Water Storage for l	Fire Fighting		
	Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	em for Protect	tion of special	NA

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/1775 dated 01/10/2015 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFO/NDZ