GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/NDZ/2018/ 260/

Dated:----

FIRE SAFETY CERTIFICATE

Certified that the Sagar Ratna Restaurant located at K-15, Connaught Circus, New Delhi comprises of Ground + Mezzanine + 02 Upper floor only, Restaurant is running at Ground + Mezzanine floor only owned/occupied by Sagar Ratna Restaurant was granted FSC by this department vide letter No.F6/DFS/MS/EH/2015/NDZ/2065 dated 18/11/15. The premises was re-inspected by the officer concerned of this department on 17/11/18 in the presence of Mr. Saji (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building Group D with effect from (3) 12/12-for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -- 03/12/12 -- at New Delhi by.

(Vipin Kental) Chief Fire officer Delhi Fire Service

Copy to:-

1. The Medical Officer of Health, Health Department, Palika Kendra, New Delhi.

2. The Manager,

Sagar Ratna Restaurant at K-15, Connaught Circus, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSP	ECT	ION	REP	ORT

1. Name & address of the building Sagar Ratna Restaurant at K-15, Connaught

Circus, New Delhi

2. Type of occupancy:- Assembly Building Group-D

Gr. + Mezz. + 02 floor

Restaurant running at Gr. + Mezz. Floor only

3. Type of case:- Renewal

4. Details of previous FSC:- F6/DFS/MS/2015/EH/NDZ/2065 dated

18/11/2015

5. Fire safety directives No.- N/A

6. Date of inspection:- 17/11/18

7. Name of the inspecting officer:- Sh. Manoj Kumar Sharma (ADO/CC)

8. Name & designation of officer

From the building side:9. Year of construction:-

10. Applicant's letter No:-

Sh. Saji (Manager)

Old Hreitage

Nil diary dated 28/10/2018

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	06 mtr.	09 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arrangement of Exits				
	A. Number of staircases		,		
	1. Upper floors	02	02	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	0.86 & 1.02 mtr. Exiting	0.86 & 1.02 mtr.	N/A	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits				
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	01	01	MR	
	staircase to terrace		*		
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1.2 mtr. Exiting	1.2 mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	N/A	N/A	
	2) Upper floors	12 a/c per	Natural	MR	
		hour			
5.	Fire Extinguishers				
	1) Total numbers	06 Nos.	08 Nos.	MR	
	2) Types	ABC & CO2	ABC & CO2	MR	

-	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel			
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &	Alarming Sys	tem	TVIIC
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	Required	Provided	MR
9.	Public Address System	N/A	N/A	N/A
10.	Automatic Sprinkler System	1471	IVA	IN/A
V	1) Basement	N/A	N/A	N/A
	2) Upper floors	Required	Provided	MR
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	1 1/2 1	11/71	IN/A
11.	Internal Hydrants	L		
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A N/A
	floor	14/17	11///	IV/A
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants	11/11	11//1	IN/A
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A N/A
13.	Pumping Arrangement	11/11	IV/A	N/A
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A N/A
	pump	11//	IVA	IN/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump		N/A N/A	
	d) Jockey pump out put	N/A	N/A N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output			N/A
	g) Stand by pump head	N/A N/A	N/A	N/A
	h) Auto starting/Manual	N/A N/A	N/A	N/A
	stopping	IN/A	N/A	N/A
	2) Terrace level			
	a) Discharge of pump	450 & 180	450 0- 100 T D) 4	I MD
	a) Discharge of pullip	LPM	450 & 180 LPM	MR
	b) Head of pump	30 mtr.	20 mates	I A/D
	c) Power supply		30 mtr.	MR
		Required Required	Provided	MR
	d) Alita starting of mirror	r Keamrea	Provided	MR
14	d) Auto starting of pump			•
14.	Captive Water Storage for F	ire Fighting	DT/A	77/1
14.	Captive Water Storage for F 1) Under ground tank		N/A	N/A
14.	1) Under ground tank capacity	ire Fighting N/A		
14.	1) Under ground tank capacity a) Draw-off connection	ire Fighting N/A N/A	N/A	N/A
14.	1) Under ground tank capacity	ire Fighting N/A		

	d) Over head tank capacity	5,000 ltr.	5, 000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
1	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/EH/2015/NDZ/2065 dated 18/11/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma

By CFONDZ

850 CF MMZ

P.T. Letter is pout up for sign. M. Sell

Pet. Letter is pout up for sign. M. Well

Well

Well