FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI – 110001

No. F6 (DFS/MS) 2018/W2/2625

Dated: 6/12/18

FIRE SAFETY CERTIFICATE

Certified that the Lavanya Orchid Banquet Hall located at Plot No. 15, Nazafgarh Road, Shivaji Marg, New Delhi - 110015 in a building comprised of Basement + Ground + 2 Upper Floors was issued NOC/FSC vide this office letter No. Banquet/2014/WZ/1510 dated 03/12/2014. The premises was re-inspected by the officers concerned of this department on 03/12/2018 in the presence of Sh. Vijay Pal Singh Bisht (Proprietor) and observed that all the fire prevention and fire safety arrangements as provided in the premises found in good working condition. The premises have therefore, deemed complied with the requirement under Rule 33 of the Delhi Fire Service Rule 2010 and the building/premises fit for Class-D Assembly occupancy effect under 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under 38 of the Delhi Fire Service Rule 2010.

Issued on at New Delhi by.

Chief Fire Officer

Copy to:

1. The Authorised Signatory,

Lavanya Orchid Banquet Hall, Plot No. 15, Nazafgarh Road, Shivaji Marg, New Delhi.

2. Dy. Health Officer, Karol Bagh Zone, NDMC, Public Health Department, Karol Bagh, New Delhi.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. Basement shall be used strictly as per Building Bye Laws.

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

N/30

Re-Inspection to see the compliance of shortcomings communicated vide letter no.F6/DFS/MS/BNQT/2018/WZ/1928 dated 10/05/2018. In this connection the Proprietor/Occupier has provided a 2 mtr wide sprinkler corridor from basement to ground floor. Also stand by pump has been provided.

INSPECTION REPORT

1. Name & address of the building: Lavanya Orchid Banquet Hall, 15 Main Road, Nazafgarh Road, Industrial Area, Moti Nagar, New Delhi – 110015.

2. Type of Occupancy

: Assembly (Basement + Ground + 2 Upper Floor)

3. Type of Case

: Renewal

4. Details of previous NOC: F6/DFS/MS/Banquet/2014/WZ/1510 dated 03/12/2014

5. Fire Safety directives Letter No.: Nil

6. Date of inspection

: 03-12-2018

7. Name of the Inspecting Officer: MukeshVerma, DO (West)

Plot Area = 669 m² Covered Area Basement=432m², GF=441 m², FF= 441 m²,

 $SF=302 \text{ m}^2$

8. Name and designation of Officer

from the building side

: Sh. Vijay Pal Singh Bisht (Proprietor)

9. Year of Construction

: 2008

10. Applicant's letter No.

: nil dated 30/11/2018

S	Minim	um standards on fire	DDI		D 111		e	
No	prevention and fire safety U/R		BBL		Provided at		Remarks	
NO	33	uon and fire safety U/R	Requirements		site	MR	/NMR	
1		C1 -11 1:						
l	Access of building							
	•	Road width	12 m		Provided	MR ,		
	• Gate width		5 m		On Main	MR		
					Road	*		
	•	Width of internal road	NA		NA	NA		
2.	Numbe	r width Type & Amore					*	
-	a.	r, width, Type & Arrang Number of staircases	ements of exits					
			2					
		Upper floors	2		Provided	M	R	
		Basements	2		03 Provided	M	IR.	
	b. Width of staircases							
	• Upper floors		2 m & 1m 1		1.97 m & 1.55 mtr		MR being	
							old case	
	•	Basements 2 m & 1m		5.5 mtr, 1.97 m &		MR		
			1		1.55mtr			
		1 10 Colon of Carts						
	•	Fire check door	Required		Provided		MR	
	•	Pressurization	Required		Provided		MR	
	d.]	No of continuous	Required		Provided		MR	
	5	staircase to terrace	required		TTOVICEC		IVIIX	
	e.	Width Of Corridor	02 mtr		Provided in		MR	
		A 90			basement		IVIK	
	f.]	Door Size	2m			0_	MD 1 :	
			2111		GF=155, 137 & 106 cm	×	MR being	
				1			old case	
					FF=106 & 237	cm		

3.	Compartmentation	1			**
	Fire check door	Required	Provided	MR	
	• Sealing of electrical shafts	Required	Provided	MR	
	• Fire Rating of shaft door	Required	Provided	MR	
	Water Curtain	NA	NA	NA	
	• Fire Dampers	NA	NA	NA	
4.	Smoke managements System				
	Basements	30 a/c per hour	Provided	MR	
	Upper floors	12 a/c per hour	Provided	MR	
5.	Fire Extinguishers	1			
	Total numbers	12 nos.	Provided	MR	
	• Types	ABC & CO2	Provided	MR	
	• IS marking	ISI marked	Provided	MR	
6.	First – Aid Hose Reels		110,110,0		-
	Total numbers on each	1	Provided	MR	-
	floor	1	110 /1404		
	 Length of hose reel hose 	30 m	Provided	MR	
	Nozzle diameter	5 mm	Provided	MR	
7.	Automatic fire detection and ala				
-	Type of detectors	Smoke & Heat	Provided	MR	
	 Location of Main Panel 	Required	Provided	MR	
	• Location of Repeater Panel	Required	Provided	MR	
	Alternate source of power	Required	Provided	MR	
	Hooters' Location	Required	Provided	MR	-
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System	Required	Provided	IVIIC	-4
10.	Basements	Required	Provided	MR	-
	Upper Floor	Required	Provided	MR	
	0 1 1 1 1 0 1 11		Provided	MR	
11.	• Sprinkler above false ceiling Internal Hydrants	required .	TTOVICE	IVIIX	
11,	Size of riser/down-	100 mm	Provided	MR	
	comer	100 111111	riovided	IVIK	1
	 Number of hydrants 	1	Provided	MR	
	per floor	1	TTOVICEC	TVIIC	
	Hose Box	1	Provided	MR	
12.	Yard Hydrants		TTOTICCE	*	
	• Total number of	NR	NR	NR	
	hydrants		1110	1 117	
	Hose Box	NR	NR	NR	
13.	Pumping Arrangements				
	Ground Level				and the same of th
	 Discharge of main 	2280 lpm	Provided	MR	
	pump		113,1404	1711	
	Head of main pump	40 m	Provided	MR	
	Number of main pumps	1	Provided	MR	
	Jockey pump out put	180 lpm	Provided	MR	
	Jockey pump head	40 m	Provided	MR	
	Standby Pump out put	2280 lpm	Provided elect		
		•	pump connect		44
			with generator		· Blackgring.
	Standby Pump Head	40 m	Provided	MR	
	Auto Staring/Manual	Required	Provided	MR	
	stopping	*			2
	Pump House Access	Required	Provided	MR	
				_	1000
					W. Carlot

Terrace level			8			
Discharge of pump	900 lpm	Provided	MR			
	40 m	Provided	MR			
	Required	Provided	MR			
> Auto starting of pump	Required	Provided	MR			
Captive water Storage for fire						
Under ground tank capacity	50,000 litres	Provided	MR			
Draw of connection	Required	Provided	MR			
16 Additional Action (Action (Provided	MR			
a second	Required	Provided	MR			
 Overhead Tank 	10, 000 litres	Found Provided	MR			
	Required	Provided	MR			
Provision of Lifts						
Pressurization of Lift Shaft	NA	NA	NA			
> Pressurization of lift lobby	NA	NA	NA			
Communication in lift Car	Required	Provided	MR			
Fireman's Grounding	Required	Provided	MR			
Switch Lift Signage	Required	Provided	MR			
	Required	Provided	MR			
Refuge Area						
> Total area	NA	NA	NA			
> Location	NA	NA	NA			
Fire control room						
Detector system panel	NA	NA	NA			
Flow Switch Panel	NA	NA	NA			
PA System Panel	NA	NA	NA			
Battery backup	NA	NA	NA			
Building Floor Plans	NA	NA	NA			
Special Fire Protection Systems for Protection of special Risks, if any;	NA	NA	NA			
	 Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire Under ground tank capacity Draw of connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area Total area Location Fire control room Detector system panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans Special Fire Protection Potentian Fire Protection Particular pump Particu	 Discharge of pump Head of the pump Power supply Auto starting of pump Required Required Required Under ground tank capacity Draw of connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage Standby power supply Required Required Required Required Required NA Pressurization of lift lobby Communication in lift Car Fireman's Grounding Required Required Required Required Required NA NA NA NA NA NA NA Fire control room Detector system panel PA System Panel PA System Panel PA System Panel Battery backup Building Floor Plans NA Special Fire Protection Systems for Protection of 	 Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting Under ground tank capacity Draw of connection Fire service inlet Access to tank Capacity Provided Provided Required Provided Required Provided NA NA			

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC vide letter No. F6/DFS/MS/ Banquet/2014/WZ/1510 dated 03/12/2014 renewal under rule 35 of the Delhi Fire Service rule 2010 is recommended.

Signature of the Inspection Officer

Name MukeshVerma

Designation DO (West)

Dy 40 42/