GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DFS/MS/GH/2018/NDZ/ 2692

Dated 13/12/18.

FIRE SAFETY CERTIFICATE

Issued on 13/12/18 at New Delhi by

(Vipin Kental) Chief Fire Officer

9ch

To,

Sh.Surinder Singh Dara (Owner)
M/s Dara Hospitality Pvt. Ltd. A-47,
Guru Nanakpura, Laxmi Nagar, Vikas Marg, Delhi-92.

Copy to-

1. The Deputy Health Officer, Shahdara(South) Zone, Karkardooma, Delhi.

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1.Name & address of the building: Dara Regency Banquet Hall running at

GF& FF, A-47, Guru Nanakpura, Laxmi Nagar, Vikas Marg, Delhi-92.

2. Building is comprised of

: B+G+3 Upper floors

2. Type of Occupancy

: Assembly(Banquet Hall)

3. Type of Case

: Renewal

4. Details of Previous NOC

: F.6/DFS/MS/GH/2014/NDZ/1286 Dated

17/10/14

5. Fire Safety direction letter No

: NBC Part-IV

6. Date of Inspection

: 22/10/18

7. Name of the Inspecting Officers : R.K.Yadav (ADO)

8. Name of the designation of Officer

from the building side

: Sh.Surinder Singh Dara (Owner)

9. Year of Construction

: 1981 & 1991

10 Applicant's letter No

: Nil Dated 04/10/18

S.No	Minimum Standards on fire	Requirement		Remarks			
0.110	prevention and fire safety U/R33	N	at Site	MR/NMR			
1	Access to building						
	Road width	6 m	15 m	MR			
	Gate width	N.A.	N.A.	N.A.			
	Width of internal road	N.A.	N.A.	N.A.			
2	Number, Width, Type and Arrangement of Exits						
	a. Number of Staircases			2.40			
	Upper Floor	2 no.	2 no.	MR			
	Basement	N.A.	N.A.	N.A.			
	B. Width of Staircases						
	Upper Floor	1.5 m	1.5 m each	MR			
	Basement	N.A.	N.A.	N.A.			
	c. Protection of exits						
	Fire check door	Required	Provided	MR			
	Pressurization	N.A.	N.A.	N.A.			
	e. No. of continuous staircases to	1 no.	2 no.	MR			
	terrace	N.A.	N.A.	N.A.			
	g. Width of Corridor	2 m	2 m	MR			
	h. Door Size						
3	Compartmentation.	N.A.	N.A.	N.A.			
	Fire check door	N.A.	N.A.	N.A.			
	Sealing of electrical shafts	N.A.	N.A.	N.A.			
	 Fire rating of shaft door 		N.A.	N.A.			
	 Water curtain 	N.A.	20.00.00				
	 Fire Dampers 	N.A.	N.A.	N.A.			
4	Smoke Management System.						
	Basement	N.A.	N.A. Provided				
	Upper floor	Required	Provided	IVIIX			

Basement is lying sealed by brick wall.

5.	Fire Extinguisher					
	Total numbers	06 no.	06 no.	MR		
	Types	CO ₂ & ABC	Provided	MR		
	ISI marking	ISI marked	Provided	MR		
6	First-aid-Hose Reels.					
	Total numbers of each floor	1 no	1 no	MR		
	Length of hose reel hose	30m	30m	MR		
	Nozzle diameter	5mm	5mm	MR		
7	Automatic fire detection and alarming system.					
	Type of detectors	N.A.	Provided	MR		
	Location of main panel	Reception	Provided	MR		
	Location of repeater panel	N.A	N.A.	N.A.		
	Alternate source of power	N.A	N.A.	N.A.		
	Hooters's location	Near staircase	Provided	MR		
8	MOEFA		Provided			
9	Public address System.	Required N.A	N.A.	MR N.A.		
10	Automatic Sprinkler System.	IN.A	IV.A.	IV.A.		
10	Basement	N.A.	N.A.	N.A.		
	upper floor	N.A.	N.A.	N.A.		
	sprinkler above false ceiling	N.A.	N.A.	N.A.		
11	Internal Hydrants	IN.A.	IN.A.	IV.A.		
- 1 1	size of riser/down-comer	100 mm	100 mm	MR		
	Number of hydrants per floor	1 no	1 no	MR		
	Hose Box	1 no	1 no	MR		
12	Yard Hydrants.	1110	1110	IVIIX		
	Total number of hydrants	N.A.	N.A.	N.A.		
	Hose Box	N.A.	N.A.	N.A.		
13	Pumping Arrangements.					
	Ground Level	N.A.	N.A.	N.A.		
	 Discharge of main Pump 	N.A.	N.A.	N.A.		
	Head of Main Pump	N.A.	N.A.	N.A.		
6	Number of main pumps	N.A.	N.A.	N.A.		
	Jockey pump out put	N.A.	N.A.	N.A.		
	Jockey pump head	N.A.	N.A.	N.A.		
	Standby pump out put	N.A.	N.A.	N.A.		
	Standby pump Head	N.A.	N.A.	N.A.		
	Auto Starting /Manual	N.A.	N.A.	N.A.		
	stopping	N.A.	N.A.	N.A		
	Pump House Access		14.7 (.	1 4.7		
	 Terrace Level 	450 LPM	450 LPM	MR		
	Discharge of pump	40 M	40 M	MR		
	Head of the Pump	Required	Provided	MR		
	Power supply	Required	Provided	MR		
	Auto Starting of pump	Toquilou	Tovided	INILY		
		1				

14	Captive Water Storage for Fire Fight	ing.		
	Underground tank capacity	N.A.	N.A.	N.A.
	Draw-off connection	N.A.	N.A.	N.A.
	Fire service inlet	N.A.	N.A.	N.A.
	Access to tank	N.A.	N.A.	N.A
	Overhead Tank capacity	10,000 Liters	10,000 Liters	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.			
4	Pressurization of Lift Shaft	N.A.	N.A.	N.A.
	Pressurization of Lift lobby	N.A.	N.A.	N.A.
	Communication in lift car	N.A.	N.A.	N.A.
	Firemen's grounding switch	N.A.	N.A.	N.A.
	Lift Signage	N.A.	N.A.	N.A.
17	Standby power supply	Required	Provided	MR
18	Refuge Area.			
	Total area	N.A.	N.A.	N.A.
	Location	N.A.	N.A.	N.A.
19	Fire Control Room			
	Detector system panel	N.A.	N.A.	N.A.
	Flow switch panel	N.A.	N.A.	N.A.
	PA system panel	N.A.	N.A.	N.A.
	Batter backup	N.A.	N.A.	N.A.
	Building Floor Plans	N.A.	N.A.	N.A.
20	Special Fire Protection systems for	N.A.	N.A.	N.A.
	protection of special Risks, if any:			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the Rules the FSC issued vide Letter No- F.6/DFS/MS/GH/2014/NDZ/1286 Dated 17/10/14 renewal under Rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officers

Name

R.K.Yadav

Designation

ADO (LN)

DO (EAST) en leave DY CAO (DD2) M. CM.V- M. SCELL WITZ Son I-T Letter és put up for signature ful