FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No:F6/MS/DFS/School/2018/ 2668

Dated: / 0/12/2018

FIRE SAFETY CERTIFICATE

Certified that the building of DAV Public School, Located at Ashok Vihar, Phase- IV, Delhi.110052comprised of Ground + 03 Upper Floors(2nd Block Abandoned) owned and occupied by DAV Public School was issued FSC vide Letter No. F6/MS/DFS/08/2064 Dated 18/11/2018 The premises was re inspected by the officer concerned of this department on 16/11/2018 in the presence of Mr Ramesh Kumar (Estate Officer) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deem complied with the fire prevention and fire safety requirements in accordance DOE Circular 262–362 Dated 17-01-2005 and that the premises is fit for occupancy class "Educational" Group B with effect from 10/211 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Atul Garg) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Principal, DAV Public School, Located at Ashok Vihar, Phase-IV, Dehi.110052
- 2. Directorate of Education Old Secretariat Delhi 110054

Following fire safety directives must be adhered to:-

- 1. The small tin shed at terrace shall not be used for school activities.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement shall be used strictly as per building bye laws.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 9. 2nd Block shall not be used for school activities.

INSPECTION REPORT

1. Name & address of the building: DAV Public School, Located at Ashok Vihar, Phase-IV, Delhi.110052.

2. Type of Occupancy: Educational Two Blocks(1st Block of Ground + 3 Upper+ Tin shed above 2 or 3 rooms & 2nd Block Ground Floor only,) (Except Abandoned 2nd Block)

3. Type of Case

: Renewal

4. Details of previous NOC: F6/MS/DFS/school//2015/2064 Dated 18/11/2015

5. Fire Safety directives Letter No.: DOE Cr 262–362 Dated 17-01-2005

6. Date of inspection

: 16-11-2018

7. Name of the Inspecting Officer: ADO (WP)

Total Area = 1.5acre (6069.66 sqmt)

Covered Area = 4903.53 M^2

(all floor).

8. Name and designation of Officer

from the building side

:Mr. Ramesh (Estate Officer)

Class rooms = 55No. of students = 2600

9. Year of Construction

: 2005-06

10. Applicant's letter No.

: DAVPSAV/PH-IV/6927 dated 05-10-2018

S No	2	num standards on fire ntion and fire safety U/R	DOE Circu 262–362 Dated 17-0 2005		Provided at s	site	Remarks MR/NMR	
1.	Acces	s of building					1	
	•	Road width	Accessible		12m Provide	d	MR	
	•	Gate width	Accessible		4m Provided		MR	
	•	Width of internal road	NA		NA		NA	
2.	Number, width, Type & Arrangements of exits					'		
	a.	Number of staircases						
	•	Upper floors	2		Provided		MR	
	•	Basements	NA		NA		NA	
	b.	Width of staircases						
	•	Upper floors	2 X1.5m		2x136 cm	MR	(Being Old case)	
	•	Basements	NA NA		NA	NA	A	
	c.	Protection of exits						
	•	Fire check door	NA	NA 1			NA	
	•	Pressurization	NA 1		NA		NA	
	d.	No of continuous	NA		NA		NA	
		staircase to terrace	NA		NA		NA	
	e. Width Of Corridor f. Door Size	1x1 m	Prov	Provided(110 cm) the class Room Having		MR		
	1			less	than 45 stude	nts		

Compartmentation			
Fire check door	NA	NA	NA NA
		- Contraction	- A
shafts	IVA	INA	NA
 Fire Rating of shaft 	NA	NΔ	NA
door		1471	INA
	NA	NA	NA
	NA	NA	NA NA
			1111
		NA	NA
• Upper floors	NA	NA	NA
		Provided	MR
	_	Provided	MR
IS marking	ISI marked	Provided	MR
	2	Provided	MR
50310-040 04/044			
		Provided	MR
	5 mm	Provided	MR
Nozzle diameter			60 (60 HeV)
Automatic fire detection and ala	arming system		
		NA	NA
		NA	NA
Panel	NA	NA	NA
 Alternate source of power 	NA	NA	NA
 Hooters' Location 	NA	NA	NA
MOEFA	NA	- 2005 955	NA
Public Address System			
Automatic Sprinkler System		TTOVIGEG	MR
• Basements	NA	NA	NA
 Upper Floor 			NA NA
			NA
ceiling		1471	INA
Internal Hydrants:			
 Size of riser/down- 	100 mm	Provided	MR
		110,1404	IVIII
comer	2	Provided	MR
 Number of hydrants per 	2	Provided	MR
 Number of hydrants per floor 	2	v	
Number of hydrants per floorHose Box		Provided Provided	MR MR
 Number of hydrants per floor 		v	
 Number of hydrants per floor Hose Box Yard Hydrants 	2	Provided	MR
Number of hydrants per floorHose Box		v	
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke managements System Basements Upper floors Fire Extinguishers Total numbers Types IS marking First – Aid Hose Reels Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and ala Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System Automatic Sprinkler System Basements Upper Floor Sprinkler above false ceiling Internal Hydrants: 	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers NA Smoke managements System Basements Upper floors Total numbers Total numbers Is nos. Types Is marking First – Aid Hose Reels Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming system Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System Basements Upper Floor Sprinkler above false ceiling Internal Hydrants:	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers NA NA

P	umping Arrangements:		\			
	Ground Level	NA	INT	NA		
	Discharge of main	NA NA	NA	NA		
	pump	NA	NA	NA		
	Beau of main pamp	NA	NA	NA		
	Nullibel of man party	NA	NA	NA		
	Juckey barrip car par	NA	NA	NA		
		NA NA	NA	NA		
	Stallady I will I	NA	NA	NA		
	Dittiliae 1 2 man 1	INA	1,12			
	> Auto Staring/Manual	NA	NA	NA		
	stopping	IVA	1112			
	> Pump House Access	450 lpm&180	Provided	MR		
	• Terrace level		110/100			
	Discharge of pump	lpm	Provided	MR		
	> Head of the pump	40 m	Provided	MR		
	> Power supply	Required	Provided	MR		
	> Auto starting of pump	Required	11011404			
4.	Captive water Storage for fire fig	ghting:	30000 ltrs	NA		
1	 Under ground tank 	NA	30000 1015			
	capacity	NIA	NA	NA		
	Draw off connection	NA	NA NA	NA		
	Fire service inlet	NA	NA	NA		
	Access to tank	NA 5000 lituas	Provided(10000			
	 Overhead Tank 	5000 litres	ltrs)			
	capacity	D ind	Provided	MR		
15	Exit Signage	Required	TTOVIGEG			
16.	Provision of Lifts	NA	NA	NA		
	> Pressurization of Lift					
	Shaft	NA NA	NA	NA		
	Pressurization of lift		INA			
	lobby	274	NA	NA		
	Communication in lift	NA	NA NA	NA		
	Car	NA	INA	· · · · · · · · · · · · · · · · · · ·		
	Fireman's Grounding	7.7.4	NA	NA		
	Switch	NA	INA			
	> Lift Signage	NA	NA	NA		
17.		INA	7.47.7			
18	. Refuge Area	NIA	NA	NA		
	> Total area	NA	NA NA	NA		
	> Location	NA	14/1			
19	Fire control room					
	,	NA	NA	NA		
1	> Detector system panel	NA NA	NA	NA		
	> Flow Switch Panel		NA	NA		
	> PA System Panel	NA	NA	NA		
	> Battery backup	NA	NA NA	NA		
	Building Floor Plans	NA	INT			

20. Special Fire Protection	NA	NA	NA	
C Duetoction Ol		· huilding	were test checked as	nd
Systems for Protection or special Risks, if any; The fire protection system found functional at the time of	stems provided inspection.	in the building	, were	
		inimum standa	rds on fire prevention a	nd
fire safety as required to F6/DFS/MS/school/2015/2064	Dated 18-11-20	015 renewal ur	ider rule 35 of the De	
Note;-The small tin shed at block shall not be used for se	terrace (above chool activities.	2 or 3 class ro	oms) and 2 distant	
1/1/2 /1/1/8	5			
Signature of the Inspecting O	fficer			
Name Udai Vir Singh Designation ADO/WP				
19/10 pm	16/11/18			
Tytto W2/	, 527	111/08		
cto well fly	11111	-Albe	Lem &	mitemsh
1/130) -	Carl	- 12 wa	89+2 2 M
			+3, Pls	explu
		9	19 /	M
	1 0/00	110		28/11/11
00/W St	sold on n			28/11/1/
00/W St				
	give to	f lette	n le but ub	Just ble
	VXIN			12/12