GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 2662

FIRE SAFETY CERTIFICATE

Certified that the Karma Durga Guest House located at T-316, General Market, Pahar Ganj, New Delhi comprised of Ground + 05 Upper floor, Ground floor (Shops), 1st floor (02 guest rooms + Reception), 2nd floor (03 guest rooms), 3rd & 4th floor (Owners residence and 5th floor sealed, total 05 guest rooms owned/occupied by Karma Durga Guest House was granted **FSC** by this department No.F6/DFS/MS/GH/2015/NDZ/1918 dated 20/10/15. The premise was re-inspected by the officer concerned of this department on 26/11/18 in the presence of Mr. Karan (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 05 guest unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued --- 10/12/12--- at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service of m

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. 2. The Manager,

Karma Durga Guest House at T-316, General Market, Pahar Ganj, New Delhi. Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building Karma Durga Guest House at T-316, General

Market, Pahar Ganj, New Delhi Residential, Sub Division-A-1 2. Type of occupancy:-

Ground + 05 Upper floor, Ground floor (Shops), 1st floor (02 guest rooms + Reception), 2nd floor (03 guest rooms), 3rd & 4th floor (Owners residence and 5th floor sealed, total 05 guest rooms.

3. Type of case:-Renewal

No. F6/DFS/MS/EH/2015/NDZ/1918 dated 4. Details of previous FSC:-

20/10/15.

N/A 5. Fire safety directives No.-

26/11/18 6. Date of inspection:-

Sh. Manoj Kumar Sharma (ADO/CC) 7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Sh. Karan (Manager)

2008

4532/Addl. C.P./Lic. (H) dated 11/10/2018.

Old Case

				Old Case
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building			
>	1) Road width	N/A	05 Feet	N/A
	2) Gate width	N/A	N/A	N/A
	3) Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arra	angement of Ex	its	
	A. Number of staircases			
	1. Upper floors	01 Nos.	01 Nos.	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase		9 4 J 5	
	1. Upper floors	0.80 mtr.	0.90 mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits			
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	N/A	N/A	N/A
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	01 mtr.	01 mtr.	MR
3.	Compartmentation			
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System			
	1) Basements	30 ACPH	N/A	N/A
	2) Upper floors	12 ACPH	Natural	MR
5.	Fire Extinguishers		*	
	1) Total numbers	06 Nos.	06 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided	MR

	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel			
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 m	30 m	
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &	Alarming Sy	vstem	MR
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	N/A		N/A
10.	Automatic Sprinkler System	INA	N/A	N/A
	1) Basement	N/A	N/A	27/4
	2) Upper floors	N/A		N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	IN/A	N/A	N/A
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	77/4	
	2) Number of hydrants per	N/A	N/A	N/A
	floor	IN/A	N/A	N/A
	3) Hose box	N/A	N/A	27/4
12.	Yard Hydrants	14/21	IN/A	N/A
	1) Total number of hydrants	N/A	N/A	27/4
	2) Hose box	N/A	N/A N/A	N/A
3.	Pumping Arrangement	TVA	IN/A	N/A
	1) Ground level	N/A	DT/A	
	a) Discharge of main	N/A	N/A	N/A
	pump	IN/A	N/A	N/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	-
	stopping	1,171	IVA	N/A
	2) Terrace level			
	a) Discharge of pump	180 LPM	180 LPM	MD
	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required .	Provided	MR
	d) Auto starting of pump	Required	Provided	MR
1.	Captive Water Storage for Fir	e Fighting	Frovided	MR
		N/A	N/A	N/A
	\ D	N/A	NI/A	27/
		IN/A	N/A	N/A

	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	N/A
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures required under the rules the FSC issued vide F6/DFS/MS/EH/2015/NDZ/1918 dated 20/10/15 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation: - ADO (CC)

Dy. CFO (NDZ)

F.T. letter is port up for 879