## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 2673

Dated :----12/13

## **FIRE SAFETY CERTIFICATE**

Certified that the M/s Rama Inn located at 8539, Arakashan Road, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (Reception + 02 guest rooms + office), 1st floor (09 guest rooms), 2nd floor (09 guest rooms) and 3rd floor (06 guest rooms + staff room + staff kitchen), total 26 guest rooms owned occupied by M/s M/s Rama Inn was granted **FSC** by this department No.F6/DFS/MS/GH/2015/NDZ/2043 dated 13/11/15. The premises was re-inspected by the officer concerned of this department on 29/11/18 in the presence of Mr. Rahul (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 26 guest rooms only with effect from ------ for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued --1-2/12/18---at New Delhi by.

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- The Manager,
   M/s Rama Inn at 8539, Arakashan Road, Pahar Ganj, New Delhi.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTI	ONT	DEDO	>=		
HADIECII	VIV	KEP()	₹1		

1. Name & address of the building M/s Rama Inn at 8539, Arakashan Road,

Pahar Ganj, New Delhi 2. Type of occupancy:-Residential, Sub Division-A-1

Gr. + 03 Upper floors (total 26 Guest rooms) Ground floor (Reception + 02 guest rooms + office), 1<sup>st</sup> floor (09 guest rooms), 2<sup>nd</sup> floor (09 guest rooms) and 3<sup>rd</sup> floor (06 guest rooms + staff room + staff kitchen)

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/2015/NDZ/2043 dated 13/11/15.

5. Fire safety directives No.-N/A 6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

29/11/18

Sh. Manoj Kumar Sharma (ADO/CC)

Mr. Rahul (Manager)

1948

Nil date 30/10/19

	. Applicant's letter No:-	Nil date	30/10/18.	8
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	Old Case Remarks MR/NMR
1.	Access to Building			-
	1) Road width	N/A	12 mtr.	) AD
	2) Gate width	N/A	N/A	MR
	3) Width of internal road	N/A	71/4	N/A
2.	Number, Width Type & An	rrangement of	Evite	N/A
	11. I vulliber of staircases	gement of	EXILS	2 0
	1. Upper floors	01 Nos.	01 Nos.	
	2. Basements	N/A	N/A	MR
	B. Width of staircase	1071	IN/A	N/A
	1. Upper floors	0.80 mtr.	1.23 Mtr.	MR
	2. Basements	N/A	N/A	27/
	C. Protection of exits		IVA	N/A
	1. Fire check door	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous	N/A	N/A	N/A
	staircase to terrace		IV/A	N/A
	E. Width of corridor	N/A	N/A	21/4
	F. Door size	01 mtr.	01 mtr.	N/A
	Compartmentation		or mu.	MR
	1) Fire check door	N/A	N/A	
- 1	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
4	4) Water curtain	N/A	N/A N/A	N/A
4	5) Fire Dampers	N/A		N/A
	Smoke Management System	11/11	N/A	N/A
_1	) Basements	30 ACPH	N/A	
2	2) Upper floors	12 a/c per	37	N/A
		hour	Natural ]	MR

5.								
).	Fire Extinguishers							
	1) Total numbers		09 Nos.	_	09 Nos.		MR	
	2) Types		ABC & CO2	1	ABC & CO2		MR	
	3) ISI marking	F	Required	]	Provided		MR	
6.	First-Aid Hose Reel							
	1) Total number of eachfloor			01		MR		
	2) Length of hose reel hose		30 mtr.		30 mtr.	]	MR	
7	3) Nozzle diameter (		)5 mm		05 mm		MR	
7.	Automatic Fire Detection & Alarming System							
	1) Type of detectors		I/A N/A			N/A		
	2) Location of main panel N		I/A	-	V/A	1	V/A	
	3) Location of repeater panel	N	I/A	N/A		1	V/A	
	4) Alternate source of power	_	I/A	_	J/A	. 1	V/A	
0	5) Hooter's Location		N/A		N/A		N/A	
8.	MOEFA		/A	_	J/A	1	J/A	
9.	Public Address System	R	equired	P	rovided	N	⁄IR	
10.	Automatic Sprinkler System							
	1) Basement	_	/A	_	I/A	1	J/A	
	2) Upper floors		N/A		Ī/A	I	I/A	
	3) Sprinkler above false	N.	N/A		N/A		I/A	
11	ceiling							
11.	Internal Hydrants							
	1) Size of riser/down-comer	N.		-	N/A		/A	
	2) Number of hydrants per	N	/A	N	/A	N	/A	
	floor			- 2" 's				
12.			/A	N	/A	N	l/A	
4.	Yard Hydrants							
	1) Total number of hydrants 2) Hose box	N/		-	/A		/A	
3.		N/	A	N	/A	N	/A	
J	Pumping Arrangement				l d.	1.5	500	
	1) Ground level		N/A		N/A		N/A	
	a) Discharge of main		N/A		N/A		N/A	
	b) Head of main		27/4		27/4			
	b) Head of main pump		N/A N/A			N/A		
	c) Number of main pu	mp	N/A N/A			N/A		
	d) Jockey pump out pr	ut	N/A N/A			N/A		
	e) Jockey pump head f) Stand by pump out		N/A N/A			N/A		
	J T T o mop and		N/A N/A				N/A	
	g) Stand by pump head h) Auto starting/Manual		N/A N/A			N/A		
	8		N/A		N/A		N/A	
	stopping 2) Terrace level			_				
			207 1 707		225 1 D) 1		7 55	
	<ul><li>a) Discharge of pump</li><li>b) Head of pump</li></ul>		225 LPM				MR	
	c) Power supply		25 mtr.	-	25 mtr.		MR	
	d) Auto starting of pun	20	Required Required	+	Provided Provided		MR MR	
			K WILLIAM	- 1	LINOXIII dod		IN ALD	

14.	Captive Water Storage for 1	Fire Fighting		
	1) Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2,500 ltr.	2,500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	m for Protection	n of special	N/A

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/2043 dated 13/11/2015 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFONDZ

F.T. litter is put wp.