

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6/DFS/MS/2018/W2/272/

Dated 17 /12/18

## FIRE SAFETY CERTIFICATE

Certified that the Community Hall located at CSC/OCF-5, Sector - 13, Rohini, Delhi110085 comprised of ground and three upper floors owned/ occupied by Delhi Development
Authority have complied with the fire prevention and fire safety requirements in accordance
with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Fire
Service on 29.11.2018 in the presence of Mr. Suresh Dhankhar, E.E (Elec.) and that the
building / premises is fit for occupancy "Assembly" only with effect from

171118 for a period of 03 (Three) years in accordance with rule 36 unless renewed
under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions
under rule 38 of the Delhi Fire Service Rules, 2010.

## Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>WWW.dfs.Delhigovt.nic.in</u>
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

Issued on ...... at New Delhi by

Chief Fire Officer Ph-011-23414250

The

Copy to:-

The Executive Engineer (Elec.)
 D.D.A, Electrical Division No. IX
 DDA Zonal Office Building, Rohini, Delhi-110085.

## **INSPECTION REPORT**

Name & address of the building : Community Hall, CSC/OCF-5, Sector - 13 Rohini

Delhi. (G + 03 upper floors)

2 Type of Occupancy

:Assembly

3 Type of Case

:New Case

4 Details of previous NOC

: Nil

5 Fire Safety directives letter No

: F 6/DFS/MS/BP/2016/251 dated 06.10.2016.

6 Date of inspection

:29.11.2018

7 Name of the Inspecting Officers

:ADO (RN) / Rajesh Kumar

8 Name and designation of officers

from the building side

: Sh Suresh Dhankhar, EE( Elect.)

9. Year of Construction

: 2018

10. Applicant's letter No.

:F3(163)/ED-9/DDA/1053 Dated 11.10.2018

	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR		
1	Access to building					
	Road width	06m	13m (approx)	MR		
	Gate width	. 5m	5.0m	MR		
	Width of internal road	NA	NA	NA		
2	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases	02	02	MR		
	Upper Floors	02	13 Acres			
	Basements	NA	NA	NA		
	b. Width of staircases	,				
	Upper Floors	2.0m	02m each	MR		
	Basements	NA	NA	NA		
	c. Protection of exits					
	• Fire check door	NA	NA	NA		
	Pressurization	NA	NA	NA		
	d. No. of continuous staircases to terrace	01	01	MR		
	e. Width of Corridor	NA	NA	NA		
	f. Door Size	2.0m	Provided	MR		
3	Compartmentation.		4			

			2 111	MR
	Fire check door	Required	Provided	
	Galling of electrical shafts	Required	Provided	MR
	r: Dating of shaft door	Required	Provided	MR
	W. ton Curtain	NA	NA	NA
		NA	NA	NA
	Fire Dampers			
S	Smoke Management System.		NA NA	NA
	Basements	30 a/c per hour		MR
	<ul> <li>Upper floors</li> </ul>	12 a/c per hour	Natural Ventilated	IVIIC
	•			
5	Fire Extinguishers	10nos	16 nos	MR
	<ul> <li>Total numbers</li> </ul>	ABC & Co2	ABC/CO2	MR
	• Types		Yes	MR
	<ul> <li>ISI marking</li> </ul>	Yes	162	
6	First-Aid Hose Reels.		01	MR
·	Total numbers on each floor	01		MR
	<ul> <li>Length of hose reel hose</li> </ul>	30m	30m	
	a La diameter	5mm	5mm	MR
7	Automatic fire detection and alarming syst	Required	Provided	MR
	<ul> <li>Type of detectors</li> </ul>	GF	Provided	MR
	<ul> <li>Location of Main Panel</li> </ul>	Required	Provided	MR
	<ul> <li>Location of Repeater Panel</li> </ul>	Required	Provided	MR
	Alternate source of power	NA	NA	NA
	Hooters' Location			MR
		Required	Provided	NA NA
8	MOEFA Public Address System.	NA	NA	
9	Automatic Sprinkler System.			
10		NA	NA	NA
	Basement	NA	NA	NA
	Upper Floor	•	NA	NA
	<ul> <li>Sprinkler above false ceiling</li> </ul>	NA	IVA	
11	Internal Hydrants	21	.01provided	MR
1 1	Size of riser/down-comer	01	01	MR
	<ul> <li>Number of hydrants per floor</li> </ul>	01	NA	NA
	Hose Box	NA	INA	
12	Yard Hydrants.			
12		02	02	MR
	Total number of hydrants	02		

	• F	Hose Box	02	02	MR	
F		Arrangements.	· ·			
		Ground Level				
		Carlin Dump	2280 Lpm	2280 lpm	MR	
			70 mtr	70m	MR	
		Head of Main pump	lnos	Inos	MR	
		Number of main pumps	180 LPM	180 LPM	MR	
		> Jockey Pump out put	70 mtr	70m	M/R	
		Jockey pump head		2280 lpm	MR	
		Standby Pump out put	2280LPM	2280 Ipili	MD	
		Standby Pump Head	70 mtr	70m	MR	
		<ul><li>Auto Starting/ Manual stopping</li><li>Pump House Access</li></ul>	Required	Provided	MR	
		Terrace level		D. dad	MR	
	and the second	Discharge of pump	450lpm	Provided	MR	
		> Head of the pump	40m	40m		
		> Power Supply	Required	Provided	MR	
		> Auto Starting of pump	Required	Provided	MR	
1.4	Captive Water Storage for fire fighting.					
14	Сарич		50,000 ltr	50,000 ltr.	MR	
	•	Underground tank capacity		NA	NA	
	>	Draw-off connection	NA		NA	
	>	Fire service inlet	NA	NA	NA	
	>	Access to tank	NA	NA	8	
	•	Overhead Tank capacity	5000 ltrs	5,000 ltrs	MR	
15	Exit S	ignage.	Required	Provided	MR	
16	27.10					
			Required	Provided	MR	
	•	Pressurization of Lift Shaft	N/A	N/A	N/A	
	•	Pressurization of Lift lobby		NA	NA	
	•	Communication In lift Car	NA			
	•	Fireman's Grounding Switch	NA	NA	NA	
	•	Lift Signage	NA	NA	NA	
		dhy power supply	Required	Provided DG Set	MR	
17	Stan	dby power supply		x x		
18	Refu	uge Area.			7	

	1			
	Total Area	N/A	N/A	N/A
	Location	N/A	N/A	N/A
19	Fire Control Room			
	Detector System Panel	N/A	N/A	N/A
	<ul> <li>Flow Switch Panel</li> <li>PA System Panel</li> <li>Batter backup</li> <li>Building Floor Plans</li> </ul>	N/A	N/A	N/A
		N/A	N/A	N/A
		N/A	N/A	· N/A
		N/A	N/A	N/A
20	Special Fire Protection Systems for Protection of special Risks, if any:	NA	NA	NA

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view of satisfactory compliance of the minimum standards on fire prevention and fire safety required under the rules and fire safety guidelines issued vide letter of even no. 251 dated 06.10.2016, it is recommended to issue Fire Safety Certificate under rule 2010.

> Signature of the Inspecting Officer Name: - Rajesh Kumar

Designation:- ADO/RN

As approved, f.T. letter in Joutup for your signature pl.