GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 269 7

Dated :-- 19 12 18

FIRE SAFETY CERTIFICATE

Certified that the M/s Natraj Please Guest House located at 1665 & 1750, Chuna Mandi, Pahar Ganj, New Delhi comprised of Basement + Ground + 04 Upper floors, Basement (Storage), Ground floor (Reception + 03 guest rooms + 01 office 01 staff kitchen), 1st floor to 3rd floor (10 guest rooms at each floor) and 4th floor (04 guest rooms), total department granted **FSC** by this was 37 No.F6/DFS/MS/GH/2016/NDZ/708 dated 06/05/16. The premises was re-inspected by the officer concerned of this department on 02/12/18 in the presence of Sh. Ashish (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 37 with rule 36 miless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Jessey - 14/12/18 at New Delhi by.

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

2. The Manager, M/s Natraj Please Guest House at 1665 & 1750, Chuna Mandi, Pahar Ganj, New Delhi

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This the safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The content occupier shall submit a declaration every year in form 'K' provided in the first sched and Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The regions of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an energency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its explanation.

	INSF	PECTION REPO	ORT					
1.	Name & address of the building							
		New Delh	i					
2.	Type of occupancy:-	Residential, Sub Division-A-1						
		B+Gr. + 04 Upper floors (total 37 Guest rooms) Basement (Storage), Ground floor (Reception + 03 guest rooms + 01 office 01 staff kitchen), 1 st floor to 3 rd floor (10 guest rooms at each floor) and 4 th floor (04 guest rooms)						
3.	Type of case:-	Renewal						
	Details of previous FSC:-	No. F6/DFS/MS/GH/2013/NDZ/708 dated						
		06/05/16.						
5.	Fire safety directives No N/A							
	6. Date of inspection:- 02/12/18							
	Name of the inspecting officer	:- Sh. Manoj	Kumar Sharma (AI	OO/CC)				
	Name & designation of officer	-						
From the	he building side:-	Sh. Ashish	(Manager)					
9.	Year of construction:-	1976						
10.	Applicant's letter No:-	4664/Addl	. C.P/Lic. (H) dated	15/10/2018. Old Case				
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	Remarks MR/NMR				
1.	Access to Building		N					
	1) Road width	N/A	12 mtr.	MR				
	2) Gate width	N/A	N/A	N/A				
	3)Width of internal road	N/A	N/A	N/A				
2.	Number, Width Type & Arrangement of Exits							
	A. Number of staircases							
	1. Upper floors	01 Nos.	01 Nos.	MR				
	2. Basements	01 Nos.	01 Nos.	MR				
	B. Width of staircase							
	1. Upper floors	0.80 mtr.	1.30 Mtr.	MR				
	2. Basements	0.80 mtr.	1.30 Mtr.	MR				
	C. Protection of exits		# 7 T	W				
	1. Fire check door	N/A	N/A	N/A				
	2. Pressurization	N/A	N/A	N/A				
	D. No. of continuous staircase to terrace	N/A	N/A	N/A				
	To The late of the	DT/A	DT/A	NI/A				

N/A

N/A

N/A

N/A

N/A

N/A

30 ACPH

12 ACPH

1 mtr.

N/A

N/A

N/A

N/A

N/A

N/A

Natural

Exhaust fan

1 mtr.

E. Width of corridor

Compartmentation

2) Sealing of electrical shafts

Smoke Management System

3) Fire rating of shaft door

1) Fire check door

4) Water curtain

5) Fire Dampers

1) Basements

2) Upper floors

F. Door size

3.

4.

N/A

MR

N/A

N/A

N/A

N/A

N/A

MR

MR

	Fire Extinguishers 1) Total numbers	12 Nos	,	10.3-			
	2) Types	ABC &		12 Nos.		MR	
	3) ISI marking	Require	CO2	ABC & C	02	MR	
6.	First-Aid Hose Reel		a	Provided		MR	
	1) Total number of eachflo	or 01					
	2) Length of hose reel hose			01		MR	
	3) Nozzle diameter	0.5		30 mtr.		MR	
7.	Automatic Fire Detection	& Alami	~	05 mm		MR	
	Automatic Fire Detection & Alarming System 1) Type of detectors N/A N/A						
	2) Location of main panel	DT/A		N/A		N/A	
	3) Location of repeater page	1 DILA		N/A		N/A	
	4) Alternate source of nove	r N/A		N/A		N/A	
	5) Hooter's Location	N/A		N/A		N/A	
8.	MOEFA			N/A		N/A	
9.	Public Address System	Required		Provided		MR	
10.	Automatic Sprinkler System	Required]	Provided	ITA III	MR	
	1) Basement						
	2) Upper floors	Required		Provided		MR	
	3) Sprinkler above false	N/A	N	V/A		N/A	
	ceiling	N/A	N	√A		N/A	
1.	Internal Hydrants					- 1/2 1	
07-	1) Size of riser/down-comer	77/4					
	2) Number of hydrants per	N/A		I/A		N/A	
	floor	N/A	N	N/A		N/A	
	3) Hose box	NT/A				- 07.1	
2.	Yard Hydrants	N/A	N/	/A		N/A	
	1) Total number of hydrants	NI/A					
	2) Hose box	N/A N/A	N/		1	N/A	
3.	Pumping Arrangement	IN/A	N/	A	1	V/A	
	1) Ground level	77/4	-	is:		25	
	a) Discharge of main	N/A	N	/A		N/A	
	pump	N/A	N.	/A		N/A	
İ	b) Head of main pump	27/				- 112 1	
	c) Number of main pump	N/A	N/	'A	1	N/A	
Ţ	d) Jockey pump out put		N/	- 1		V/A	
T	e) Jockey pump head	N/A	N/	A		V/A	
r	f) Stand by nump output	N/A	N/			V/A	
	f) Stand by pump output g) Stand by pump head	N/A	N/A			J/A	
	h) Auto starting/Manual	N/A	N/A	A ,		I/A	
	stopping	N/A	N/A			I/A	
	2) Terrace level			(8)		77 X	
	a) Discharge of pump						
	b) Head of pump	450 LPM*	450	LPM	M	IR	
	c) Power supply	40 mtr.		0		R	
- 1	-, I ower supply	Required	Prox	Provided M			
	d) Auto starting of pump	Required	1101	rided		K	

14.	Captive Water Storage for Fire Fighting					
	1) Under ground tank capacity	N/A	N/A	N/A		
	a) Draw-off connection	N/A	N/A	N/A		
	b) Fire service inlet	N/A	N/A	N/A		
1	c) Access to tank	N/A	N/A	N/A		
4.5	d) Over head tank capacity	5000 ltr.	5000 ltr.	MR		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.	*		IVIIC		
	a) Pressurization of lift shaft	N/A	N/A	N/A		
	b) Pressurization of lift lobby	N/A	N/A	N/A		
	c) Communication in lift car	N/A	N/A	N/A		
	d) Fireman's switch	N/A	N/A	N/A		
17.	e) Lift signage	N/A	N/A	N/A		
	Stand by Power Supply	Required	Provided	MR		
18.	Refuge Area	N/A	N/A	N/A		
	Total area location	N/A	N/A	N/A		
19.	Fire Control Room	N/A	N/A	N/A		
	a) Detector system panel	N/A	N/A	N/A		
	b) Flow switch panel	N/A	N/A	N/A		
	c) PA system panel	N/A	N/A	N/A		
	d) Battery backup	N/A	N/A	N/A		
	e) Building floor plan	N/A	N/A	N/A		
0.	Special Fire Protection System Risk, if any: One ABC fire extingu	ion of special	MR			

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2016/NDZ/708 dated 06/05/2016 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

> Signature of the Inspecting Officer MUS

Name: - M.K. Sharma Designation: - ADO (CC)

Dy. CFO/NDZ

of miscell FTD.

WITIZ