GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/School/2018/SZ/ 27/3

Dated: 14/11/18

FIRE SAFETY CERTIFICATE

Certified that New Mother Saraswati School located at G-657, Sangam Vihar, New Delhi-110062 comprised of ground plus two upper floors owned/occupied by Saraswati Education Society was granted Fire Safety Certificate by this department vide letter No. F.6/MS/DFS/School/2015/1826 dated 09/10/2015. The premises was re-inspected by officer concerned of this department on 01/12/2018 in presence of Mr. Madan Mohan Sharma (Incharge) and observed that the said School building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class "Educational Building" Group-B, with effect from the date of issue of this certificate for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 19/12/18 at New Delhi by

(Vipin Kental)
Chief Fire Officer

Copy to: -

- 1. The Principal, New Mother Saraswati School, G-657, Sangam Vihar, New Delhi-110062
- 2. Directorate of Education, South MCD, Civic Centre, Minto Road, New Delhi-110002

Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

		N REPORT	ti Cahaal at G 657		
1	Name & Address of the Building	New Mother Saraswati School at G-657,			
0		Sangam Vihar, New Delhi-110062			
2	Type of Occupancy	Educational, Group-B (School)			
3	Building Comprised of	Ground plus two upper floors			
4	Type of Case	Renewal F.6/MS/DFS/School/2015/1826 dated 09/10/2015.			
5	Details of Previous NOC		01/2015/1826 dated 09/	10/2013.	
6	Fire Safety Directives Letter No	Nil			
7	Date of Inspection	01/10/2018	(0.1)		
8	Name of the Inspecting Officers	Mehmood, ADO (SJ)			
9	Name & Designation of Officers from the building side	Mr. Madan Mohan Sharma (Manager)			
10	Year of construction	2000			
11	Applicant letter No.	Nil dated 11/09/2018			
	Minimum standards on Fire Prevention	Old NOC	Provided at Site	Remarks	
S. No.	and Fire Safety U/R 33	Requirement		MR/NMR	
1	Access to Building.				
1		6 mtr	5.20 mtr	MR (old case)	
	San Germanian Company	-NA-	-NA-	-NA-	
	Gate width	0.00	-NA-	-NA-	
	Width of internal road	-NA-	-INA-	1171	
2	Number, width, type & arrangement of ex	kits.			
	a) Number of Staircase		_ 11.1	MD	
	Upper floors.	02 Nos	Provided	MR	
	Basement floor.	-NA-	-NA-	-NA-	
	b) Width of Staircase > Upper floors	1.50 mtr	1.53m,1.16m	MR (old case	
		-NA-	-NA-	-NA-	
	> Basement floor	-IVA-	1111		
	c) Protection of exits	DIA	-NA-	-NA-	
	> Fire check door	-NA-		-NA-	
	Pressurization	-NA-	-NA-		
	d) No. of continuous staircase to terrace	01 No	Provided	MR	
	e) Width of corridor	Required	1.45m	MR	
	f) Door size	1 mtr	Provided	MR	
3	Compartmentation.				
3	Fire check door.	-NA-	-NA-	-NA-	
	 Sealing of electrical shafts. 	-NA-	-NA-	-NA-	
	• Fire rating of shaft door.	-NA-	-NA-	-NA-	
	Water curtain	-NA-	-NA-	-NA-	
	• Fire dampers.	-NA-	-NA-	-NA-	
4					
4.	Smoke Management system.	30 ACPH	-NA-	-NA-	
	Basement	12 ACPH	Natural Ventilation	MR	
	Upper floors	12 ACFTI	Tratulal Volitiation	1711	
5.	Fire Extinguishers.		10 N	MR	
	Total numbers	Required	12 Nos		
	• Types	ABC/CO2	ABC & Co2	MR	
	ISI Marking	ISI mark	Provided	MR	
-	First Aid Hose Reels.	*		38	
6.		01 Nos	Provided	MR	
	Total numbers on each floor.		Provided	MR	
	 Length of hose-reel hose. 	30m			
	Nozzle Diameter	5mm	Provided	MR	

7	Automatic fire detection & alarming system.			
	Type of detectors	-NA-	-NA-	-NA-
	Location of Main Panel	-NA-	-NA-	-NA-
	Location of Repeater Panel	-NA-	-NA-	-NA-
	Alternate source of power	-NA-	-NA-	-NA-
	Hooter's location	-NA-	-NA-	-NA-
8.	MOEFA	Required	Provided	MR
9.	Public Address System	-NA-	-NA-	-NA-
10.	Automatic Sprinkler System			
	Basement	-NA-	-NA-	-NA-
	Upper floors	-NA-	-NA-	-NA-
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11.	Internal Hydrants.	1111	A 14 A	1111
111	Size of Riser/Down-comer	-NA-	-NA-	-NA-
	Number of Hydrant per floor	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
12.	Yard Hydrants.	1117	TALK	1121
14.	Total number of hydrants.	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13.	Pumping arrangements.	-14/4-	-1477-	-1471-
10.	Ground Level			
	> Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	> Jockey Pump output.	-NA-	-NA-	-NA-
	> Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	➤ Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
	Terrace Level	1111	1471	1171
	Discharge of pump.	450LPM	Provided	MR
	Head of pump.	35 mtr	Provided	MR
	➤ Power supply.	Required	Provided	MR
	➤ Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.			1
	Underground tank capacity.	-NA-	-NA-	-NA-
	> Draw-off connection.	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
	Overhead tank capacity.	10,000 Ltr	Provided	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	Communication in lift car.	-NA-	-NA-	-NA-
	Fireman's switch.	-NA-	-NA-	-NA-
	Lift signage.	-NA-	-NA-	-NA-
	Standby Power Supply	-NA-	-NA-	-NA-
17.				
17. 18.				
	Refuge Area • Total area	-NA-	-NA-	-NA-

19	Fire Control Room.			274
17	D to to more and	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
	• Flow switch panel.	-NA-	-NA-	-NA-
	PA system panel.	-NA-	-NA-	-NA-
	Battery backup.	-NA-	-NA-	-NA-
	 Building floor plan. Special Fire Protection System for the 			-NA-

The fire protection system provided in the building / premises were test checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No.F.6/MS/DFS/School/2015/1826 dated 09/10/2015, renewal under rule 37 of the Delhi Fire Service Rules 2010, is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting

Name: Mehmood Design: ADO (SJ)

Miscell Kyper for Signature Please