GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

Fax No. 011-23412593, Ph. 011-23412225

No. F.6/DFS/MS/School/2018/SZ/ 2719

Dated: ...! 12/18

FIRE SAFETY CERTIFICATE

Certified that the St. Mary's Public School located at 530, Durga Vihar, Devli, New Delhi110062, comprised of ground plus two upper floors only was issued FSC by this department vide
letter No. F.6/MS/DFS/School/2016/SZ/118 dated 18/01/2016. The said premise was re-inspected by
officer concerned of this department on 26/11/2018 in the presence of Mr. James K.C. (Principal) and
observed that the school building have deemed complied with the fire prevention and fire safety
requirements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and that the building is fit
for occupancy class "Educational Building" Group-B, with effect from the date of issue of this
certificate for period of Three years in accordance with DOE circular subject to compliance of the
conditions mentioned below.

Issued 14/12/18 at New Delhi by

(Vipin Kental)
Chief Fire Officer

Copy to: -

- 1. The Principal, St. Mary's Public School, 530, Durga Vihar, Devli, New Delhi-110062
- 2. Directorate of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054

Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

		TION REPORT	chool,530,Durga Vih	ar,		
1 N	Name & Address of the Building	St. Mary's Public S	10067	7		
1		Devli, New Delhi-1	7(0.11)			
2	Type of Occupancy	Educational, Group-	3 (School)			
3 I	Building Comprised of		Ground plus Two Upper floors			
3 1	Type of Case	Renewal	Renewal 118/01/2016			
	Details of Previous NOC	F.6/MS/DFS/School/	F.6/MS/DFS/School/2016/SZ/118 dated 18/01/2016			
	Fire Safety Directives Letter No	Nil				
6	Date of Inspection	26/11/2018				
7	Name of the Inspecting Officers	Mehmood, ADO (SJ	Mehmood, ADO (SJ)			
8	Name & Designation of Officers	Mr. James K C (Prin	Mr. James K C (Principal)			
9	from the building side					
	Year of construction	2005				
10	Applicant letter No.		Nil dated Nil Provided at Site Remarks			
	Minimum standards on Fire Prevention	As Per Old NOC	I I U VICE CLI CLI	MR/NMR		
. No.	and Fire Safety U/R 33			IVIN/IVIIV		
	and Fire Salety O'N 30			MR(Old		
1	Access to Building.	6 mtr	5.70 m			
	Road width			Case) MR		
	C-to width	3.5m	3.5m			
	Gate widthWidth of internal road	-NA-	-NA-	-NA-		
	• Width of internal road	f exits.				
2	Number, width, type & arrangement of) (D		
	a) Number of Staircase	02 No's	02No's	MR		
	> Upper floors.	-NA-	-NA-	-NA-		
	Basement floor.					
	b) Width of Staircase			MR (Ol		
	> Upper floors	1.50m	1.90m & 0.85m	Case)		
		-NA-	-NA-	-NA-		
	Basement floor	-NA-	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
	c) Protection of exits	NIA	-NA-	-NA-		
	Fire check door	-NA-	-NA-	-NA-		
	Pressurization	-NA-		MR		
	a di satainage to terra	ace 01 No	Provided	MR		
	, c don	1.5m	Provided			
	e) Width of corridor	1 m	Provided	MR		
	f) Door size			1 N. A		
3	Compartmentation.	-NA-	-NA-	-NA-		
	• Fire check door.	-NA-	-NA-	-NA-		
	Sealing of electrical shafts.	-NA-	-NA-	-NA-		
	• Fire rating of shaft door.	-NA-	-NA-	-NA-		
	Water curtain	-NA-	-NA-	-NA-		
	• Fire dampers.					
4.	Smoke Management system.	30 ACPH	-NA-	-NA-		
	Basement	12 ACPH	-NA-	-NA-		
	Upper floors	12 ACITI				
5.	Fire Extinguishers.	15 Nos	15 Nos	MR		
J.	Total numbers	ABC / CO2	ABC & Co2	MR		
1	• Types		Provided	MR		
	1 4 5 6 3	ISI marked	TTOVICCE			
×						
	ISI Marking	1 2	Al nes et each floo	r MR		
6.	ISI Marking First Aid Hose Reels.	01 nos	01 nos at each floo			
6.	ISI Marking	01 nos 30m	01 nos at each floo 30m	r MR MR MR		

7.	Automatic five detection			
7 •	Automatic fire detection & alarming system			
	Type of detectors Location of Main Parall	-NA-	-NA-	-NA
	Docation of Main Panel	-NA-	-NA-	-NA
	200 Repeater Panel	-NA-	-NA-	-NA
	Alternate source of power	-NA-	-NA-	-NA
8.	Hooter's location	-NA-	-NA-	-NA
	MOEFA	-NA-	-NA-	
9.	Public Address System	-NA-	-NA-	-NA
10.	Automatic Sprinkler System		-IVA-	-NA
	• Basement	-NA-	-NA-	NIA
	• Upper floors	-NA-	-NA-	-NA
	Sprinkler above false ceiling	-NA-	-NA-	-NA
11.	Internal Hydrants.		-IVA-	-NA-
	Size of Riser/Down-comer	-NA-	D.T.A.	
	 Number of Hydrant per floor 	-NA-	-NA-	-NA-
	Hose box.		-NA-	-NA-
12.	Yard Hydrants.	-NA-	-NA-	-NA-
	• Total number of hydrants.	27.4		
	 Hose box. 	-NA-	-NA-	-NA-
13.	Pumping arrangements.	-NA-	-NA-	-NA-
-	• Ground Level			
F	Discharge of main pump.			
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.	-NA-	-NA-	-NA-
	Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting / Manual Stopping.	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
-		-NA-	-NA-	-NA-
-	Terrace Level		. 11.1	-IVA-
	Discharge of pump.	450 LPM	450 LPM	MD
	Head of pump.	40m	40m	MR
	Power supply.	Required	Provided	MR
4	Auto starting of pump.	Required	Provided	MR
1. (Captive water storage for fire fighting.		TTOVIDED	MR
	 Underground tank capacity. 	-NA-	-NA-	T A
	Draw-off connection.	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
,	 Overhead tank capacity. 	10,000liter		-NA-
	xit Signage.	Required	10,000 liter	MR
. P	rovision of Lifts.	- toquirou	Provided	MR
	 Pressurization of lift shaft. 	-NA-	NIA	
	 Pressurization of lift lobby. 	-NA-	-NA-	-NA-
	• Communication in lift car.	-NA-	-NA-	-NA-
	• Fireman's switch.	-NA-	-NA-	-NA-
	• Lift signage.		-NA-	-NA-
St	andby Power Supply	-NA-	-NA-	-NA-
	- Salphy	-NA-	-NA-	-NA-

				The second secon
18.	Refuge Area	-NA-	-NA-	-NA-
	• Total area	-NA-	-NA-	-NA-
19.	• Location Fire Control Room.	N.A.	-NA-	-NA-
17.	 Detector system panel. Flow switch panel. PA system panel. Battery backup. 	-NA- -NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
20.	Building floor plan. Special Fire Protection System for the	-NA-	-NA-	-NA-
20.	Protection of special Risk, if any.	remises were checke	d / operated at rand	lom and four

The Fire protection systems provided in the premises were checked / operated at random and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rule, FSC issued vide letter No. F.6/MS/DFS/School/2016/SZ/118 dated 18/01/2016, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Mehmood Design: ADO (SJ)

DO (8D)

Quilarh

U/12/18

Quick(52)

R/C PO (62)

R/C PO (62)

Left of

Pela 17/10 SI

Cho (Sy) M. scell

A. G. H. Jelle Ver up for

Jamaret 11/12/18 Am Cos

croup)

Miscell Wells