GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/School/2018/SZ/ 2752

Dated: 28.11.21.18

FIRE SAFETY CERTIFICATE

Certified that the DPS International located at P-37,Sector-VI, Pushp Vihar, M.B. Road Saket, New Delhi-110017, having three blocks, A-Blocks: B+G+3, B-Block: B+G+1 (Audi at 1st Floor of B-Block) and C-Block: B+G+2 (A & B blocks are interconnected upto 1st floor and C block interconnect with A block at first floor) was granted NOC by this department vide letter No. F6/MS/DFS/2003/1428 dated 03/07/2003 (school) and F6/MS/DFS/2004/670 dated 26/03/2004 (auditorium). The premises was re-inspected by officer concerned of this department on 01/12/2018 in presence of Mr. G.P. Sharma (Admin) and observed that the said School building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class "Educational Building" Group-B, with effect from the date of issue of this certificate for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on _____ at New Delhi by

(Vipin Kental) Chief Fire Officer Ph: 011-23412225

Copy to: -

- 1. Principal, DPS International, P-37, Sec-VI, Pushp Vihar, M.B. Road, Saket, New Delhi-17
- 2. Directorate of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054

Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL- 2016), if any.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

	INSPEC	TION REPOR	T				
1	Name & Address of the Building	DPS International, P-37, Sector-VI, Pushp Vihar					
		M.B. Road, Saket, New Delhi-110017					
2	Type of Occupancy	Educational	Educational, Group—B (School)				
3	Building Comprised of	School has three blocks. A-Bk: B+G+3, B-Bk: B+G+1					
		(Audi at FF of	B-Bk	and C-RV. R+C+02 (A	0-D D11		
		micronnected	upto	1 st Floor & C Bk intercor	nected with		
4	Type of Case	Block at 1 floor)					
5	Details of Previous NOC	Renewal					
	Betails of Flevious NOC	F.6/MS/DFS/2003/1498 dated 03/07/2003 (School)					
6	Fire Safety Directives Letter No	F.6/MS/DFS/2004/670 dated 26/03/2004 (Auditorium					
7	Date of Inspection	F.6/DFS/MS/BP/2002/1105 dated 09/07/2002					
8	Name of the Inspecting Officers		01/12/2018				
9	Name & Designation of Officers	Mehmood, A	DO (S	SJ)			
	from the building side	Mr. G.P. Shar	rma (A	Admin)	4		
10	Year of construction						
11	Applicant letter No.	2002					
S. No.	Minimum standards on Fire Prevention	DPSI/Estate/0	DPSI/Estate/0086 dated 26/10/2018				
	and Fire Safety U/R 33			Provided at Site	Remarks		
1	Access to Building.	Requireme	nt		MR/NMI		
	Road width						
	Gate width	6 mtr		10 mtr	MR		
	Width of internal road	5 mtr		Provided	MR		
2	Number width to a	-NA-		-NA-	-NA-		
	Number, width, type & arrangement of a) Number of Staircase	exits.					
	> Upper floors.						
	opper moors.	06 Nos		Provided	MR		
	,	(A&B Bk: 3 Nos GF to Terrace + 01 FF to Terrace & 02 in C Bk)		(A &B Bk: 3 Nos GF to			
				Terrace + 01 FF to			
	g 31	A&B Bk: 06 No		Terrace & 02 in C Bk	1		
	Basement floor.	C Bk: 02 Nos	OS	A&B Block- 06 Nos	MR		
	b) Width of Staircase	C DR. 02 140S	Bk: 02 Nos C Block- 02 No				
	> Upper floors	1.5	A 0- D	DI 140 105 105			
		1.5 mtr A&I		B Bk: 1.40m, 1.85m, 1.85m n, C Block: 1.40m each	MR		
	➤ Basement floor	1.5 mtr		Bk. 1.40m x 3, 1.20m, 1m	(old case)		
		1.5 IIII	and 0.90m, C block-1.40m x 2		MR (old case)		
	c) Protection of exits				(ord case)		
	Fire check door	Required		Provided	MR		
	Pressurization	-NA-		-NA-			
	d) No. of continuous staircase to terrace	04 No			-NA-		
	e) Width of corridor	1.5m		Provided	MR		
	f) Door size	Class rooms-1	m	Provided	MR		
		Audi- 1.50m		Class room-1m Audi-1.60m, 2.05m &	MR		
2		1100111		2.05m			
3	Compartmentation.			2.00111	-		
	• Fire check door.	Required		Provided	MR		
	 Sealing of electrical shafts. 	-NA-		-NA-	447 3 2 3 1 7 4 5 5		
	 Fire rating of shaft door. 	-NA-		-NA-	-NA-		
	Water curtain	-NA-		-NA-	-NA-		
	 Fire dampers. 	-NA-		-NA-	-NA-		
4	Smoke Management system.	- 14 1		-1 AV-	-NA-		
	Basement	30 ACPH		Exhaust Fan	MD		
	Upper floors	12 ACPH			MR		
		12 ACFI		-NA-	-NA-		

_				
5	Fire Extinguishers.			
	 Total numbers 	Required	11427	
	 Types 	ABC/CO2	114 Nos	MF
	ISI Marking		ABC & Co	MF
6	First Aid Hose Reels.	ISI mark	Provided	MF
	Total numbers on each floor.	107771		
	numbers on each moor.	A&B Bk-04 nos.	A&B Bk-04 nos.	MR
		C Bk-02 nos.	C block-02 nos.	
	 Length of hose-reel hose. 	Audi-02 nos.	Audi-02 nos.	
	Nozzle Diameter	30m	30m	MR
7	Automatic fire detection & alarming	5mm	5mm	MR
	Type of detectors			
	Location of Main Panel	Reqd. in basement	Smoke & Heat	MR
	Location of Repeater Panel	-NA-	-NA-	-NA
	Alternate source of power	-NA-	Ground floor	-NA
	Hooter's location	-NA-	-NA-	-NA
8	MOEFA	-NA-	-NA-	-NA
9		Reqd. in Audi	Provided	
10	Public Address System	-NA-	Provided	MR
10	Automatic Sprinkler System		1 TOVIDEU	-NA
	• Basement	Required	Provided	1.00
	 Upper floors 	-NA-	-NA-	MR
	 Sprinkler above false ceiling 	-NA-		-NA
11	Internal Hydrants.	1471	Provided	-NA
	 Size of Riser/Down-comer 	100mm	D 11.1	
	G G	A&B block-04 nos.	Provided	MR
	 Number of Hydrant per floor 	C block-02 nos.	A&B block-04 nos.	
		Auditorium-02 nos.	C block-02 nos.	MR
		A&B block-04 nos.	Auditorium-02 nos. A&B block-04 nos.	
	 Hose box. 	C block-02 nos.	C block-02 nos.	
10		Auditorium-02 nos.	Auditorium-02 nos.	MR
12	Yard Hydrants.	V 100.	raditorium-02 nos.	
	 Total number of hydrants. 	-NA-	04 Nos	214
	 Hose box. 	-NA-	04 Nos	-NA-
13	Pumping arrangements.		04 1108	-NA-
-	 Ground Level 			
	Discharge of main pump.	1620 LPM	2280 LPM	1.00
	Head of main pump.	50m	1	MR
	Number of main pumps.	One	50m	MR
-	Jockey Pump output	One	Provided	MD
	Jockey Pump output.	180 I DM	100 1 73 7	MR
	anipoutput.	180 LPM	180 LPM	MR
	Jockey Pump head	50m	50m	MR MR
	Jockey Pump headStandby Pump output.	50m 1620 LPM	50m 2280 LPM	MR
	 Jockey Pump head Standby Pump output. Standby Pump head. 	50m 1620 LPM 50m	50m 2280 LPM 50m	MR MR
	 Jockey Pump head Standby Pump output. Standby Pump head. Auto Starting/Manual 	50m 1620 LPM	50m 2280 LPM	MR MR MR
	 Jockey Pump head Standby Pump output. Standby Pump head. Auto Starting/Manual Stopping. 	50m 1620 LPM 50m Required	50m 2280 LPM 50m Provided	MR MR MR MR MR
	 Jockey Pump head Standby Pump output. Standby Pump head. Auto Starting/Manual Stopping. Pump house access. 	50m 1620 LPM 50m	50m 2280 LPM 50m	MR MR MR MR
	 Jockey Pump head Standby Pump output. Standby Pump head. Auto Starting/Manual Stopping. Pump house access. Terrace Level 	50m 1620 LPM 50m Required Required	50m 2280 LPM 50m Provided Provided	MR MR MR MR MR
	 Jockey Pump head Standby Pump output. Standby Pump head. Auto Starting/Manual Stopping. Pump house access. Terrace Level Discharge of pump. 	50m 1620 LPM 50m Required Required A&B & C Bk	50m 2280 LPM 50m Provided Provided	MR MR MR MR MR
	 Jockey Pump head Standby Pump output. Standby Pump head. Auto Starting/Manual Stopping. Pump house access. Terrace Level Discharge of pump. Head of pump. 	50m 1620 LPM 50m Required Required A&B & C Bk 40 mtr	50m 2280 LPM 50m Provided Provided	MR MR MR MR MR MR
	 Jockey Pump head Standby Pump output. Standby Pump head. Auto Starting/Manual Stopping. Pump house access. Terrace Level Discharge of pump. Head of pump. Power supply. 	50m 1620 LPM 50m Required Required A&B & C Bk 40 mtr Required	50m 2280 LPM 50m Provided Provided	MR MR MR MR MR MR
	 Jockey Pump head Standby Pump output. Standby Pump head. Auto Starting/Manual Stopping. Pump house access. Terrace Level Discharge of pump. Head of pump. Power supply. Auto starting of pump. 	50m 1620 LPM 50m Required Required A&B & C Bk 40 mtr	50m 2280 LPM 50m Provided Provided 540 LPM + 540 LPM 43.5m each	MR MR MR MR MR MR MR
L	 Jockey Pump head Standby Pump output. Standby Pump head. Auto Starting/Manual Stopping. Pump house access. Terrace Level Discharge of pump. Head of pump. Power supply. Auto starting of pump. Captive water storage for firefighting.	50m 1620 LPM 50m Required Required A&B & C Bk 40 mtr Required	50m 2280 LPM 50m Provided Provided 540 LPM + 540 LPM 43.5m each Provided	MR MR MR MR MR MR
1	 Jockey Pump head Standby Pump output. Standby Pump head. Auto Starting/Manual Stopping. Pump house access. Terrace Level Discharge of pump. Head of pump. Power supply. Auto starting of pump. Captive water storage for firefighting. Underground tank capacity. 	50m 1620 LPM 50m Required Required A&B & C Bk 40 mtr Required	50m 2280 LPM 50m Provided Provided 540 LPM + 540 LPM 43.5m each Provided Provided	MR MR MR MR MR MR MR MR MR
	 Jockey Pump head Standby Pump output. Standby Pump head. Auto Starting/Manual Stopping. Pump house access. Terrace Level Discharge of pump. Head of pump. Power supply. Auto starting of pump. Captive water storage for firefighting. Underground tank capacity. Draw-off connection. 	50m 1620 LPM 50m Required Required A&B & C Bk 40 mtr Required Required	50m 2280 LPM 50m Provided Provided 540 LPM + 540 LPM 43.5m each Provided Provided Provided	MR
! (Jockey Pump head Standby Pump output. Standby Pump head. Auto Starting/Manual Stopping. Pump house access. Terrace Level Discharge of pump. Head of pump. Power supply. Auto starting of pump. Captive water storage for firefighting. Underground tank capacity. Draw-off connection. Fire Service Inlet. 	50m 1620 LPM 50m Required Required A&B & C Bk 40 mtr Required Required 50,000 Ltr -NA-	50m 2280 LPM 50m Provided Provided 540 LPM + 540 LPM 43.5m each Provided Provided Provided Provided -NA-	MR M
-	 Jockey Pump head Standby Pump output. Standby Pump head. Auto Starting/Manual Stopping. Pump house access. Terrace Level Discharge of pump. Head of pump. Power supply. Auto starting of pump. Captive water storage for firefighting. Underground tank capacity. Draw-off connection. 	50m 1620 LPM 50m Required Required A&B & C Bk 40 mtr Required Required 50,000 Ltr -NANA-	50m 2280 LPM 50m Provided Provided 540 LPM + 540 LPM 43.5m each Provided Provided Provided -NANA-	MR M
1	 Jockey Pump head Standby Pump output. Standby Pump head. Auto Starting/Manual Stopping. Pump house access. Terrace Level Discharge of pump. Head of pump. Power supply. Auto starting of pump. Captive water storage for firefighting. Underground tank capacity. Draw-off connection. Fire Service Inlet. 	50m 1620 LPM 50m Required Required A&B & C Bk 40 mtr Required Required 50,000 Ltr -NA-	50m 2280 LPM 50m Provided Provided 540 LPM + 540 LPM 43.5m each Provided Provided Provided Provided -NA-	MR M

15	Exit Signage.	Required				
16	Provision of Lifts.	Required	Provided	MR		
	 Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. 	-NA-				
			-NA-	-NA-		
		-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
		Required	Provided	MR		
17	Standby Power Supply	-NA-	-NA-	-NA-		
18	Refuge Area	Required	Provided	MR		
				14110		
	Total areaLocation	-NA-	-NA-	-NA-		
		-NA-	-NA-			
19	Fire Control Room.		-11//-	-NA-		
	 Detector system panel. Flow switch panel. PA system panel. Battery backup. Building floor plan. 	-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
20	Savidary 1100r plan.	-NA-		-NA-		
20	Special Fire Protection System for the Protection of special Risk, if any.					

The fire protection system provided in the building / premises were test checked at random and found functional at the time of inspection. Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F.6/MS/DFS/2003/1428 dated 03/07/2003 (School) and F.6/MS/DFS/2004/670 dated 26/03/2004 (Auditorium), renewal under rule 37 of the Delhi Fire Service Rules 2010, is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Mehmood Design: ADO (SJ)

DO (SD)

plopean We T/2 men udu terting at basemets one